FXLuminaire.


LED Path Lights



The LED CA emmits a soft, efficient light for a variety of applications. Visually, it joins an austere appearance with a basic organic quality that compliments adjoining garden elements.

CA: Path Light

NUMBER OF LEDS:	1	3
HALOGEN LUMEN OUTPUT EQUIVALENT:	10 Watt	20 Watt
USEFUL LED LIFE (L70):	50,000 hrs avg	50,000 hrs avg
INPUT VOLTAGE:	10 to 15V	10 to 15V
VA TOTAL: (Use this number to size the transformer)	2.4	4.5
WATTS USED:	2.0	4.2
LUMENS PER WATT (EFFICACY)	19.4	25
MAX LUMENS:	39	103
CCT (Ra)	86	66.6



ORDERING INFORMATION

CA: Path Light

		OPTIONS (TOP ASSEM	BLIJ. OIUEI	ITZ				- Antique Pron*
Step	Description	Code						B = Antique Bronze* n Copper)
1	TOP ASSEMBLY							r = Antique Tumbled
2	TOP FINISH	AB*, AT*, CU, NP*, WG, FW,					(O	n Copper)
EXAM	IPLE: CALEDTA-AT	= CA Top Assembly - Antiq	ue Tumbled Fi	nish			CL	J = Copper
FACT	ORY INSTALLED	OPTIONS (RISER ASSE	MBLY): Orc	ler 1 + 2 (op	tional) + 3 -	- 4 + 5	ARCAL!	
Step	Description	Code					NF	P = Nickel Plate*
1	RISER TYPE	G					POWDER	COAT
2	OPTIONAL ZD	ZD (Refer to the Luxor pag	ge in the Light	ing Control see	ction)			
3	LAMP	1LED, 3LED (50,000 avg. 1	ife hours)				W	G = White Gloss
4	RISER HEIGHT	8RA, 12RA, 18RA, 24RA, 3	6RA (in inches	5)			FV	V = Flat White
5	FINISH	AB*, AT*, CU, NP*, WG, FW, AL, BZ, DG, WI, VF, SB, FB						
EXAM	PLE: G-ZD-3LED-1	8RA-AT = Riser Type - ZD C	ption - 3 LED	Board - 18" R	iser - Antique	Tumbled Finish	AI	= Almond
FIFI		TIONS: Order Individua	allv					
Mounting Options							BZ	Z = Bronze Metallic
Long Slot Spike (250015840000) 2.5" x 10" Included >				w	D	G = Desert Granite		
			Y	V	M			
	Slot Spike (753900)						W	I = Weathered Iron
SuperJ	I-Box (SJ-XX**) 2.5" >	(12"	V	▼	•	DestM		
Post M	lount (<i>PM-XX**</i>) 2.5"	' x 13"	Long Slot Spike	Super Slot Spike	Super J-Box XX**	Post Mount XX**	VF	= Verde Speckle
EXAM	IPLE: 753900 = Suj	per Slot Spike					CI.	3 = Sedona Brown
рнот	OMETRICS:						51	
							FE	I = Flat Black
CA 1LED ISOFOOTCANDLE PLOT CA 3LED ISOFOOTCANDLE PLOT 5 4 3 2 1 0 1 2 3 4 5 5 4 3 2 1 0 1 2 3 4 5								
	4		4					All CA path lights co standard with ambe
	3		3					green, blue and frosted filters
	1		1	$(\bigcirc$				
	0		0					udes choice of LED size, finish, 5 ft.
	1							
	12		2				leaa wire ar	nd Long Slot Spike
	123		3				ieda wire ar	nd Long Slot Spike
	1 2 3 4 5		3 4 5				Note: Only th	ne copper portions o
	1 2 3 4 5 0 0	fc 2.5 fc 0.2 fc Mount height: Ift fc 0.1 fc 0.1 fc Total LLF: 1 0.5 fc 0.5 KMax Candela	3 4 5 20 fc 10 fc	1 fc ≡0.1 fc Tot	unt height: 1ft tai LLF: 1 Ja		Note: Only th the path light	ne copper portions o
	1 2 3 4 5 2 0 0 10 0 5 10 0 5		3 4 5 20 fc 10 fc 5 fc		al LLF: 1		Note: Only th the path light	nd Long Slot Spike ne copper portions o ts are powder coate eces remain natural.

LED

FXLuminaire.