FXLuminaire.

LED Path Lights



The CB is a soft, efficient, and safe path light that can be used for pathways of all shapes, sizes, and locations. It's sleek hat shape gives it a more contemporary look that can accentuate landscapes that are trying to acheive a modern facade.

CB: Path Light

NUMBER OF LEDS:	1	3
HALOGEN LUMEN OUTPUT EQUIVALENT:	10 Watt	20 Watt
USEFUL LED LIFE (L70):	50,000 hrs avg	50,000 hrs avg
INPUT VOLTAGE:	10 to 15V	10 to 15V
VA TOTAL: (Use this number to size the transformer)	2.4	4.5
WATTS USED:	2.0	4.2
LUMENS PER WATT (EFFICACY)	19.4	25
MAX LUMENS:	39	103
CCT (Ra)	86	66.6



ORDERING INFORMATION

CB: Path Light

FACT	ORY INSTALLED	OPTIONS (TOP ASSEM	BLY): Orde	1+2			METAI	_S
Step	Description	Code						AB = Antique Bronze* (On Copper)
1	TOP ASSEMBLY	CBLEDTA						
2	TOP FINISH	TOP FINISH AB*, AT*, CU, NP*, WG, FW, AL, BZ, DG, WI, VF, SB, FB					AT = Antique Tumbled* (On Copper)	
		G = CB Top Assembly - Deser			tional) + 3 +	4 + 5		CU = Copper
Step	Description	D OPTIONS (RISER ASSEMBLY): Order 1 + 2 (optional) + 3 + 4 + 5 Code						NP = Nickel Plate*
1	RISER TYPE	G					POWD	ER COAT
2	OPTIONAL ZD	ZD (Refer to the Luxor page in the Lighting Control section)						
3	LAMP	1LED, 3LED (50,000 avg. life hours)					WG = White Gloss	
4	RISER HEIGHT	8RA, 12RA, 18RA, 24RA, 36RA (in inches)						FW = Flat White
5	FINISH	AB*, AT*, CU, NP*, WG, FW, AL, BZ, DG, WI, VF, SB, FB						
EXAMPLE: G-ZD-3LED-24RA-DG = Riser Type - ZD Option - 3 LED Board - 24" Riser - Desert Granite Finish							AL = Almond	
		TIONS: Order Individua	ally					BZ = Bronze Metallic
	iting Options	10000) 2.5" x 10" Included >			Ū	ω		DG = Desert Granite
Super	Slot Spike (753900)	2" x 10"		V	- M			
SuperJ	I-Box (SJ-XX**) 2.5" >	x 12"	↓	₩	↓			WI = Weathered Iron
Post M	lount (PM-XX**) 2.5'	" x 13"	Long Slot Spike	Super Slot Spike	Super J-Box XX**	Post Mount XX**		VF = Verde Speckle
EXAM	IPLE: 753900 = Su	per Slot Spike						SB = Sedona Brown
рнот	OMETRICS:							
CB 1LED ISOFOOTCANDLE PLOT CB 3LED ISOFOOTCANDLE PLOT								FB = Flat Black
	5 4 3 2 1 0		5 4 3 4 3 2 1 0		2 3 4 5			All CB path lights con standard with amber, green, blue and frosted filters includes choice of LED iser size, finish, 5 ft.

Beam angle is calculated using LM-79 method for SSL Luminaires: "Beam angle is defined as two times the vertical angle at which the intensity is 50% of the maximum." * May require longer lead time ** Denotes finish option

FXLuminaire.

LED

760.744.5240 | fxl.com

4/12