

VGBA-2017 PRODUCT SPECIFICATIONS


Suction Outlet Fitting Assembly (SOFA)

VGBA-2017 Flow Ratings, Sump Dimensions, Sump Flow Path Zone, and Head Loss Curves



DIRECTIONS: Please follow the SOFA specific flow rates, sump specifications, and flow path zone information below. The installation must conform to these minimum/maximum requirements including the SOFA dimension defined in Figure 1. The flow path zone is defined by dimensions A through E. The installed sump may be manufactured or field-built and it may be larger/deeper than Figure 1. Please write the Cover Model Number, orientation, and SOFA Model Flow Rating on the *VGBA DRAIN COVER IDENTIFICATION INFORMATION* label that comes with each AquaStar Pool Products, Inc. drain cover.

Cover Model Number: R12MFxxx



FOR MOST CURRENT INFORMATION
SCAN THE QR CODE OR VISIT

WWW.AQUASTARPOOL.PRODUCTS.COM/FLOWCODE
PRINTED DOCUMENTS MAY NOT HAVE THE MOST CURRENT FLOW
RATINGS OR INSTALLATION OPTIONS.



SOFA Model No.	Pipe Size (Nominal)	Pipe Depth (Minimum)	Orientation (Wall / Floor)	Flow Rating (GPM)	Head Loss Curve
R12MF-12f_A-1.5b_B3_C0.3_D0.7_E3.5_F16	1.5" (b)	3"	Floor (f)	126	А
R12MF-12f_A-2b_B3_C0.3_D0.7_E5.5_F16	2" (b)	3"	Floor (f)	120	В
R12MF-12f_A-2b_B6_C0.3_D0.7_E3_F16	2"(b)	6"	Floor (f)	150	С
R12MF-12f_A-2.5b_B3.1_C0.3_D0.7_E3.5_F16	2.5" (b)	3.1"	Floor (f)	160	D
R12MF-12f_A-3b_B3_C0.3_D0.7_E4_F16	3" (b)	3"	Floor (f)	250	E
R12MF-12f_A-3s_B6_C0.3_D0.7_E3_F16	3"(s)	6"	Floor (f)	320	F
R12MF-12f_A-3s,2b_B6_C0.3_D0.7_E3_F16	3"(s),2"(b)	6"	Floor (f)	400	G
R12MF-12f_A-4b_B3_C0.3_D0.7_E3.75_F16	4" (b)	3"	Floor (f)	400	Н
R12MF-12f_A-4s_B6_C0.3_D0.7_E3_F16	4" (s)	6"	Floor (f)	500	I
R12MF-12f_A-4s,2.5b_B6_C0.3_D0.7_E3_F16	4"(s), 2.5" (b)	6"	Floor (f)	496	J
R12MF-12f_A-6b_B3_C0.3_D0.7_E3_F16	6" (b)	3"	Floor (f)	420	K
R12MF-12f_A-6b_B10.5_C0.3_D0.7_E3_F16	6" (b)	10.5"	Floor (f)	496	L
R12MF-12w_A-1.5b_B3_C0.3_D0.7_E3.5_F16	1.5" (b)	3"	Wall (w)	126	М
R12MF-12w_A-2b_B3_C0.3_D0.7_E3.5_F16	2" (b)	3"	Wall (w)	150	N
R12MF-12w_A-2.5b_B3_C0.3_D0.7_E4.7_F16	2.5" (b)	3"	Wall (w)	200	0
R12MF-12w_A-3b_B3_C0.3_D0.7_E4_F16	3" (b)	3"	Wall (w)	230	Р
R12MF-12w_A-4b_B3_C0.3_D0.7_E3.75_F16	4" (b)	3"	Wall (w)	360	Q
R12MF-12w_A-6b_B10.5_C0.3_D0.7_E3_F16	6" (b)	10.5"	Wall (w)	496	R

Note 1: "SOFA Model No" nomenclature; bottom pipe = (b), side pipe = (s). See Fig 1 for capital letters A through E

Note 2: Head loss in Hg is measured 16 to 24 inches from the finish surface of the pool. Reference Fig 1 dimension F.

