

Brilliant Wonders[®]

LED LIGHTING



1.5" NICHELESS LED
POOL & SPA LIGHT

CMP POOL
PRODUCTS

BRILLIANT LED POOL & SPA LIGHTING . . .



SIMPLE INSTALLATION & SERVICE

Installs in any 1.5" pool wall fitting and locks in place with a quarter-turn. Uses an industry-first quick disconnect IP68 connection for rapid service, winterizing or replacement.



HIGH PERFORMANCE. ENERGY EFFICIENT.

Precise engineering delivers a perfect balance of brightness, energy savings and longevity. Over 50,000 hours of low voltage LED life saves customers money and reduces service calls.



BUILT-IN CMP SMART SYNC™ TECHNOLOGY

Available with Smart Sync programming to synchronize with lighting and controls from major pool OEMs.



THE PERFECT DESIGN FOR ANY POOL

Choose the right fitting for the perfect look in any pool. For gunite pools, the flush fitting creates the most seamless 1.5" LED light install on the market. For vinyl and fiberglass, faceplates in fifteen different styles completely disguise the wall fitting.

The Brilliant Wonders® 1.5" nicheless LED pool and spa light is versatile, easy to install and designed to sell. Create a sense of drama and excitement in any pool with bright LED light and colorful shows. Illuminate a pool, accent a spa or showcase steps, swim-outs and spillovers. Unleash your creativity with this designer LED light that is sized to fit in virtually any location. With so much to offer in one light, the next pool you build should be brilliant.

PRODUCT FEATURES

- Bright & Efficient Cree® LEDs Outlast and Outperform Other Lights
- RGBW LED Design for True White Performance
- Installs in Gunite, Fiberglass & Vinyl Pools
- Non-Metallic Design: No Bonding, No Grounding
- Heat-Conductive Body Increases LED & Electronics Life
- Soft Light Falloff: Smooth Blending, Soft Shadows, No Hard Edges
- Full Color, Full Stainless and Color Accent Stainless Faceplate Options
- Small Size can Retro-fit and Replace Almost Any Nicheless Light

... HIGH PERFORMANCE NICHELESS DESIGN



Quick
Disconnect



Installation
Multi-tool

TECHNICAL GUIDE

- ETL Certified
- Available in 11, 8 & 5 watt configurations
- Nicheless non-metallic design; no bonding; no grounding
- Standard model includes nine colors & five light shows
- 12V AC transformer required (not included)
- 140 degree beam angle
- Water-cooled with heat conductive PPS body
- Available in color or white LED styles
- 4" minimum water depth
- Wall or floor installation
- Install in most 1.5" wall fittings (vinyl, fiberglass or gunite)
- Durable, bayonet-style quarter turn installation
- 4.5" body with 6" watertight quick disconnect IP68 cord
- Synchronize with other popular pool OEM lighting systems



Stainless Steel
Color Accent

Stainless
Steel

Full Color
Plastic

Gunite
Flush Fitting

BRILLIANT WONDERS® 1.5" LED LIGHT ORDERING GUIDE

- Select light kit.** Available in four cord lengths and three LED styles. Each kit includes LED light, white faceplate OR flush fitting & multi-tool.
- Smart Sync:** Order to match CMP or other OEM lighting.
- Select custom faceplate. (Optional)**

BRILLIANT WONDERS® 1.5" LED LIGHT

25 FT KIT	50 FT KIT	100 FT KIT	150 FT KIT	DESCRIPTION	WATTS
25503-560-025	25503-560-050	25503-560-100	25503-560-150	11C RGBW COLOR LIGHT KIT	11W
—	—	25503-568-109	25503-568-159	11C RGBW COLOR LIGHT KIT (FLUSH)	11W
25503-520-025	25503-520-050	25503-520-100	25503-520-150	8C RGBW COLOR LIGHT KIT	8W
—	—	25503-528-109	25503-528-159	8C RGBW COLOR LIGHT KIT (FLUSH)	11W
25503-500-025	25503-500-050	25503-500-100	25503-500-150	BRILLIANT WHITE LIGHT KIT	5W

For H-Style or P-Style lighting, simply append the CMP part number with "H" or "P"

SMART SYNC™ TECHNOLOGY

P/N GUIDE	DESCRIPTION
25503-XXX-XXX	CMP / J-STYLE - NO CHANGE TO PART NUMBER
25503-XXX-XXXH	H-STYLE LIGHTING - ADD "H" TO PART NUMBER
25503-XXX-XXXP	P-STYLE LIGHTING - ADD "P" TO PART NUMBER

A



Full Color
Plastic

B



Stainless
Steel

C



Stainless Steel
Color Accent

D



Clear
Flush Fitting

BRILLIANT WONDERS® 1.5" LED LIGHT FACEPLATES

REF	WHITE/OTHER	GRAY	BLACK	DARK GRAY	LIGHT BLUE	DARK BLUE	TAN
A	25503-510-000	25503-511-000	25503-514-000	25503-517-000	25503-559-000	25503-569-000	25503-519-000
B	25503-510-200	—	—	—	—	—	—
C	25503-510-220	25503-511-220	25503-514-220	25503-517-220	25503-559-220	25503-569-220	25503-519-220
D	25503-519-300	—	—	—	—	—	—