

IPS-M820



M820 Automated pH and ORP Controller

Application: Commercial and Custom Residential

Maintain consistent pH and sanitizer levels through out the day, assuring the chemicals are balanced and the water is clean and clear.

Automatically monitor, adjust and dispense the correct amount of chemicals based on user demand.

Perfect for pools, spas and water features of all sizes, anywhere—hotels, condominiums, aquatic centers, schools, public facilities, homes and more.

Our IPS M820 offers automated control of pH with the convenience of the unique dual ORP, allowing operators to install multiple output devices on the same pool. With dual ORP, you can use a primary sanitizer, such as salt chlorine generator, with a secondary sanitizer, such as liquid chlorine, for rapid response to increased bather load. The second ORP may also be used as a safety backup (second pump and tank) for liquid systems.

Quick and simple to operate, easy installation right out of the box and system set up takes just minutes. It's rare, but if technical support is needed, we are just a phone call away.

Specifications

- ✓ pH set level 7.0- 8.0
- ✓ ORP set level 400-900
- ✓ Default high/low alert settings
- ✓ Readout – LED with digital display
- ✓ Alarm – LED alert display
- ✓ Push button overfeed adjustment
- ✓ Push button high/low alert adjustment
- ✓ Dose Rate – timed or continuous
- ✓ Electrical Input/Output 110 VAC
- ✓ Electrical Input/Output 230 VAC
- ✓ Electrical Output 110V, 230V, & Dry Contact
- ✓ System pre-mounted on 16"x12" hanging board
- ✓ Compatible with all sanitizing methods
- ✓ Delay time – 1-99 minutes
- ✓ Tank level inputs – 2
- ✓ Lock-out feature
- ✓ Can be used with Muriatic Acid or CO2
- ✓ Chemical pump option
- ✓ Gold-tipped ORP probe for salt pools (required)
- ✓ Dual ORP, for secondary sanitizer or backup for liquid systems
- ✓ Accessories available
- ✓ NSF Certified for the highest level of code compliance 
- ✓ 5-year limited warranty; Made in the USA
- ✓ Web-based remote monitoring is an available option
- ✓ Web-based remote programming is an available option
- ✓ Temperature monitoring and display is an available option
- ✓ External visual and audible alarm is an available option

Need a custom product or more information? Email or Call 877-693-6903.

IPS-M820 Data Sheet Revised 12/14

www.ipscontrollers.com Phone: 877-693-6903
Email: info@ipscontrollers.com Fax: 951-693-3224
26111 Ynez Road, Suite C-4, Temecula, CA 92591

