



Type 2551 Magmeter; Display Version no relays Current output (4 to 20 mA)

Flow:

- Installs into pipe sizes: DN15 to DN900, 0.5 to 36 in
- Operating range: 0.05 to 10 m/s, 0.15 to 33 ft/s
- Max Pressure rating: PP 10.3 bar @ 25 °C, 150 psi @ 77 °F
- Power source: 4 to 20mA: 21.6 to 26.4 VDC, 22.1mA max
- *Only Signet installation fittings

MFR #	Body	Electrode	Pipe Size (inch)	Sensor Type	Code
3-2551-P0-42	PP	316L SS	0.5 - 4.0	-X0	159 001 279
3-2551-P1-42	PP	316L SS	5.0 - 8.0	-X1	159 001 280
3-2551-P2-42	PP	316L SS	10.0 - 36.0	-X2	159 001 441
3-2551-T0-42	PVDF	Titanium	0.5 - 4.0	-X0	159 001 442
3-2551-T1-42	PVDF	Titanium	5.0 - 8.0	-X1	159 001 443
3-2551-T2-42	PVDF	Titanium	10.0 - 36.0	-X2	159 001 461
3-2551-V0-42	PVDF	Hastelloy C	0.5 - 4.0	-X0	159 001 281
3-2551-V1-42	PVDF	Hastelloy C	5.0 - 8.0	-X1	159 001 282
3-2551-V2-42	PVDF	Hastelloy C	10.0 - 36.0	-X2	159 001 463

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: info.ps@georgfischer.com

Internet: <http://www.gfps.com>