



91392 FEATURES

- Energy efficient 1/3 HP split capacitor motor.
- Lower amp draw, runs cooler, lasts longer
- Stainless steel construction
- Hermetically sealed, oil cooled motor for long pump life
- Stainless steel impeller
- 1-1/4" NPT top discharge
- Motor is thermally protected with automatic reset thermal protector
- Stainless steel motor shaft
- Stainless steel fasteners
- Large intake screen
- Bottom screen removes easily for cleaning
- Pumps down to 1/8" from surface with removable thermoplastic pump base
- Acceptable for indoor or outdoor use
- Compact, lightweight design is easily portable
- Every unit is 100% pressure tested



1 YEAR WARRANTY

3300 GALLONS PER HOUR










230584

91392 - Application

Submersible utility pur	p for general water transfer				
Motor Specifications					
Horsepower	1/3 HP				
Voltage	120				
Amps	6				
Hertz	60 Hz				
Phase	Single				
RPM	3450 RPM				
Motor Type	Permanent Split Capacitor (PSC)				
Insulation	Class A				
Circuit Requirements	15 amp (min) individual circuit				
Duty Rating	Continuous				
Shaft Seal	Carbon/ceramic and stainless steel				
Motor Shaft	Stainless Steel				
Upper Motor Bearing	Ball Bearing				
Lower Motor Bearing	Ball Bearing				
Motor Protection	Auto reset thermal overload protector				

MOTOLLIA	Auto reset thermal overload protector				
Pump Specifications	3				
Discharge Size	1-1/4" NPT				
Cord Length	25'				
Cord Type	SJTW, UL listed, 3-wire, 18 gauge				
Pump Housing	Stainless Steel				
Pump Base	Stainless Steel				
Impeller Material	Stainless Steel				
Impeller Type	Non-clogging				
Gasket	Buna-N				
Solids Handling	3/8" spherical				
Liquid Temp. Range	32°- 120° F				
Operation	Non-automatic				
Fasteners	Stainless steel				
Max Flow Rate	55 Gallons per minute				
Maximum Head	30 feet				
Max Pressure	10.8 psi				
Weight	12.65 lbs				
Pumps down to	1/2" From surface				
With removable thermoplastic base, pumps down to	1/8" From surface				

Performances



Discharge Height	0′	5′	10′	15′	20′	25′	30′
Gallons Per Minute	55	49	40	30	22	11	0
Gallons Per Hour	3300	2940	2400	1800	1320	660	0

Dimensions

