

SECTION V – HEALTH HAZARD DATA

Effects of Overexposure:

Vapor odors may cause irritation in the upper and lower respiratory tracts, nausea, headaches, and dizziness. Eye contact can cause irritation, redness and tearing. Skin Contact can cause minor irritation. Ingestion can cause nausea, vomiting, diarrhea and gastrointestinal irritation.

Medial Conditions Prone to Aggravation by Exposure:

Overexposure to vapors can produce headaches, dizziness and nausea.

Primary Route(s) of Entry: Inhalation, Ingestion.

Emergency and First Aid Procedures:

If affected by vapors, move person to fresh air. Apply artificial respiration to person who loses consciousness and call a doctor immediately. Treat eye and skin contact by thoroughly washing with clean water. If irritation persists, see a doctor immediately. If material is ingested and the person is conscious, give two glasses of water to drink and call a doctor immediately.

SECTION VI – REACTIVITY DATA

Stability: Stable

Hazardous Polymerization: Will not occur.

Hazardous Polymerization is not established.

Hazardous Decomposition Products:

Burning can produce carbon dioxide and/or carbon monoxide.

Conditions to Avoid:

Avoid temperatures below 40 degrees Fahrenheit. Avoid freezing conditions.

Incompatibility (Materials To Avoid):

Avoid materials that react with water, also strong acids and alkalis.

SECTION VII – SILL OR LEAK PROCEDURES

Steps To Be Taken In Case Material Is Released or Spilled:

Dike and absorb spilled material with inert absorbent material such as sand, earth and sawdust. Use rags to clean up small amounts of spilled material.

Waste Disposal Method:

Collect material-contaminated absorbent and rags into a disposable container and dispose of in accordance to local, state and federal regulations. Consult with your local hazardous waste regulations regarding landfill dumping.

SECTION VIII – SAFE HANDLING AND USE INFORMATION

Respiratory Protection:

Wear approved organic vapor respirator unless ventilation equipment is adequate to keep airborne concentrations below the exposure standards.

Ventilation:

General mechanical ventilation may be sufficient to keep product vapor concentration below specified TLV ranges. If inadequate, use local exhaust.

Protective Gloves:

Use impermeable solvent resistant gloves to protect from skin contact.

Eye Protection:

Use safety goggles, chemical safety glasses and/or face shields to protect eyes.

Other Protective Equipment:

Impermeable aprons and protective clothing are advised when working with this product. The use of head caps is recommended whenever possible.

Hygienic Practices:

Eye washes and safety showers in the workplace are recommended

SECTION IX – SPECIAL PRECAUTIONS

Precautions To Be Taken In Handling And Storing:

Keep containers closed when not in use. Do not store or handle near heat, flames and strong oxidants. Store in cool well ventilated area. Rotate stock, use older materials first. Inspect for leaks in all containers.

Other Precautions:

Do not store in freezing areas. Keep above 40 degrees Fahrenheit. Keep out of reach of children.

****DISCLAIMER – The information contained herein, is based on data considered accurate. However, no warranty, whether expressed or implied.****