

Baptismal Equipment System

BES-55 Series

STANDARD FEATURES

Full Range Thermostat
High Limit Protected
Pressure Switch Activated
Pump Air switch
Bonding Lug & Wire
Heater Indicator Light
Base
15A GFCI Cord (BES-15 Only)
Installation Kit (see below)
Detailed Owner's Manual & Wiring Diagram
UL Listed



BES-55 SYSTEM

BAPTISMAL EQUIPMENT SYSTEMS BY MODEL

MODEL	Voltage	Htr Wattage	Pump
BES-15	120	1.375KW	120
BES-55	120/208/240*	5.5KW	120
BES-55-3W	240**	5.5KW	240
BES-11	208/240*	11KW	120
BES-11-3W	240**	11KW	240

INSTALLATION KIT INCLUDED



The BES-55 Series is our newest Baptismal Equipment System. It is a vertically mounted circulation style baptistry heater system. Simple, compact design for easy installation and it's a great replacement for all existing vertical circulation style systems. Hydro-Quip has been producing reliable Spa & Baptismal Systems for over 30 years and we understand the importance of safety and reliability. That's why we take pride in manufacturing an efficient and quality system that churches can depend on. We have various configurations to choose from for all of your Baptismal needs.

From the ease of installation, to the efficiency of our products and exclusive troubleshooting features, your customers will be glad you made the "Smart Choice" in choosing equipment produced by Hydro-Quip, the industry's oldest and most trusted manufacturer.

APPROVAL LISTINGS:

UL LISTED, INDOOR ONLY, UI1563

ELECTRICAL SPECIFICATIONS:

SINGLE PHASE

50/60HZ *4-Wire

**3-Wire

MINIMUM SPACE REQUIRED:

36"H X 16"W X 10"D

TOTAL AMP DRAW:

BES-15	18A
BES-15	18A
BES-11	52A

DIMENSIONS:

BES-15	29"H X 15"W X 9"D
BES-55	29"H X 15"W X 9"D
BES-11	35.25"H X 15"W X 9"D

SHIPPING WEIGHT:

Offil I INO WEIGHT.		
BES-15	23 LBS.	
BES-55	23 LBS.	
BES-11	25 LBS.	