



PRISM

< Halogen PAR

PRISM Halogen PAR

Halco
LIGHTING TECHNOLOGIES

Energy Efficient

- Increased lumens per watt compared to incandescent lamps

Technical Data

- 120 and 130 volt designs
- Heavy-duty 2-piece construction
- Multi-support CC-8 filament
- Nickel-plated brass base

Long Life

- 3,000 Hours Average Rated Life

Benefits

- Crisp, white light
- Increased lumens per watts
- Frosted lamps provide soft light without shadows

Applications

- Retail/display lighting
- Accent lighting
- Office building and residential lighting

Spiral lens eliminates striations to provide a consistent, smooth beam pattern.

Call Halco today and get a great look at our vast product line, personal service and fast delivery. Visit us at halcolighting.com.

Your account representative is your single source for pricing, orders and technical support.

Shipping from Atlanta, Cleveland, Houston and Phoenix.

ISO 9001 Certified

where there's light,
there's halco®

(800) 677-3334
halcolighting.com

Bulb Type	Watts	Base	Item #	Product Code	Description	Pkg/ Qty	Volts	Initial Lumens	Avg Rated Life	Filament Design	MOL (Inches)	Beam Spread
PAR14												
PAR14	35	Med.	107548	HP14FL35	Flood	10/40	130	300	3000	CC-8	2.4"	50°
PAR16												
PAR16	45	Med.	107502	HP16NFL45	Narrow Flood	15	130	500	3000	CC-2V	3.3"	30°
PAR16	60	Med.	107616	HP16NFL60	Narrow Flood	15	130	680	3000	CC-8	3.3"	30°
PAR16	60	Med.	107850	HP16NFL60/120	Narrow Flood	15	120	680	3000	CC-8	3.3"	30°
PAR16	60	Med.	107504	HP16NSP60	Narrow Spot	15	130	680	3000	CC-8	3.3"	10°
PAR20												
PAR20	35	Med.	107610	HP20NFL35	Narrow Flood	15	130	450	3000	CC-8	3.3"	30°
PAR20	50	Med.	107660	HP20NFL50/120	Narrow Flood	15	120	560	3000	CC-8	3.3"	30°
PAR30												
PAR30	50	Med.	70202	HP30NFL50 [ⓔ]	Narrow Flood	15	130	660	3000	CC-8	3.6"	25°
PAR30	75	Med.	107633	HP30FL75 [ⓔ]	Flood	15	130	1150	3000	CC-8	3.6"	40°
PAR30	75	Med.	107634	HP30FL75L [ⓔ]	Flood Long Neck	15	130	1100	3000	CC-8	4.8"	40°
PAR30	75	Med.	107672	HP30FL75L/120 [ⓔ]	Flood Long Neck	15	120	1100	3000	CC-8	4.8"	40°
PAR30	75	Med.	107542	HP30SP75L [ⓔ]	Spot Long Neck	15	130	1100	3000	CC-8	4.8"	10°
PAR38												
PAR38	45	Med.	107564	HP38FL45 [ⓔ]	Flood	15	130	500	3000	CC-8	5.4"	30°
PAR38	45	Med.	107690	HP38FL45/120 [ⓔ]	Flood	15	120	500	3000	CC-8	5.4"	30°
PAR38	60	Med.	107568	HP38FL60 [ⓔ]	Flood	15	130	800	3000	CC-8	5.2"	30°
PAR38	90	Med.	107644	HP38FL90 [ⓔ]	Flood	15	130	1350	3000	CC-8	5.2"	30°
PAR38	100	Med.	70402	HP38FL100 [ⓔ]	Flood	15	130	1500	3000	CC-8	5.2"	30°

[ⓔ] Means this lamp meets Federal Minimum Efficiency Standards.