



**PRISM** MR11



**Technical Data**

- Cool beam dichroic reflector
- Protective glass lens for operation in open or enclosed fixtures
- 24 volt lamps use half the current of 12 volt systems, allowing higher wattage loads and up to twice as many lamps on one transformer
- Integrated UV protection
- High lumen maintenance, greater than 90% throughout lamp life

**Benefits**

- Compact light source
- White light
- Greatly reduces fading caused by UV exposure

- » 2900K, white light
- » Protective glass lens
- » UV protection

**Markets:**

- Residential
- Commercial

**Applications:**

- Display lighting
- Accent lighting
- General lighting
- Decorative lighting

where there's light, there's halco®

Contact your account representative at 800.677.3334 for pricing, orders and technical support.

Visit us at [halcolighting.com](http://halcolighting.com)

## Ordering Information

Watt	Base	Product #	Product Code	Description	Volts	Color Temp.	CBCP	Filament Design	Avg. Life	Pkg. Qty.	Beam Spread	MOL
<b>MR11 GU4</b>												
5 Watt	GU4	107516	MR11FL5/L	Flood w/Lens	12V	2950	80	C-6	2000	10/200	30°	1.38"
10 Watt	GU4	107940	MR11FL10/L	Flood w/Lens	12V	2900	300	C-6	2000	10/200	30°	1.38"
10 Watt	GU4	107114	MR11SP10/L	Spot Flood w/Lens	12V	2900	2500	C-6	3000	10/200	30°	1.38"
20 Watt	GU4	107100	MR11FTB/L	Narrow Spot w/Lens	12V	2900	5500	C-6	3000	10/200	10°	1.38"
20 Watt	GU4	107102	MR11FTC/L	Medium Flood w/Lens	12V	2900	1750	C-6	3000	10/200	20°	1.38"
20 Watt	GU4	107104	MR11FTD/L	Narrow Spot w/Lens	12V	2900	700	C-6	3000	10/200	30°	1.38"
35 Watt	GU4	107106	MR11FTE/L	Narrow Spot w/Lens	12V	2900	4600	C-6	3000	10/200	10°	1.38"
35 Watt	GU4	107108	MR11FTF/L	Medium Flood w/Lens	12V	2900	2400	C-6	3000	10/200	20°	1.38"
35 Watt	GU4	107110	MR11FTH/L	Flood w/Lens	12V	2900	1500	C-6	3000	10/200	30°	1.38"
<b>MR11 TWIST-LOCK</b>												
20 Watt	Ba15d	107101	MR11FTB/L/TL	Narrow Spot w/Lens Twist Lock	12V	2900	5500	C-6	3000	10/200	30°	1.77"
20 Watt	Ba15d	107103	MR11FTC/L/TL	Medium Flood w/Lens Twist Lock	12V	2900	1750	C-6	3000	10/200	20°	1.77"
20 Watt	Ba15d	107105	MR11FTD/L/TL	Flood w/Lens Twist Lock	12V	2900	700	C-6	3000	10/200	30°	1.77"
35 Watt	Ba15d	107456	MR11FTF/L/TL	Medium Flood w/Lens Twist Lock	12V	2900	2400	C-6	3000	10/200	20°	1.65"
<b>MR11 GU10</b>												
20 Watt	GU10	107544	MR11FL20/L/GU10	Flood w/Lens	120V	3000	220	CC-2V	2000	10/200	30°	1.38"
35 Watt	GU10	107546	MR11FL35/GU10	Flood w/Lens	120V	2850	560	CC-2V	2000	10/100	30°	1.38"