

# DIVERTER VALVES



Size:	1 1/2" - 2" - 2 1/2" spigot
Material:	CPVC body black, Glass filled Noryl rotor, ABS handle, NSF 61
O-Rings:	NITRILE
Rotor Seal:	High temperature silicone gasket with teflon jacket
Pressure Rating:	50 PSI
Positive seal back pressure:	15 PSI
Vacuum Rating:	29" Mercury

## FEATURES:

- High heat lid that will not warp in the sun
- Proportional mixing availability.
- Double O-ring shaft seal.
- Permanently lubricated rotor seal with extreme wear resistance, exceeds 3000 dry cycle requirement.
- Chlorine, acid and ozone resistant construction.
- Handle-locking knob provides eye-let for lock attachment.
- Engineered "PLAST-TITE" screws ( 18.8 stainless) will not crack plastic when servicing valve.
- Universal shaft spline pattern adapts to most actuators.
- All wetted materials are of NSF-50 or 61 designation.
- **patented design us 6497250**



OV2-2010

## CPVC BODY



NOTE: VISIT [www.nsf.org](http://www.nsf.org) FOR UPDATED LISTINGS

SIZE	MODEL #	DESCRIPTION	LIST PRICE	QTY. PER CARTON
1 1/2" - 2"	OV2-1500	2-Way Diverter Valve, Slip (1.5" ID, 2" OD)	\$52.75	12
1 1/2" - 2"	OV2-1590	90° 2-Way Diverter Valve, Slip (1.5" ID, 2" OD)	\$54.59	12
1 1/2" - 2"	OV3-1500	3-Way Diverter Valve, Slip (1.5" ID, 2" OD)	\$59.94	12
1 1/2"	OV3-1503	3-Way Diverter Valve, FPT	\$62.93	12
2" - 2 1/2"	OV2-2000	2-Way Diverter Valve, Slip, C/W 1.5" Reducer Bushings (2" ID, 2.5"	\$57.55	12
2" - 2 1/2"	OV2-2010	2-Way Diverter Valve, Slip (2" ID, 2.5" OD)	\$55.62	12
2" - 2 1/2"	OV2-2090	90° 2-Way Diverter Valve, Slip (2" ID, 2.5" OD)	\$57.68	12
2" - 2 1/2"	OV3-2000	3-Way Diverter Valve, Slip, C/W 1.5" Reducer Bushings (2" ID, 2.5" OD)	\$69.01	12
2" - 2 1/2"	OV3-2010	3-Way Diverter Valve, Slip (2" ID, 2.5" OD)	\$63.40	12

## NEW\*

SIZE	MODEL #	DESCRIPTIO	LIST PRICE	QTY. PER CARTON
1 1/2"	OV3-1500-NP	3-Way Diverter Valve, Slip, Soloar By-Pass	\$63.14	12
2" - 2 1/2"	OV3-2010-NP	3-Way Diverter Valve, Slip, Soloar By-Pass (2" ID, 2.5" OD)	\$66.46	12