

VGBA-2017 PRODUCT SPECIFICATIONS Suction Outlet Fitting Assembly (SOFA) VGBA-2017 Flow Ratings, Sump Dimensions, Sump Flow Path Zone, and Head Loss Curves




DIRECTIONS: Please follow the SOFA specific flow rates, sump specifications, and flow path zone information below. The installation must conform to these minimum/maximum requirements including the SOFA dimension defined in Figure 1. The flow path zone is defined by dimensions A through E. The installed sump may be manufactured or field-built and it may be larger/deeper than Figure 1. Please write the Cover Model Number, orientation, and SOFA Model Flow Rating on the VGBA DRAIN COVER IDENTIFICATION INFORMATION label that comes with each AquaStar Pool Products, Inc. drain cover.



FIGURE 1 – SOFA MODEL & FLOW PATH

WWW.AQI
PRINTED
PRINTED
FL



FOR MOST CURRENT INFORMATION


SCAN THE OB CODE OB VISIT

SOFA Model No.		Pipe Size (Nominal)	Pipe Depth (Minimum)	Orientation (Wall / Floor)	Flow Rating (GPM)	Head Loss Curve
CC10-10f_A-1.5b_B3_C0.4_D0.5_E2.5_F16		1.5" (b)	3"	Floor (f)	80	А
CC10-10f_A-2b_B3_C0.4_D0.5_E3.9_F16		2" (b)	3"	Floor (f)	106	В
CC10-10f_A-2.5b_B3_C0.4_D0.5_E3.8_F16		2.5" (b)	3"	Floor (f)	119	С
CC10-10f_A-3b_B3_C0.4_D0.5_E3.5_F16		3" (b)	3"	Floor (f)	156	D
CC10-10f_A-4s_B5.2_C1.1_D1.2_E2.5_F16	[Sump P/N 10-3SB]	4" (s)	5.2"	Floor (f)	200	E
CC10-10w_A-1.5b_B3_C0.4_D0.5_E2.5_F16		1.5" (b)	3"	Wall (w)	80	F
CC10-10w_A-2b_B3_C0.4_D0.5_E3.9_F16		2" (b)	3"	Wall (w)	106	G
CC10-10w_A-2.5b_B3_C0.4_D0.5_E3.8_F16		2.5" (b)	3"	Wall (w)	119	н
CC10-10w_A-3b_B3_C0.4_D0.5_E3.5_F16		3" (b)	3"	Wall (w)	156	I
CC10-10w_A-4s_B5.2_C1.1_D1.2_E2.5_F16	[Sump P/N 10-3SB]	4" (s)	5.2"	Wall (w)	200	J


Note 1: "SOFA Model No" nomenclature; bottom pipe = (b), sde pipe = (s). See Fig 1 for capital letters A through E

Note 2: Head loss inHg is measured 16 to 24 inches from the finish surface of the pool. Reference Fig 1 dimension F.





© 2021 AquaStar Pool Products. Inc. All rights reserved.



11012021