

# PSH040 4" Straight Hat Path Light

Stainless Steel

# **Fixture Ordering Guide**

| Product<br>Code | Finish               | Stem |
|-----------------|----------------------|------|
| PSH040          | SS - Stainless Steel | 12"  |
|                 |                      | 15"  |
|                 |                      | 18"  |

JC20 Halogen lamp shipped with fixture. To substitute a ProLED® lamp, add lamp product code

Example: PSH040-SS-15-JC20/2WW/LED

# Housing:

- Stainless Steel construction
- Underside of 4" diameter hat is coated with white reflective paint for optimum output and diffusion
- Stepped, threaded brass collar for tool-less attachment and easy relamping
- Clear 4mm thick lens protects the lamp

## Stem:

• 7/8" diameter stem provides solid, stable mounting

# Finish:


• Stainless Steel

### Socket:

- Ceramic G4 bi-pin socket
- Heat-resistant wire leads

#### Lamp:

- T3-G4 bi-pin 20W maximum
- ProLED® JC lamps provide up-to 40,000 hour rated life, 10-18V input voltage range and 3000K, amber, blue, green and red color options
- ProLED® IP65 Rated JC lamps are rated for use outdoors where exposed directly water from rain or irrigation



Product:



# Mounting:

• 8" black ground stake included

## **Electrical:**

- 12 Volt system
- Pre-wired with 36", 18-2 lead wire
- Two King® DryConn™ waterproof connectors included

# **Certifications:**

• ETL Listed to UL Standard 1838 and CSA C22.2 No. 12-1982

#### Warranty:

- Backed by a lifetime limited warranty to be free from defects in material and/or workmanship
- ProLED® IP65 Rated JC lamps installed in Sollos fixtures per installation instructions are backed by a 20-year limited warranty

## **Photometrics:**

