

In-Ground Rock Guard Cover

Natural Metal Composite Black

Fixture Ordering Guide

Product Code	Finish
IGG049	AB - Antique Brass
	BR - Brass
	CB - Composite Black
	SS - Stainless Steel

Order Lamp Separately

Example: IGG049-AB-MR16BAB/827/LED

Housing:

- Single-piece compression molded fiberglass reinforced polyester composite
- Silicone o-ring provides a watertight seal

Cover:

• Antique Brass, Brass, Composite Black or Stainless Steel

Lens

Shock and heat-resistant clear, tempered glass

Socket:


- Ceramic GU5.3 bi-pin socket
- Stainless steel retention clip ensures secure lamp seating and protects the lamp from shock and vibration
- Heat-resistant wire leads

Lamp:

- MR16 57W maximum
- ProLED® MR16 lamps offer 40,000 hour rated life, 10-15V input voltage range, multiple beam spreads (flood, narrow flood, spot and wide flood) and 2700K, amber, blue, green, red and color changing options









Electrical:

- 12 Volt system
- Pre-wired with 36", 18-2 lead wire
- Two King® DryConn™ waterproof connectors included

Certifications:

• ETL Listed to UL Standard 1838 and CSA C22.2 No. 250.7

Fasteners:

• All fasteners are corrosion-resistant stainless steel

Warranty:

- Backed by a lifetime (Brass and Stainless Steel) or 10-year (Composite) limited warranty to be free from defects in material and/or workmanship
- ProLED® MR16 lamps installed in Sollos fixtures per installation instructions are backed by a 20-year limited warranty

Photometrics:

