



COPPER-FIN II[®] POOL HEATER PRODUCT SUMMARY

(CP) 500,000 - 2,070,000 BTU/HR

	CP-0502	CP-0652	CP-0752	CP-0992	CP-1262	CP-1442	CP-1802	CP-2072
WATER								
GALLON CAPACITY	1.7	1.9	2.0	3.4	3.7	4.1	4.5	4.8
HEATING SURFACE (SQ. FT.)	59.0	76.8	88.1	96.0	120.2	144.0	176.0	200.0
WATER CONNECTIONS	2"	2"	2"	2-1/2"	2-1/2"	2-1/2"	2-1/2"	2-1/2"
DRAIN	3/4"	3/4"	3/4"	3/4"	3/4"	3/4"	3/4"	3/4"
WATER FLOW RATE (GPM)	55	55	55	90	90	90	115	115
HEAD LOSS (FT. OF HD.)	6.5	6.7	6.8	5.8	6.6	7.2	8.4	9.2
MAX. WORKING PRESSURE (PSI)	160	160	160	160	160	160	160	160
MAX. WATER HARDNESS (GRAINS)	25	25	25	25	25	25	25	25
# OF RELIEF VALVES	1	1	1	1	1	1	1	2
RELIEF VALVE SIZE	3/4"	3/4"	3/4"	3/4"	3/4"	3/4"	3/4"	3/4"
RELIEF VALVE RATING (MBH)	1,912	1,912	1,912	1,912	1,912	1,912	1,912	1,912
RELIEF VALVE PRESSURE RATING (PSI)	150	150	150	150	150	150	150	150
RELIEF VALVE TEMPERATURE RATING (°F)	210	210	210	210	210	210	210	210
GAS								
INLET CONNECTION	1-1/4"	1-1/4"	1-1/4"	2"	2"	2"	2"	2"
MAX. INLET PRESSURE, NAT	14" w.c.	14" w.c.	14" w.c.	14" w.c.	14" w.c.	14" w.c.	14" w.c.	14" w.c.
MIN. INLET PRESSURE, NAT	4.5" w.c.	4.5" w.c.	4.5" w.c.	4.5" w.c.	4.5" w.c.	4.5" w.c.	4.5" w.c.	4.5" w.c.
MANIFOLD PRESSURE, NAT	1.8" w.c.	1.8" w.c.	1.8" w.c.	1.2" w.c.	1.2" w.c.	1.2" w.c.	1.2" w.c.	1.2" w.c.
MAX. INLET PRESSURE, LP	14" w.c.	14" w.c.	14" w.c.	14" w.c.	14" w.c.	14" w.c.	14" w.c.	14" w.c.
MIN. INLET PRESSURE, LP	8.0" w.c.	8.0" w.c.	8.0" w.c.	8.0" w.c.	8.0" w.c.	8.0" w.c.	8.0" w.c.	8.0" w.c.
MANIFOLD PRESSURE, LP	4.6" w.c.	4.6" w.c.	4.6" w.c.	4.6" w.c.	4.6" w.c.	4.6" w.c.	4.6" w.c.	4.6" w.c.
BTU/HR INPUT	500,000	650,000	750,000	990,000	1,260,000	1,440,000	1,800,000	2,070,000
BTU/HR OUTPUT	425,000	552,500	637,500	841,500	1,071,000	1,224,000	1,530,000	1,759,500
ELECTRICAL								
VOLTAGE/HEATER	120	120	120	120	120	120	120	120
VOLTAGE/PUMP	120	120	120	120	120	120	120	120
VOLTAGE/CONTROL	24	24	24	24	24	24	24	24
TOTAL AMPS W/PUMP	12.1	14.6	14.6	17.9	17.9	21.4	21.4	21.4
# OF ELECTRICAL CONNECTIONS	2	2	2	2	2	2	2	2
DIMENSIONS								
HEIGHT	31-1/2"	31-1/2"	31-1/2"	36"	36"	36"	36"	36"
WIDTH (BYPASS NOT INCLUDED)	45-1/2"	56-3/4"	64"	48-1/4"	58-1/2"	68-1/4"	82-1/4"	92-1/2"
DEPTH	22-1/4"	22-1/4"	22-1/4"	33-1/2"	33-1/2"	33-1/2"	33-1/2"	33-1/2"
SERVICE CLEARANCES								
FRONT	30"	30"	30"	30"	30"	30"	30"	30"
BACK	3"	3"	3"	3"	3"	3"	3"	3"
RIGHT SIDE	3"	3"	3"	3"	3"	3"	3"	3"
LEFT SIDE (PIPING)	24"	24"	24"	24"	24"	24"	24"	24"
TOP	3"	3"	3"	3"	3"	3"	3"	3"
VENTING								
SIZE	6"	8"	8"	10"	12"	12"	14"	14"
VENT CATEGORY	I	I	I	I	I	I	I	I
VENT MATERIAL	B-VENT	B-VENT	B-VENT	B-VENT	B-VENT	B-VENT	B-VENT	B-VENT
MAXIMUM DRAFT	-0.08" w.c.	-0.08" w.c.	-0.08" w.c.	-0.08" w.c.	-0.08" w.c.	-0.08" w.c.	-0.08" w.c.	-0.08" w.c.
MINIMUM DRAFT	-0.02" w.c.	-0.02" w.c.	-0.02" w.c.	-0.02" w.c.	-0.02" w.c.	-0.02" w.c.	-0.02" w.c.	-0.02" w.c.

Lochinvar, LLC • 300 Maddox Simpson Pkwy • Lebanon, TN 37090 • 615-889-8900 / Fax: 615-547-1000
www.Lochinvar.com