


affinity[®] Two Speed with Timer **NEW** Switchless Design, 6.5" Frame Diameter, Category "S" & "J"



FEATURES:

- Two Compartment
- Shaft Threads – (Square Flange) 1/2-20 UNC-2A or (C-Flange) 7/16-20 UNF-2A
- 50°C Ambient
- 1081 Design
- Continuous Duty
- Class B Insulated
- Open Drip-Proof
- 300 Series Stainless Steel Shaft
- Thermally Protected
- Program for Low & High Speeds
- Two Settings – Mon-Fri and Sat/Sun
- High/Low Speed Override
- Freeze Sensor
- California Title 20/24 Compliant



- Optimized internal airflow design minimizes heat and moisture buildup inside the motor
- Internal bearing cover protects the drive/pump end ball bearing from water and debris that may occur inside of the motor
- Three additional layers of drive/pump end bearing protection:
 - Double Sealed Ball Bearing
 - Lip Seal
 - Water Slinger

extreme-E[®] Square Flange, Premium Energy Efficient, Total Horsepower Rated, **Category "S"**

THP	RPM	Voltage	Freq	Amps	Catalog Number	Motor Frame	Length Less Shaft	Wgt.
1.25/0.20	3450/1725	230	60	5.8 / 1.2	ASB2980T*	56Y	12.99	32
1.65/0.26	3450/1725	230	60	7.4 / 1.4	ASB2982T*	56Y	13.24	34
2.25/0.38	3450/1725	230	60	9.2 / 2.1	ASB2983T*	56Y	13.74	36
2.60/0.43	3450/1725	230	60	10.6 / 2.4	ASB2984T*	56Y	14.24	39

extreme-E[®] C-Flange, Premium Energy Efficient, Total Horsepower Rated, **Category "J"**

THP	RPM	Voltage	Freq	Amps	Catalog Number	Motor Frame	Length Less Shaft	Wgt.
1.25/0.17	3450/1725	230	60	5.8/1.2	ASB2973HT*	56J	12.01	31
1.65/0.20	3450/1725	230	60	7.4/1.3	ASB2975T*	56J	12.01	33
2.25/0.30	3450/1725	230	60	9.2/2.1	ASB2977T*	56J	12.51	35
2.60/0.33	3450/1725	230	60	10.6/2.4	ASB2979T*	56J	12.51	38



* California Energy Commission (CEC) Appliance Regulations (Title 20) compliant
Catalog numbers are for competitive comparison purposes only.

extreme-E[®] Extreme-E[®] represents our most efficient running, highest performing lines of motors.