

Function

A simple vertical column of clear water. Ideal as a focal point for small and medium-sized displays. Also appropriate as a peripheral effect for large displays.

Not water level dependent.



NLC075

NLC125

NLC200

Specification

Construction shall be machined bronze and brass. Lid shall be removable for easy cleaning.

Comes standard with N.P.T. threads, B.S.P.T. available upon request.


NLC075 comes complete with copper ground connector for flush mounting in concrete.

Options


ASU Series - 15° swivel connection for direction alignment of nozzle

WMF082 - Cover removal key for NLC075

part no.	inlet	overall dimensions		suction strainer openings req'd.
		diameter	height	
NLC075	1"	2-1/2"	2"	.040"
NLC125	1-1/4"	5"	5"	.080"
NLC200	2"	5"	5"	.125"



**ASU100
ASU125
ASU200**



WMF082

part no.	spray height	2'	3'	4'	5'	6'	8'	10'	12'	15'	20'
NLC075	gpm	10	12	14	15	16'					
	head	4'	6'	8'	9'	11'					
	spread	8"	10"	10"	12"	12"					
NLC125	gpm		16	20	24	25	30	33	38		
	head		5'	6'	20'	10'	13'	15'	20'		
	spread		12"	15"	20"	24"	24"	30"	36"		
NLC200	gpm				40			57		69	78
	head				9'			18'		25'	32'
	spread				24"			36"		44"	52"



PROPRIETARY AND CONFIDENTIAL

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF CRYSTAL FOUNTAINS INC. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF CRYSTAL FOUNTAINS INC. IS PROHIBITED.

CUT SHEET
NLC-D101

PAGE
1 OF 1

www.crystalfountains.com



COLUMN JET

SERIES
NLC

REV.
E

TEL. 1-905.660.6674

FAX. 1-905.660.6916

JUNE 2015