


ENERGYRITE® POOL HEATER

Submittal Sheet

ERP-Sub-03

ENERGYRITE® POOL HEATER

Job Name:	Model No.
Location:	Type Gas
Engineer:	Btu/Hr Input Btu/Hr Output
Agent/Wholesaler:	Equipment Tag(s):
Contractor:	
NOTES:	



	Model Number	Btu/Hr Input	A	В	C	Dimensions D	E	F	G	Air Intake	Vent Size	E-Rite/ Powered Sidewall Vent	Ship Wgt. (lbs.)
0	ERN152	150,000	26-1/2"	23"	22"	18"	10-1/4"	22"	5-1/2"	4"	5"	4"	183
0	ERN202	199,000	26-1/2"	26-1/2"	22"	20-3/4"	12"	22"	6"	4"	5"	4"	195
0	ERN252	250,000	26-1/2"	30"	22"	21-1/2"	13-3/4"	22"	6"	5"	6"	5"	217
0	ERN302	300,000	26-1/2"	33-3/4"	22"	25-3/4"	16-1/4"	21-1/2"	6-1/2"	5"	6"	5"	240
0	ERN402	399,000	26-1/2"	41"	22″	29-1/2"	20"	21-1/2"	6-1/2"	5"	6"	6"	269

Note: Change "N" to "L" for LP gas models. No deration for LP. Performance data is based on manufacturer test results. Agency certification applies to the boiler. Water connections are 2" NPT on 4-1/2" centers. Gas connections are 3/4" NPT Add "A" for ASME Construction.



Standard Features

- 2-Line, 16-Character Digital Display
- Pool & Spa Temperature Control
- · Password Security
- CPVC or PVC Ready
- 3rd-Party Remote Compatible
- Sealed Combustion Chamber
- Fan-Assisted Combustion
- Built-in Combustible Floor Shield
- Direct-Spark Ignition
- Stainless Steel Burners
- Loch-Heat Ceramic Tile
- 24V Terminal Strip
- Dual Voltage 240V or 120V/60HZ
- On/Off Switch
- Built-in Air & Water Pressure Switches
- Inlet & Outlet Temperature Sensors
- Automatic Reset Hi Limit Safety
- Polymer Header with Built-in Bypass
- Low-NOx Emissions Meet the Most Stringent Standards
- Flame View Port
- Outdoor Venting
- 3-Year Limited Warranty on Heat Exchanger
- 2-Year Limited Warranty on Parts



Optional Equipment	Venting Options
ASME Construction	Conventional
ASME Pressure Relief Valve	DirectAire Vertical w/ Side Wall Inlet
Bronze Headers	DirectAire Vertical w/ Rooftop Inlet
Cupro-Nickel Heat Exchanger	Power DirectAire
Stack Frame	Powered Side Wall
Indoor Vent Kits	E-Rite Side Wall
Flow Switch	Outdoor







