

56 Frame Pool & Spa Motors

Switchless Design, 6.5" Frame Diameter, Category "S" & "J"



FEATURES:

- Two Compartment
- Shaft Threads - 7/16-20 UNF-2A
- 50°C Ambient
- Triple Bearing Protection
- 1081 Design
- Continuous Duty
- Class B Insulated
- Open Dripproof
- Sealed Ball Bearings
- 303 Stainless Steel Shaft
- Switchless Design
- Thermally Protected
- Discount Symbol: DS-FPS

extreme-E Square Flange, Premium Energy Efficient, Full Service Factor, Full Rated

HP	SF	RPM	Voltage	Freq	SF Amps	Catalog Number	List	Motor Frame	Length Less Shaft	Ship Wt. (lbs)
3/4 / 1/8	1.67	3450/1725	230	60	5.8/1.2	*EB2980	\$433	56Y	12.05	30
1.0 / 0.16	1.65	3450/1725	230	60	7.4/1.3	*EB2982	\$445	56Y	12.30	32
1 1/2 / 1/4	1.47	3450/1725	230	60	9.2/2.1	*EB2983	\$507	56Y	12.55	34
2 / 1/3	1.30	3450/1725	230	60	10.6/2.4	*EB2984	\$618	56Y	13.30	37

extreme-E C-Flange, Premium Energy Efficient, Full Service Factor, Full Rated, Category "J"

HP	SF	RPM	Voltage	Freq	SF Amps	Catalog Number	List	Motor Frame	Length Less Shaft	Ship Wt. (lbs)
3/4 / 1/10	1.50	3450/1725	230	60	5.6/1.2	*EB2973H	\$431	56J	12.27	21
1 / 1/8	1.40	3450/1725	230	60	6.5/1.3	*EB2975	\$443	56J	12.27	28
1 1/2 / 1/5	1.30	3450/1725	230	60	8.2/2.0	*EB2977	\$505	56J	12.27	32
2 / 1/4	1.20	3450/1725	230	60	10.0/2.1	*EB2979	\$616	56J	12.52	23

*Meets California Energy Commission Appliance Regulations 2008 (Publication Number CEC-400-2006-002-REV1)

Catalog numbers are for competitive comparison purposes only

extreme-E EXTREME E® represents our most efficient running, highest performing lines of motors.

† All marks shown within this document are properties of their respective owners.



HURST MOTORS AND GEARING
BRAKEMOTORS
GENERAL PURPOSE SINGLE PHASE
HVAC
WASHDOWN
AGRICULTURE
COMMERCIAL PUMP MOTORS
CLOSE COUPLED PUMP MOTORS
FIRE PUMP MOTORS
POOL & SPA MOTORS
RESIDENTIAL WATER PUMP
ELEVATOR GATE & DOOR