

X2 BASKETBALL ASSEMBLY & INSTALLATION GUIDE



www.global-poolproducts.com



TABLE OF CONTENTS

Introduction	PAGE	3
Pool Side Games Safety Guidelines	PAGE	4
Cleaning Instructions	PAGE	4
Assembly & Installation	PAGE	5-6
Warranty	PAGE	6

Global Pool Products 1330 Pigeon Rd Bad Axe, MI 48413 P: 989-269-5900 - TF: 866-712-0606 Fax: 989-269-5902 www.global-poolproducts.com

Information contained in this document is proprietary and confidential to Global Pool Products and not to be reproduced without written consent from Global Pool Products.



INTRODUCTION

Global Pool Products is located in Mid-Michigan. Global Pool Products prides itself in manufacturing top of the line quality aquatic pool equipment and products. Global Pool Product's key staff has a century of combined industry experience and we take pride in each and every product that we build. Our products are made in the United States. Global Pool Products uses only the finest materials and processes to provide our customers with the highest quality products while still maintaining a price competitive edge.

The X2 BASKETBALL is designed for in ground residential swimming pools ONLY. The Basketball Hoop must be properly assembled, installed, used, and supervised for proper use and operation to reduce the risk of serious injury.

Please refer to your local building codes and national building codes to be implemented prior to installation.

Before starting assembly, remove all packaging and materials from the boxes. Double check to make sure that nothing is left inside the boxes. Identify the parts and hardware utilizing the parts listed in this document. Examine all parts thoroughly prior to installation to avoid anything that may have been damaged in transit. A damaged part should not be used in the installation. Proper assembly and installation of the Basketball System is imperative. Not following the directions provided will void Global Pool Products Warranty and may affect the safety.

MEGLECTING TO FOLLOW THESE INSTRUCTIONS AND THE
OWNER'S MANUAL MAY RESULT IN SERIOUS INJURY OR DEATH



POOL SIDE GAMES SAFETY GUIDELINES

The X2 BASKETBALL is designed for in ground residential swimming pools ONLY. The Basketball System must be properly assembled, installed, used, and supervised for proper use and operation to reduce the risk of serious injury.

- Please make sure to teach everyone the instructions to use the Basketball Hoop.
- No jumping or diving from any part of the Basketball Hoop Structure.
- No horseplay or shenanigans should be allowed while playing.
- Make sure you know how deep the water is prior to playing the game.
- Avoid collisions with other objects or swimmers.
- Do not play if under the influence of drugs or alcohol.
- Individuals with physical disabilities should be cautious and may require help playing the game.
- If you are pregnant, do not play.
- If you have any medical conditions that could inhibit your reaction time, please consult your physician before playing.
- DO NOT USE THE BASKETBALL HOOP if it is deteriorated or fractured. Block access and have it repaired.

CLEANING INSTRUCTIONS

Use nonabrasive soap and water as often as needed.

Keep clear of any abrasive or harsh cleaners, chemicals and/or disinfectants that could damage the basketball system.



Basketball Hoop Assembly & Installation Instructions

Tools Needed:

Crescent Wrench 7/32" Allen Wrench 4" Concrete Hole Saw (minimum)

Included Hardware:

(8) - 5/16" Lock Washer (4) - 5/16" Button-head Bolt - $1 \frac{1}{2}$ " (8) - 5/16" Nut

(4) - 5/16'' Button-head Bolt $-1 \frac{1}{4}''$ (12) - $5/16'' \times 7/8''$ Washer (2) - Escutcheons

Assembly

- 1. Remove protective paper from backboard before assembly and place on a non-abrasive surface.
- 2. Attach backboard to backboard bracket with four 5/16" x 1 $\frac{1}{4}$ " Button-head bolts and four 5/16" washers (on the back side of the bracket) and four 5/16" nuts.
- 3. Attach the basketball pole to the basketball backboard with four 5/16" x 1 ½" Button-head bolts, eight 5/16" washers, four 5/16" lock washers and four 5/16" nuts. (Order of fasteners goes as follows: Rim Side: washer and bolt; Pole Side: washer, lock washer and nut.)

Installation:

Retrofitting to Existing Pool Deck (Wedge anchor not included)

- 1. In the desired location, measure and mark anchor location 17 $\frac{1}{2}$ " inches apart on center. Stay 12" back from the pool edge.
- 2. Core drill the holes with a minimum diameter of 4" and to the depth where the anchor sits slightly below the pool deck.
- 3. Clean any debris from the holes before setting your anchor cups so it sits level. A Shop-vac may be needed to clear any hard to reach debris.
- 4. Place anchor cups in core drilled holes with the wedge bolt away from the water.
- 5. Check to ensure the drain holes are clear and nothing is blocking them to prevent water pooling in cups and the chance of corrosion to set in.
- 6. Bond your anchors to existing rebar. See your local electrical codes before bonding.
- 7. Use minimum 3,000 psi Quickrete, epoxy, or compression cement for solidifying the placement of your anchor cups. See the manufacturer's instruction for mixing and cure time. (Not included with Global Pool Product's products.)



8. Install your Basketball Hoop into the anchors, ensuring that the backboard is parallel to the pool edge, and tighten the wedges.

New Construction (Wedge anchor not included)

- 1. Place the anchors 12" away from pool's edge with the wedge bolt facing away from the water's edge. Anchor spacing is 17 ½" apart on center.
- 2. Secure anchors into place to keep anchors from shifting while pouring pool deck.
- 3. Install your Basketball Hoop into the anchors ensuring that the backboard is parallel to the pool edge and tighten the wedges.

Global Pool Products Warranty

All Global Pool Products Basketball Systems have a 3 Year **Limited Warranty** on all components (not including the fasteners, balls, and nets) to the original retail end user only products manufactured by Global Pool Products, when properly installed in accordance to the assembly and installation instructions, and when the equipment is properly *used and maintained, to be free from material defects and workmanship. All fasteners, balls, and nets carry a 90 day warranty from material defects and workmanship from the date of purchase.*

This warranty does not cover damages to **ANY** of our products due to: accident, abuse, negligence, misuse, damage by improper use of chemicals, fading, ice damage, fire, rust to fasteners, exceeding the weight capacity for model purchased, failure to install or to assemble the product in accordance with the installation and assembly instructions, normal wear and tear from day to day use, or not maintained properly.

THE WARRANTIES ARE IN LIEU OF ALL OTHER WARRANTIES, EXPRESSED OR IMPLIED, WHICH ARE HEREBY DISCLAIMED AND EXCLUDED, INCLUDING WITHOUT LIMITATION ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR USE.

IN NO EVENT SHALL GLOBAL POOL PRODUCTS BE LIABLE FOR ANY INCIDENTAL, CONSEQUENCIAL, INDIRECT, SPECIAL EXEMPLARY OR PUNITIVE DAMAGES OR LOST PROFITS FROM ANY BREACH OF THIS LIMITED WARRANTY. THE SOLE AND EXCLUSIVE REMEDY OF THIS WARRANTY IN REGARDS TO GLOBAL POOL PRODUCTS PRODUCT SHALL BE LIMITED TO REPLACEMENT OR REPAIR AT A GLOBAL POOL PRODUCTS FACILITY OR A DULY APPOINTED DISTRIBUTOR'S LOCATION OR AT A GLOBAL POOL PRODUCTS DESIGNATED LOCATION. IN NO EVENT SHALL GLOBAL POOL PRODUCTS LIABILITY EXCEED THE ENTIRE AMOUNT PAID TO GLOBAL POOL PRODUCTS BY THE ORIGINAL PURCHASER IN REGARDS TO THE DEFECTIVE OR FAILED PRODUCT.