



# CONTINENTAL SUBWAY

3" x 6"

<https://cepactile.com/product/continental-subway/>

## PROFILE

### Coordinating Trim:

Jolly Piece 9/16" x 6" Bead

Jolly Piece 1/2" x 6" Surface Bullnose

Please note the Jolly pieces are coordinating trims that are fired at different times than the field tile. In this regard, there can be wide shade variations between the field and trim pieces.

747-224-0600

[www.cepactile.com](http://www.cepactile.com)

[customercare@cepactile.com](mailto:customercare@cepactile.com)

*Where Excellence in Quality & Service Unite!*

## RECOMMENDED AREAS OF USE

With regard to the durability of the bisque and glaze, this material is suitable for:

- All vertical applications - residential and commercial
- All interior wall, countertop and floor applications
- Fireplace surround, hearth and firebox
- Light commercial flooring applications
- All exterior wall applications including building facades, swimming pools, fountains and outdoor kitchens, including regions that experience extreme weather conditions subject to the method of installation

## INSTALLATION AND MAINTENANCE

- Please refer to the TCNA handbook for installation method <http://www.tcnatile.com/>
- Always inspect material prior to installation, for color, shade, size, mounting and any other deciding factors as installed material cannot be accepted for return or credit. Use signifies acceptance.
- Recommended Grout Joint: 1/8" or greater
- Material can be cleaned with any mild nonabrasive household cleaning product due to the chemical resistant nature of the glaze.

## TECHNICAL DATA

- Japanese Porcelain – fired at approx. 2300 degrees Fahrenheit
- Chemical Resistant
- Frost Proof – subject to method of installation
- Water absorbency
  - Bisque less than 1%
  - Glazed surface 0%
- TCNA – MOH's Scale Rating 7
- TCNA – DCOF - COS-2: Avg. Rating: 0.28
- TCNA – DCOF – COS-1, COS-3, COS-4, COS-5, COS-6, COS-7, COS-8, COS-9 and COS-10: Avg. Rating: 0.19
- Loose pcs. – 8 pieces = 1 sq. ft. / 120 pieces = 15 sq. ft. per box
- Weight: 3.25 lbs. per sq. ft. / 50 lbs. per box
- Thickness: 5/16"
- Pre-consumer recycled content – 52%
- Variations of shade are inherent characteristics of all kiln fired products. To ensure satisfaction, please visually inspect all merchandise prior to installation, as use signifies acceptance.
- We will endeavor to resolve any issues that may arise with material purchased prior to installation.