


CPVC 90° SPRING CHECK VALVE

RATED @160 PSI STATIC PRESSURE @ 72°F
 MOLDED IN THE USA
 MADE OF CPVC
 EPDM O-RING
 PARTS ARE TAN COLOR

IPS SLIP X IPS SLIP CONNECTION

IPS—IRON PIPE SIZE
 (SAME AS SCH. 40 PIPE)



PART #	
OPEN PSI	FULL OPEN PSI

PART NUMBER				A	B	C	D	WEIGHT	IPS
1# SPRING		3# SPRING		(INCHES)	(INCHES)	(INCHES)	(INCHES)	(LBS)	CONNECTION
1901-15		1903-15		3.56	5.03	1.91	2.84	0.65	1 1/2" IPS
0.43 PSI	1.30 PSI	1.18 PSI	3.00PSI						
1901-20		1903-20		4.61	5.88	2.39	3.29	1.05	2" IPS
0.44 PSI	1.16 PSI	1.95 PSI	4.40 PSI						

NOTE: VALVE IS CONSIDERED OPEN WHEN SPRING IS COMPRESSED 1/8". FULL OPEN IS COMPLETE COMPRESSION OF SPRING.
 FOR 1/2" AND 3/4" VALVES FULL OPEN IS APPROXIMATELY 1/8".

NOTE: LENGTH VARIES WITH TIGHTNESS OF END NUT
 END NUT MAY BE WHITE OR GRAY