Control Systems

The S.R.Smith's wireless lighting control systems are easy to install and simple to operate. They operate on a 915 MHz frequency so that they can respond faster to commands and penetrate walls.









PT-6000 Control

- Upgrade your Fiber system to LED with ease
- You can use an existing Fiberstars fiberoptic illuminator base for installation. 2000 & 6000 series only.
- Works for existing pool automation systems
- 60 Watt system,
 30 Watts per channel (2)

WIR-TRAN Control

- Easy installation
- Includes replaceable fuse for surge protection
- Great for existing or new pool construction
- Handheld wireless remote included with every unit
- 75' wireless operating range (extension kit available)
- Manual override switch inside enclosure
- 30 Watt system

WPCI-XXXX-T Control

- 3 position On, Off, Auto, 24 hour time clock
- 2 wireless controlled circuits: Circuit I: I2VAC, 30 Watt max Circuit 2: I10VAC, 8 Amp max
- Manual override switches on each circuit
- 75' wireless operating range (extension kit available)
- GFCI knockout
- 30 Watt system

WPC2-XXXX-T Control

- 3 position On, Off, Auto, 24 hour time clock
- 2 wireless controlled circuits: Circuit I: I2VAC, 30 Watt max Circuit 2: I10VAC, 8 Amp max
- Manual override switches on each circuit
- 75' wireless operating range (extension kit available)
- 2 GFCI knockouts,
 I Internal, I External
- 100 Amp sub panel for up to 8 breaker locations
- 30 Watt system

Features

	PT-6000	WIR-TRAN	WPCI-XXXX-T	WPC2-XXXX-T
Circuits	2	I	2	2
Transformers	2	I	1	I
Number of LED or CLS Product	10	5	5	5
Sub Panel	No	No	No	Yes
Remote Included	Yes	Yes	Yes	Yes
24-hour Time Clock	No	No	Yes	Yes

