FX | LUMINAIRE® **DP-10**



Ultra-Micro Size, Halogen Power

The DiamantePiccolo[®] is the most petite luminaire in the FX family. Milled from extra-heavy gauge copper and solid brass, the patent pending DP is engineered to survive.

The beam spread of the DP provides maximum projection with minimum glare.

This model is perfect for coastal exposures or areas where irrigation water contains high levels of mineral or caustic salts.

The copper will patina naturally over time and can be accelerated with solution spray. For patina formulas visit our website at: www.FXL.com/learning/patina.htm



Perimeter Lighting



DIAMANTEPICCOLO[®] | FX LUMINAIRE[®]

LIFETIME PERFECTION

At FX, we engineer fixtures from the inside out. Our use of semi precious metals, aerospace sealants and materials is without peer. This commitment to excellence provides your client with decades of problem-free ownership.

Compare FX copper luminaires with any other, and you will find a dramatic difference in quality of materials, precision of fit and consistency of finish.



47

DIAMANTEPICCOLO[®] – ORDERING INFORMATION

The DP comes standard with 10 watt Xenon G4 lamp, Super Slot Spike®, and in Copper (CU).

STANDARD OPTIONS:

I + 2 + 3 + 4 ORDERED TOGETHER ON SAME LINE

AVAILABLE LAMP CONFIGURATIONS:

Your choice of one lamp will come pre-installed.

FIXTURE/CODE WATTAGE/CODE AVG. LIFE HOUR Image: Description of the state of t


STANDARD RISER OPTIONS::

Your choice of one riser option will come pre-assembled. Riser Specs: Copper 0.5" Diameter

	CODE	DESCRIPTION	
	3 8R	8" Riser	
	I2R	12" Riser	
	18R	18" Riser	

STANDARD FINISH OPTIONS:

Copper is standard. All other choices must be specified.



STANDARD PARTS: Xenon G4 Super Slot Spike® Copper

ORDERING SAMPLE:

SECTIONS:	DESCRIPTION:	WHAT TO ORDER:
I + 2 + 3 + 4 optional	🕈 + 🖉 + 🦯 + 🗔	=DP-10-12R
Α	PostMount®	= PM

NON-STANDARD OPTIONS:

MUST BE ORDERED ON SEPARATE LINE!

ADDITIONAL MOUNTING OPTIONS:

Comes pre-assembled with Super Slot Spike®.

All other mounting options will arrive in separate box.



PHOTOMETRICS:

Spacing for minimum footcandle illumination on level ground. Note: Ifc for commercial projects .3fc for residential projects DP-5 6' for Ifc, 9' for .3fc DP-10 7' for Ifc, 10' for .3fc						
14'	Foot	candle	Power (12R riser)		
12'	2'	1.7	2.6			
10'	4'	.31	.57			
10	6'	.10	.13			
8'	8'	.04	.05			
6'	10'	.02	.03			
0	12'	.01	.02			
4'	14'		.0			
2'	111100	X glossary		oly footcandles escription of fc		