FX | LUMINAIRE®

PV-10





PERIMETER LIGHTING



WHY USE PATHLIGHTING?

The most visible source of lighting equipment comes from Pathlights. Pathlighting should be used to draw attention to pedestrian hazards such as grade changes or to illuminate surfaces that can't be reached by downlighting from trees, eaves and other architectural elements or integral wall mounted fixtures.




Perfect, Mid-sized Luminaire

Whether your view is of Monaco, Miami or Monterey, the FX copper pathlites are the best choice for high-end residential and intimate resort projects. The PV is our mid-sized model designed for small scale garden pathways and planters. Choose between the high output / high efficiency halogen lamp or the extended life xenon lamp.

The most successful gardens are a harmonious blend of organic materials. The FX copper line is the perfect match to wood, masonry, and plant materials since the natural patina process allows each fixture to melt into its background.

Compare FX copper luminaires with any other, and you will find a dramatic difference in quality of materials, precision of fit and consistency of finish.

The copper will patina naturally over time and can be accelerated with solution spray. For patina formulas visit our website at: www.FXL.com/learning/patina.htm



PIATTINO VESTITO® - ORDERING INFORMATION


The PV comes standard with a 10 watt Xenon G4 lamp, Super Slot Spike®, and in Copper (CU).

STANDARD OPTIONS:

I + 2 + 3 + 4 ORDERED TOGETHER ON SAME LINE

AVAILABLE LAMP CONFIGURATIONS:

Your choice of one lamp will come pre-installed.



STANDARD RISER OPTIONS:

Your choice of one riser option will come pre-assembled.

Riser Specs: Copper 0.5" Diameter

CODE	DESCRIPTION	
3 8R	8" Riser	
I2R	12" Riser	
18R	18" Riser	

STANDARD FINISH OPTIONS:

Copper is standard. All other choices must be specified.

CODE	DESCRIPTION
cu	Copper (will naturally patina)

NON-STOCKING FINISH OPTIONS:

Allow extra time for the following finish options:



STANDARD PARTS:



ORDERING SAMPLE:				
SECTIONS:	DESCRIPTION:	WHAT TO ORDER:		
1 + 2 + 3 + 4 optional	+ + + +	=PV-10-12R		
Α	PostMount®	= PM		


NON-STANDARD OPTIONS:

MUST BE ORDERED ON SEPARATE LINE!

ADDITIONAL MOUNTING OPTIONS:

Comes pre-assembled with Super Slot Spike[®].

All other mounting options will arrive in separate box.



PHOTOMETRICS:



14'	Foot	Footcandle Power (12R riser)			
	Distance	PV-10	PV-20		
12'	2'	1.7	2.6		
10'	4'	.31	.57		
10	6'	.10	.13		
8'	8'	.04	.05		
	10'	.02	.03		
	12'	.01	.02		
	14'		.01		
2'	× 10. See F	For conversion to lumens: Multiply footcandles x 10. See FX glossary for a full description of fc and lumens.			