

Performance Reliability Technology

Legacy[™] Heaters

Legacy – Value & Efficiency

With 60 years experience as the No. 1 selling brand of pool heaters – Jandy's new Legacy Heater is designed for today's discerning market. Available in two models, the Legacy LRZE (electronic ignition) heater features a technologically-advanced dual-thermostat control, and the LRZM (millivolt ignition) model features a single control with easy on/off switch.

Whichever model you select, it's sure to provide years of dependable service. With our industry-leading 24-point quality check system, you can depend on Legacy's performance and reliability year after year, season after season.

DESIGNED TO SAVE ENERGY

heat your pool.



Ceramic fiber combustion chamber for lightweight, compact design.

Copper heat exchanger and Flo-Thru

baffles provide efficient heat transfer and

lower the amount of energy needed to



Reliable hot surface ignition systems provide trouble-free operation on the LRZE model season after season.

TWO MODELS TO CHOOSE FROM:

The Legacy LRZE



The LRZE's feature-rich control panel has a userfriendly backlit display and a simplified menu for ease of operation.

LRZE Control Panel

The Legacy LRZM



single control for pool water temperature maintenance.

The LRZM keeps it

simple with an easy

on/off switch and a

LRZM Control Panel

Reliability You Can Depend On

Performance you can rely on... with 60 years of experience!



Legacy[®] Heaters

Specifications:

BTU Input

. 1000's (kcal)

125 (32)

175 (44)

250 (63)

325 (82)

399 (101)

Indoor and

Outdoor Models

"W" Width

Inches/cm

15¹/₈ (38)

18^{1/}8 (40)

22¾ (58)

267/8 (68)

32^{3/}8 (82)

QH

"V" Vent

Diameter

Inches/cm

6 (15)

6 (15)

7 (18)

8 (20)

9 (23)

SIDE

Model #

LRZE /

LRZM

125

175

250


325

400

FRONT

Jandy's expertise

and design know-how are reflected in the technologicallyadvanced Legacy Heaters.



"H" U.S.

Outdoor Stack

Inches/cm

18 (46)

18 (46)

18¼ (47)

18^{7/}8 (48)

211/2 (55)

"H" U.S. Indoor Stack

Inches/cm

24¹/₈ (61)

24^{1/}8 (61)

25¼ (64)

261/2 (67)

271/2 (70)

Weight Lbs/kg

145 (66)

157 71)

174 (79)

207 (94)

231 (105)

LEGACY PERFORMANCE CHARTS

Model	125		175		250		325		400	
			ater (wic	dth x length)						
Temp Diff*	0 Wind	3 ½ MPH	0 Wind	3 ½ MPH	0 Wind	3 ½ MPH	0 Wind	3 ½ MPH	0 Wind	3 ½ MPH
15°F	875	675	1250	925	1775	1325	2300	1725	2850	2125
20°F	675	500	925	700	1325	1000	1725	1300	2125	1600
25°F	525	400	750	550	1075	800	1400	1050	1700	1300
30°F	450	325	625	475	900	700	1250	875	1425	1075
35°F	400	300	550	400	775	575	1000	750	1225	900

POOL SIZING GUIDE

The Pool Sizing Guide shows the maximum pool surface area our Legacy models will heat based on the temperature difference between the air temperature during the coldest month the pool is used and the desired pool temperature. Figures are based on average wind conditions and average pool depth.

SPA SIZING GUIDE

Model 125		175	250	325	400			
Spa Size	Time Required to Raise Temp 30°							
200 Gallons	30 Minutes	25 Minutes	20 Minutes	15 Minutes	10 Minutes			
400 Gallons	60 Minutes	45 Minutes	30 Minutes	25 Minutes	20 Minutes			
600 Gallons	90 Minutes	65 Minutes	45 Minutes	35 Minutes	30 Minutes			
800 Gallons	120 Minutes	90 Minutes	60 Minutes	50 Minutes	40 Minutes			
1000 Gallons	150 Minutes	110 Minutes	75 Minutes	60 Minutes	50 Minutes			

The Spa Sizing Guide details the time required for each model to raise spa temperature by 30°F.

See your Sales Representative for more information!

and



Pumps • Filters • Heaters • Heat Pumps • Controls Lights • Water Purification • Valves • Water Features • Water Leveling Cleaners • In-Floor • Pool Covers • Accessories

ALL JANDY PRODUCTS WORK SEAMLESSLY TOGETHER

Jandy Control Systems manage our complete line of technologically advanced products.



USA: 1.800.822.7933 • Canada: 1.888.647.4004 • www.jandy.com • info@jandy.com