

- never buy chlorine again
 environmentally friendly
- simple to use
- no more red eyes
- no more itchy skin
- no more faded swimwear
 energy efficient
- soft, silky feeling water

- automatic cell cleaning
- · no more damaged hair
- no more vacation worries



SRLT = 2800 PPM 11:50 780 F





Features:

- Extra bright Vacuum Fluorescent Display (VFD)
- Optional relay provides time clock control of pool pump and freeze protection
- More purifier output than any other unit Up to 2.5 lbs. per day 47 g/h
- Microprocessor technology
- Patented temperature compensation
- 24 & 72 hour boost cycles
- Front panel quick reference guide
- Operates at all salt levels 2,000 35,000 ppm 2 to 35 g/L
- Operates at water temperature up to 104°F/40°C
- Soft reverse cell cleaning
- Choice of 4 cells to suit pool size
- Patented bypass manifold
- Controlled flow rate for optimum chlorine production
- Easy installation and service
- Upgrade easily to the CoPilot® Ozonator to get the convenience of salt chlorination with the power of ozone

Part#	Description	Maximum Pool Size
DIG-220	Digital Power Supply 110/220V	
94105	Manifold with RC-35 Cell	35,000 gallons/133 m³
94107	Manifold with RC-42 Cell	42,000 gallons/159 m³
94113	Manifold with RC-52 Cell	52,000 gallons/197 m³
94115C	Manifold with CC-15 Cell	67,000 gallons/254 m³

Protected by U.S. patents 5,985,155, 5,993,669 and 6,096,202.





