

## **VGB** Series

**Product Specification Sheet** 

## Features

For single or multiple drain use (see installation instructions)

Single Floor: 88 GPM at 3.2 fps Wall: 70 GPM at 2.6 fps

Floor/wall: 41 GPM at 1.5 fps

8.8 square inch opening

Meets or exceeds NSF 50/ASME/ANSI A112.19.8a-2008 national standards and ASTM G154 UV testing

Two extra 1" knock-out ports

Adjustable collar aids in leveling drain cover to pool finish

#316 stainless steel screws

Includes 2" threaded plug and 2" x 1<sup>1</sup>/<sub>2</sub>" reducer bushing S/S

USPC-listed with IAPMO R&T

Part Numbers / Colors

8SBAC101 White

8SBAC102 Black 8SBAC103 Lt. Gray 8SBAC104 Blue 8SBAC105 Dk. Gray

8SBAC106 Bone

8SBAC107 Taupe 8SBAC108 Tan

Cover with adjustable collar can be

purchased separately p/n 8AVACxxx 36 per case

Also available with sump only p/n 8SBNOACxxx 8 per case

8 per case

## and Sump with Adjustable Collar

8" Anti-Entrapment Suction Outlet Cover

The AguaStar line of suction outlet covers, compliant with the new Virginia Graeme-Baker Pool and Spa Safety Act (ASME/ANSI A112.19.8a-2008)



**P**877-768-2717 **F**877-276-POOL Outside the US: **P**+1-949-459-1202 **F**+1-949-336-1940 info@aquastarpoolproducts.com www.aquastarpoolproducts.com

