

# 12" Square SUN Suction Outlet Cover and Mud Frame

### **VGB** Series

**Product Specification Sheet** 

The AquaStar line of suction outlet covers, compliant with the new Virginia Graeme-Baker Pool and Spa Safety Act (ASME/ANSI A112.19.8a-2008)

#### **Features**

For single or multiple drain use (see installation instructions)

Requires a minimum 3" sump depth

Floor: 280 GPM at 2.5 fps Wall: 280 GPM at 2.5 fps

Floor/wall: 166 GPM at 1.5 fps

35.3 square inch opening

#316 stainless steel screws

The SUN Series has the lowest profile 9" x 9" and 12" x 12" VGB 2008 compliant suction outlets in the industry

Manufactured from superior UV-resistant engineered polymers

Easily and safely retrofits most brands' existing 12" frames\* (see chart and installation instructions for details and special requirements)

Mud frame included for new construction

All components (cover, adapter plate, frame, screws) meet or exceed NSF 50/ASME/ANSI A112.19.8a-2008 national standards and ASTM G154 UV testing exposure

Listed with IAPMO R&T

12 per case

### **NEW SUN Series**

Lowest profile – great for spas and wading pools!






Part # SUN12xxx


\*Fits: AquaStar, Pentair #1, AquaStar pre-VGB (3/4" deep frames)

### Part Numbers / Colors

- SUN12101 White
- SUN12102 Black
- SUN12103 Lt. Gray
- SUN12104 Blue
- SUN12105 Dk. Gray
- SUN12106 Bone
- SUN12107 Taupe
- SUN12108 Tan

VGB 2008 Compliant





- 1. 12" shallow square "SUN" to 10" round adapter
- 2. 10" round anti-entrapment cover
- 3. 12" square drain frame
- 4. #10 x 3/4" flat head phillips screw, 316 ss
- 5. #10 x 3/4" flat head phillips screw, 316 ss

P 877-768-2717 F 877-276-POOL Outside the US: P +1-949-459-1202 F +1-949-336-1940 info@aquastarpoolproducts.com www.aquastarpoolproducts.com



### ADDITIONAL PRODUCT CONFIGURATIONS FOR SUN12xxx

### Features: Sump Buckets for SUN12xxx

For single or multiple drain use (see installation instructions)

#316 stainless steel screws

The SUN Series has the lowest profile 9" x 9" and 12" x 12" VGB 2008 compliant suction outlets in the industry

Manufactured from superior UV-resistant engineered polymers


All components (cover, adapter plate, frame, screws) meet or exceed NSF 50/ASME/ANSI A112.19.8a-2008 national standards and ASTM G154 UV testing exposure

Sold with SUN12xxx, not sold separately

## 12" Square Double-Deep Sump



Part # SUN12DDxxx 4 per case




- 1. 12" square double-deep frame
- 2. 10" round flat grate (optional)
  3. 12" x 12" to 10" round adapter with flow slots
- 4. 10" anti-entrapment suction outlet cover
- 5. #10 x 3/4" Ig flat head phillips screw, 316 ss, qty 8

### 12" Square SUN Suction Outlet with Dual-Port 21/2" Spigot x 2" Socket Deep PVC Sump



Part # SUN12DDSBxxx 1 per case



- 1. Dual-port 2-1/2" spigot x 2" socket deep PVC sump
- 2. 10" round flat grate (optional)3. 12" x 12" to 10" round adapter with flow slots
- 4. 10" anti-entrapment suction outlet cove
- 5. #10 x 3/4" Ig flat head phillips screw, 316 ss, qty 8
- 6. 2" tapered pipe thread plug

# 4" Spigot Deep PVC Sump



Part # SUN12DDSB4SPxxx 1 per case


- 17/32 29/32 .237 min 4" spigot
  - 1. 4" spigot deep PVC sump
  - 2. 10" round flat grate (optional)
  - 3. 12" x 12" to 10" round adapter with flow slots
- 4. 10" anti-entrapment suction outlet cover 5. #10 x 3/4" Ig flat head phillips screw, 316 ss, qty 8

# 12" Square SUN Suction Outlet



SUN12DDSB4SOCxxx 1 per case

Part #




- 1. 4" socket deep PVC sump
- 2. 10" round flat grate (optional)
- 3. 12" x 12" to 10" round adapter with flow slots
- 4. 10" anti-entrapment suction outlet cover
- 5. #10 x 3/4" Ig flat head phillips screw, 316 ss, qty 8

#### 12" Square SUN Suction Outlet with 6" Spigot Deep PVC Sump



Part # SUN12DDSB6SPxxx




- 2. 10" round flat grate (optional)3. 12" x 12" to 10" round adapter with flow slots
- 10" anti-entrapment suction outlet cover
- 5. #10 x 3/4" Ig flat head phillips screw, 316 ss, qty 8

### with 6" Socket Deep PVC Sump



Part # SUN12DDSB6SOCxxx



- 1. 6" socket deep PVC sump
- 2. 10" round flat grate (optional)
- 3. 12" x 12" to 10" round adapter with flow slots
- 4. 10" anti-entrapment suction outlet cover 5. #10 x 3/4" Ig flat head phillips screw, 316 ss, qty 8