

<u>SPECIFICATION DATA</u>: Adjustable Precision Jet; three-piece machined brass construction, adjustable to 15° off vertical in a 360° cone, male threaded connection.

<u>DESIGN/APPLICATION DATA</u>: RPJ Series precision jets produce a medium bodied, clear stream of water. Precision jets include an integral adjustment feature to allow a variety of spray angles (0-15° off center axis).

<u>NOTES</u>: 1. Fine screening at pump, half the diameter of jet orifice or smaller to minimize nozzle clogging recommended. 2. Due to continuing product improvement program, Roman Fountains reserves the right to change the specifications without notice.

TECHNICAL AND HYDRAULIC DATA													
MODEL NO.		SUCTION SCREENING REQUIRED	THREAD SIZE (M) N.P.T.	DIM 'A'	DIM 'B'	MAX. SPRAY HEIGHT	2'	4'	6'	8'	10'	12'	14'
RPJ-375	.375"	.187"	3/4"	4-1/2"	1-3/8"	GPM	4.0	6.0	7.0	8.0	9.0	10.5	11.5
						HEAD	4.0'	6.0'	8.0'	10.0'	12.0'	14.0'	17.0'
RPJ-500	.500"	.25"	3/4"	4-1/2"	1-3/8"	GPM	7.5	10.0	12.5	14.0	16.5	17.5	19.0
IXF J- 300						HEAD	4.0'	6.0'	8.0'	10.0'	12.0'	14.0'	17.0'
COPYRIGHT 2019 ROMAN FOUNTAINS ALL RIGHTS RESERVED			www.roma	ITEM#			QTY						