



QuikBlox RecordQuest Long Reach Starting Platform

PART NUMBER	A	B	C
CH30-30 thru CH40-30	30	35.00	18.00
CH30-29.5 thru CH40-29.5	29.5	34.50	17.50
CH30-29 thru CH40-29	29	34.00	17.00
CH30-28.5 thru CH40-28.5	28.5	33.50	16.50
CH30-28 thru CH40-28	28	33.00	16.00
CH30-27.5 thru CH40-27.5	27.5	32.50	15.50
CH30-27 thru CH40-27	27	32.00	15.00
CH30-26.5 thru CH40-26.5	26.5	31.50	14.50
CH30-26 thru CH40-26	26	31.00	14.00
CH30-25.5 thru CH40-25.5	25.5	30.50	13.50
CH30-25 thru CH40-25	25	30.00	13.00
CH30-24.5 thru CH40-24.5	24.5	29.50	12.50
CH30-24 thru CH40-24	24	29.00	12.00
CH30-23.5 thru CH40-23.5	23.5	28.50	11.50
CH30-23 thru CH40-23	23	28.00	11.00
CH30-22.5 thru CH40-22.5	22.5	27.50	10.50
CH30-22 thru CH40-22	22	27.00	10.00
CH30-21.5 thru CH40-21.5	21.5	26.50	9.50
CH30-21 thru CH40-21	21	26.00	9.00
CH30-20.5 thru CH40-20.5	20.5	25.50	8.50
CH30-20 thru CH40-20	20	25.00	8.00



Specification Number:	SRS-308		
Product Description:	QuikBlox RecordQuest Long Reach Starting Platform		
S.R. Smith Part Number:	CH30-20-01 to CH40-30-21	Scale:	NTS
Revision:	A	Date:	10/14/04
Written By:	K. Ball	Date:	10/14/04
Approved By:	B. Bisceglia	Date:	10/14/04
Page 1 of 2	Proprietary and confidential: The information contained in this specification is the sole property of S.R. Smith LLC. Any reproduction in part or whole without the written consent of S.R. Smith LLC is prohibited.		

S.R. Smith, LLC
P.O. Box 400, 1017 SW Berg Parkway
Canby, Oregon 97013
Tel: (888) 677-7776 (503) 266-2231
Fax: (503) 266-4334
www.srsmith.com



S.R. Smith LLC Commercial Division

Product Specifications - Written

Product Name: QuikBlox RecordQuest Long Reach Starting Platform

Part Number: CH30-20-01 to CH40-30-21

General Notes:

The **QuikBlox RecordQuest Long Reach Starting Platforms** are designed for use on competitive pools. The weldment is stainless steel and is powder coated for corrosion resistance. The anchor has a replaceable sleeve and is designed to prevent “rocking”. This platform can be ordered to fit almost any deck and water height variable. RecordQuest starting blocks are available with built-in strobe lights in both the front and rear of the platform.

Application:

Depending upon installation design and local codes, this model is suitable for use on competitive pools. The deck to water level dimension indicates which platform is to be used as well as the setback from the pool wall. Setbacks from the pool wall start at 30”(762mm) and continue up to 40”(1016mm) in 2”(50.8mm) increments.

Specifications:

- 1 Step and Platform: Both the step and platform are constructed of a gel-coat outer surface and a non-slip, sanded tread over a solid laminated board, reinforced with fiberglass. The platform is mounted at a 10° angle. The overall dimensions of the step are 2”(50.8mm) thick x 10.5” x 14.5” (266.70mm x 368.30mm) and the platform overall dimensions are 2”(50.8mm) thick x 24” x 32” (609.60mm x 812.8mm).
- 2 Platform Frame: The RecordQuest platform frame is constructed of 2.5 in² (63.5mm²) x .120” (3.05mm) wall, stainless steel tubing. The backstroke bar is attached to 1.5 in² (38.10mm²) x .065” wall (1.65mm) stainless steel tubing with a cap welded to the end. A backstroke bar constructed of 1.00” O.D. x .065 wall (25.40mm x 1.65mm) stainless steel tubing is also capped with stainless steel. The gusset is made from .125” (3.18mm) stainless steel and the footboard plate is made of .188” (4.77mm) stainless steel. The entire frame assembly is powder coated for added corrosion resistance. Lane numbers are applied to both sides and to the front and rear of the platform.
- 3 Strobe Light: An optional built-in low voltage strobe is located in the front edge of the platform, allowing swimmers to react to sight as well as to sound. An optional rear strobe allows backup timers to focus on their lane rather than on the starter. Banana plug outlets are accessed at the rear of the platform frame for customer supplied cables.
- 4 Escutcheon: This square escutcheon plate is stamped from .063” (1.60mm) 304 series stainless steel. The dimensions measure a nominal 5.0” x 5.0” x 1.0” (127mm x 127mm x 25.4mm). The Escutcheon is powder coated to match the platform frame.
- 5 Anchor: (p/n 27-107, see spec sheet for SRS-920) This single post anchor assembly is specially designed to prevent rocking and the liner can be replaced when worn. The assembly consists of a housing constructed of 4.00 in² (101.60mm²) x .120” (3.05mm) wall stainless steel tubing welded onto a 4.5 in² (114.30mm²) flange. The anchor is threaded and comes with a 1/4-20 UNC stainless steel grounding screw. The insert is made of urethane to facilitate removal of the platform. A stainless steel cap is provided to mount flush on the deck when the platform is removed.

Additional Product Numbers:

Model Number	Description
CH30-20-01 to CH40-30-01	No Strobe Model
CH30-20-11 to CH40-30-11	Front Strobe Model
CH30-20-21 to CH40-30-21	Front and Rear Strobe Model

Shipping weight: N/A.

Specification Number:	SRS-308		
Product Description:	QuikBlox RecordQuest Long Reach Starting Platform		
S.R. Smith Part Number:	CH30-20-01 to CH40-30-21		
Revision:	A	Date:	10/14/04
Written By:	K. Ball	Date:	10/14/04
Approved By:	B. Bisceglia	Date:	10/14/04
Page 2 of 2	Proprietary and confidential: The information contained in this specification is the sole property of S.R. Smith LLC. Any reproduction in part or whole without the written consent of S.R. Smith LLC is prohibited.		

S.R. Smith, LLC
P.O. Box 400, 1017 SW Berg Parkway
Canby, Oregon 97013
Tel: (888) 677-7776 (503) 266-2231
Fax: (503) 266-4334
www.srsmith.com