

2012

SPA PRODUCTS CATALOG

















"SLIDE" SERIES & WATER PRO "VALUE" SERIES....Only from Hydro-Quip.



Now Available With Balboa™ or Gecko Series Control Platforms

"The Perfect Solution For Spa Service Professionals!"

The Ultimate in Retro-Fit Control Systems

The "SLIDE" series and Water Pro "Value" Series family of Hot Tub Control Systems were designed using Hydro-Quip's 30 years of experience. Our exclusive "SLIDE" Heater feature will allow just a few basic control boxes to retro-fit practically any spa ever made! Mount the adjustable heater where you need it anywhere along the back of the control box utilizing the provided slide brackets, over, under or remote. You can now offer the maximum range of retro-fit controls while stocking a minimum number of systems.

The Water Pro "Value" Series offers the same internal components, quality and serviceability as our "SLIDE" Series although it includes a fixed bottom mount heater.

Versatile, Reliable, Affordable





About us:



Hydro-Quip ... the Smart Choice

Hydro-Quip has been providing innovative, dependable and high quality portable spa and hot tub retrofit controls to the industry for 30 years. Hydro-Quip continues to offer the broadest selection of controls to fit every spa or hot tub and we continue to lead the industry in innovation and "down to earth" product features by designing products that address the real needs and desires of today's spa and hot tub retail dealers and service technicians.

"Down to Earth" features such as this long list of industry firsts:

Electronic Controls Choice of Balboa or Gecko Series

Slide Heater Assembly Position the heater to your requirements

Versi-Heat Remote Heaters Remote heater for added convenience

<u>Universal Retro-Fit System</u> Complete ready to install bundled Control Kits

Visual Diagnostic System Provides easy system diagnostics

<u>System Mis-Wire Protection</u> Protection from improper electrical installations

<u>Universal Circuit Voltages</u> Flexible circuit designs

Built-in Ground Fault Protection Economical GFCI protection

In addition to our innovative spa and hot tub products, you will find our customer service team to be unmatched in their first hand product knowledge. Our customer service, sales and technical support teams are all industry veterans that understand not only the product but the application spa customers encounter on a daily basis. We take great pride in our reputation for superior quality and responsive customer service, all at a competitive price.

In the following pages you will find a selection of products which address your engineering needs, marketing requirements and production concerns. Please contact us if you have any additional needs, questions or requirements.



TABLE OF CONTENTS

	Model	Series Description BALBOA SERIES	Page
HYDROGUE	ES6000B - CS6000B -	Duplex Series Slide Control Systems Duplex Series Equipment Systems Serial Series Slide Control Systems Serial Series Equipment Systems	1 2 3 4
MYDRO-JUY -	ES4000B - CS4000B -	Pump Mount Duplex Series Slide Control Systems Pump Mount Duplex Series Equipment Control Systems Pump Mount Serial Series Slide Control Systems Pump Mount Serial Series Equipment Systems	5 6 7 8
HYDROGUE	CS7000B -	Lite Leader Series Slide Control Systems	9
Water Pro	CS6000B -	Water Pro Lite Leader Value Series Control Systems Water Pro Duplex Value Series Control Systems Water Pro Serial Value Series Control Systems	10 11 12
		GECKO SERIES	
H-thoo;		Standard Series Slide Control Systems Standard Series Equipment Systems	13 14
HYDRO		Pump Mount Series Slide Control Systems Pump Mount Series Equipment Systems	15 16
эгожо:		Deluxe Series Slide Control Systems Deluxe Series Equipment Systems	17 18
	CS7000 - E	Economy Series Slide Control Systems	19
Writes Pu		Vater Pro Value Series Control Systems Vater Pro Value Series Control Systems	20 21







TABLE OF CONTENTS

	Model	Series Description AIR CONTROL SYSTEMS	Page
Arross 3		Standard Series Slide Control Systems Standard Series Equipment Systems	23 24
- 10000		Pump Mount Series Slide Control Systems Pump Mount Series Equipment Systems	25 26
900	CS7000 - E	Economy Series Control Systems	27
2.0	CS500 - Pt	ump Mount Control ABS Series	28
		OUTDOOR SOLID STATE SYSTEMS	
1999	ES8748 - C	Outdoor Series Equipment Self Priming Systems Outdoor Series Equipment Systems Outdoor Series Control Systems	29 30 31
	SPA	COMPONENTS / PURE HEAT BATH HEATER	S
HEATMAX -	HEATMAX	- Remote Heater System	32
	SILENT AI	RE - Air Blower Series	33
	UNIVERSA	AL RITE-FIT - Heater Assembly	34
	TEE STYL	E - 7" Tee Style Bath Heaters	35
	INLINE - 7'	'Inline Pressure & Vacuum Style Bath Heaters	36
		INFORMATION	
Technical Facts HQ Product Infor	mation		37 38



Duplex

CS6000B Solid State Series "SLIDE" Control Systems



"SLIDE" HEATER FEATURE!

Balboa™Series

STANDARD FEATURES

M7™ Technology Equipped "SLIDE" 1.325/5.5KW, 15" Heater Assembly Spaside Control All Circuits Convertible to 120 or 240VAC 12V Light Assembly

Freeze Protection

Standard, Economy & Sleep Modes

Lighted Smart Cords Easy To Install & Service Installation Kit (see below)

Detailed Owners Manual & Wiring Diagram US and Canada UL Recognized

2 Year Warranty

OPTIONS

Versi-Heat Remote Heater with 60" Cords Various Heater Wattages Wireless Remote Control

Less Heater Unit

Spaside Control	SUPPORTE Model	D PERIPHERA Platform	LS AND CI Pump 1	RCUITS BY Pump 2	MODEL Blower	Circ Pump	Heater
ECO-200 Series 4.3"L x 1.6"H	CS6109B-US CS6209B-US CS6229B-US CS6239B-US*	VS500Z VS501Z VS511Z VS513Z/510Z	2 SPD 2 SPD 2 SPD 2 SPD	N/A 1 SPD** 0 2 SPD 1 SPD	N/A DR BLOWER** N/A 1 SPD (12A)	YES YES YES YES	5.5kW 5.5kW 5.5kW 5.5kW
ECO-401 Series	CS6109B-US-F CS6209B-US-F CS6229B-US-F CS6239B-US-F*	VS500Z VS501Z VS511Z VS513Z/510Z	2 SPD 2 SPD 2 SPD 2 SPD	N/A 1 SPD** (2 SPD 1 SPD	N/A DR BLOWER** N/A 1 SPD (12A)	YES YES YES YES	5.5kW 5.5kW 5.5kW 5.5kW

WIRELESS I/R REMOTE KIT





Wireless I/R Remote Kit HQ PT#: 48-0197 (parts available separately)

All Hydro-Quip control systems include a spaside as standard. If an optional spaside is desired, please contact your Hydro-Quip representative for more details.

INSTALLATION KIT (Included)

Kit Includes:

Spaside Control (See Above) **Spaside Adapter Plate Component Cords** 2" Tailpieces w/Gaskets 12V Light Assembly





	REPLACEMENT PARTS FOR CS6000B SOLID STATE SERIES							
Model	Circuit Board	Spaside	M7™ Sensors (46")	Heater Element (5.5kW)	Heater Assy (15")			
CS6109B-US	33-0032A	34-0225-U	34-0202B (x2)	12-0100-K	22-87M-S00-1F03			
CS6209B-US	33-0032B	34-0225-U	34-0202B (x2)	12-0100-K	22-87M-S00-1F03			
CS6229B-US	33-0032C	34-0225-U	34-0202B (x2)	12-0100-K	22-87M-S00-1F03			
CS6239B-US	33-0032D	34-0225-U	34-0202B (x2)	12-0100-K	22-87M-S00-1F03			
CS6109B-US-F	33-0032A	34-0226-U	34-0202B (x2)	12-0100-K	22-87M-S00-1F03			
CS6209B-US-F	33-0032B	34-0226-U	34-0202B (x2)	12-0100-K	22-87M-S00-1F03			
CS6229B-US-F	33-0032C	34-0226-U	34-0202B (x2)	12-0100-K	22-87M-S00-1F03			
CS6239B-US-F	33-0032D	34-0226-U	34-0202B (x2)	12-0100-K	22-87M-S00-1F03			
	F	or a complete lis	t of parts, refer to our	Parts Catalog				

SYSTEM SPECIFICATIONS

ELECTRICAL INPUT SPECIFICATION: SINGLE PHASE, 120/240VAC, 60HZ FLOW RATE: 23 GPM Min.

ELECTRICAL OUTPUT SPECIFICATION:

CIRCUIT(S) **MAXIMUM AMPS** PUMP(S) 12A **BLOWER** 12A 1A **OZONE** CIRCULATION PUMP 4A 12V LIGHT 1A **HEATER** 23A

SYSTEM DIMENSIONS: 15"W x 11"H x 6"D

SHIPPING WEIGHT: **18 LBS**

PACKAGING / SHIPPING: INDIVIDUAL (HQ STOCK) FOB CORONA, CA 92880



Duplex

ES6000B Standard Series Solid State Equipment Systems



STANDARD FEATURES

M7™ Technology Equipped 1.325/5.5KW, 15" Heater Assembly 2 SPD Pump (Various HP & Voltages)

1 HP Blower, 120V Spaside Control

All Circuits Convertible to 120 or 240VAC

12V Light Assembly Freeze Protection

Standard, Economy & Sleep Modes

Lighted Smart Cords

Easy To Install & Service Installation Kit Included

Detailed Owners Manual & Wiring Diagram

US and Canada UL Recognized

2 Year Warranty

OPTIONS

Versi-Heat Remote Heater with 60" Cords Various Heater Wattages Wireless Remote Control

	SUPPORT	ED PERIPHERA	LS AND C	RCUITS BY	MODEL		
Spaside Control	Model	Platform	Pump 1	Pump 2	Blower	Circ Pump	Heater
	ES6100B	VS500Z	2 SPD	N/A	N/A	YES	5.5kW
A. F. L. S.	ES6200B	VS501Z	2 SPD	1 SPD** C	R BLOWER**	YES	5.5kW
ECO-200 Series	ES6220B	VS511Z	2 SPD	2 SPD	N/A	YES	5.5kW
4.3"L x 1.6"H	ES6230B *	VS513Z/510Z	2 SPD	1 SPD	1 SPD (12A)	YES	5.5kW
	ES6100B-F	VS500Z	2 SPD	N/A	N/A	YES	5.5kW
* * * * * * * * * * * * * * * * * * *	ES6200B-F	VS501Z	2 SPD	1 SPD** C	R BLOWER**	YES	5.5kW
Beret Job Scop Light	ES6220B-F	VS511Z	2 SPD	2 SPD	N/A	YES	5.5kW
ECO-401 Series	ES6230B-F*	VS513Z/510Z	2 SPD	1 SPD	1 SPD (12A)	YES	5.5kW
6.3"L x 2.2"H	*Pump 2 & Blower butto	on work in sequence				**	Pump 2 OR Blo

Balboa™ Series

WIRELESS I/R REMOTE KIT

EQUIPMENT SYSTEM COMPONENT OPTIONS CHART



Wireless I/R Remote Kit HQ PT#: 48-0197 (parts available separately)

All Hydro-Quip control systems include a spaside as standard. If an optional spaside is desired, please contact your Hydro-Quip representative for more deta

Option Code*	Pump	Voltage	Blower	Voltage
-A	1 HP	120	1 HP	120
-B	1 HP	120	N/A	N/A
-C	1.5 HP	120	1 HP	120
-C5	1.5 HP	240	1 HP	120
-D	1.5 HP	120	N/A	N/A
-D5	1.5 HP	240	N/A	N/A
-E	2 HP	240	1 HP	120
-F	2 HP	240	N/A	N/A
-G	3 HP	240	1 HP	120
-H	3 HP	240	N/A	N/A
-J	4 HP	240	1 HP	120
K	4 HP	240	N/A	N/A
ails.	*Add (Option Code to	end of ES Mo	odel Number

	REPLACEMENT PARTS FOR ES6000B SOLID STATE SERIES								
Model	Circuit Board	Spaside	M7™ Sensors (12")	Heater Element (5.5kW)	Heater Assy (15")				
ES6100B	33-0032A	34-0225-U	34-0202 (x2)	12-0100-K	26-0017-M7				
ES6200B	33-0032B	34-0225-U	34-0202 (x2)	12-0100-K	26-0071-M7				
ES6220B	33-0032C	34-0225-U	34-0202 (x2)	12-0100-K	26-0071-M7				
ES6230B	33-0032D	34-0225-U	34-0202 (x2)	12-0100-K	26-0071-M7				
ES6100B-F	33-0032A	34-0226-U	34-0202 (x2)	12-0100-K	26-0071-M7				
ES6200B-F	33-0032B	34-0226-U	34-0202 (x2)	12-0100-K	26-0071-M7				
ES6220B-F	33-0032C	34-0226-U	34-0202 (x2)	12-0100-K	26-0071-M7				
ES6230B-F	33-0032D	34-0226-U	34-0202 (x2)	12-0100-K	26-0071-M7				
	Fo	or a complete list	of parts, refer to our	Parts Catalog					

SYSTEM SPECIFICATIONS

ELECTRICAL INPUT SPECIFICATION: SINGLE PHASE, 120/240VAC, 60HZ **SYSTEM DIMENSIONS:** 21.5"W x 12"H x 15"D

ELECTRICAL OUTPUT SPECIFICATION:

CIRCUIT(S) **MAXIMUM AMPS** PUMP(S) 12A 12A **BLOWER OZONE** 1A CIRCULATION PUMP 4A 12V LIGHT 1A **HEATER**

PACKAGING / SHIPPING: INDIVIDUAL (HQ STOCK) FOB CORONA, CA 92880

WARRANTY:

SHIPPING WEIGHT:

2 YEAR LIMITED WARRANTY STANDARD - CONTACT YOUR HYDRO-QUIP REPRESENTATIVE FOR MORE DETAILS

Some Assembly Required

58.7 LBS



Serial

CS6000B Solid State Series "SLIDE" Control Systems



"SLIDE" HEATER FEATURE!

Balboa Series

STANDARD FEATURES

M7™ Technology Equipped "SLIDE" 1.325/5.5KW, 15" Heater Assembly Spaside Control All Circuits Convertible to 120 or 240VAC 12V Light Assembly Freeze Protection Standard, Economy & Sleep Modes Lighted Smart Cords Easy To Install & Service Installation Kit (see below)

Detailed Owners Manual & Wiring Diagram

US and Canada UL Recognized

2 Year Warranty

OPTIONS

Versi-Heat Remote Heater with 60" Cords Various Heater Wattages Wireless Remote Control Less Heater Unit

SUPPORTED PERIPHERALS AND CIRCUITS BY MODEL

Spaside Control	Model	Platform	Pump 1	Pump 2	Blower	Circ Pump	Heater	
HT-701S Series	CS6229B-USZ CS6239B-USZ CS6339B-USZ	VS511SZ VS510SZ VS520SZ	2 SPD 2 SPD 2 SPD	2 SPD 1 SPD 2 SPD	N/A 1 SPD (12A) 1 SPD (12A)	YES YES YES	5.5kW 5.5kW 5.5kW	

SPASIDE OPTIONS



Wireless I/R Remote Kit HQ PT#: 48-0197 (parts available separately)

Auxiliary Spaside HQ PT#: 34-0228-U 7.5"L x 2.3"H

All Hydro-Quip control systems include a spaside as standard. If an optional spaside is desired, please contact your Hydro-Quip representative for more details **INSTALLATION KIT (Included)**



12V Light Assembly



FOB CORONA, CA 92880

REPLACEMENT PARTS FOR CS6000B SOLID STATE SERIES

Model	Circuit Board	Spaside	M7™ Sensors (46")	Heater Element (5.5kW)	Heater Assy (15")
CS6229B-USZ CS6239B-USZ CS6339B-USZ	33-0033A 33-0033 33-0033B	34-0227-U 34-0227-U 34-0227-U	34-0202B (x2) 34-0202B (x2) 34-0202B (x2)	12-0100-K 12-0100-K 12-0100-K	22-87M-S00-1F03 22-87M-S00-1F03 22-87M-S00-1F03
	F	or a complete list	of parts, refer to our F	Parts Catalog	

SYSTEM SPECIFICATIONS

ELECTRICAL INPUT SPECIFICATION: SINGLE PHASE, 120/240VAC, 60HZ **FLOW RATE:** 23 GPM Min.

ELECTRICAL OUTPUT SPECIFICATION:

CIRCUIT(S) **MAXIMUM AMPS** PUMP(S) 12A **BLOWER** 12A **OZONE** 1A CIRCULATION PUMP 4A 12V LIGHT 1A **HEATER** 23A

SYSTEM DIMENSIONS: 15"W x 11"H x 6"D

SHIPPING WEIGHT: **18 LBS**

PACKAGING / SHIPPING: INDIVIDUAL (HQ STOCK)

WARRANTY:



Serial

ES6000B Standard Series Solid State Equipment Systems



STANDARD FEATURES

M7™ Technology Equipped 1.325/5.5KW, 15" Heater Assembly 2 SPD Pump (Various HP & Voltages) 1 HP Blower, 120V Spaside Control All Circuits Convertible to 120 or 240VAC 12V Light Assembly

Freeze Protection Standard, Economy & Sleep Modes

Lighted Smart Cords

Easy To Install & Service Installation Kit Included

Detailed Owners Manual & Wiring Diagram US and Canada UL Recognized

2 Year Warranty

4 HP

240

N/A

N/A *Add Option Code to end of ES Model Number

58.7 LBS

OPTIONS

Versi-Heat Remote Heater with 60" Cords Various Heater Wattages Wireless Remote Control

Some Assembly Required

Kit Includes:

Remote Control

I/R Receiver Sensor (10')

HEATER

Balboa™Series

SUPPORTED PERIPHERALS AND CIRCUITS BY MODEL

Spaside Control	Model	Platform	Pump 1	Pump 2	Blower	Circ Pump	Heater
HT-701S Series 7.4"L x 3.2"H	ES6220B-Z	VS511SZ	2 SPD	2 SPD	N/A	YES	5.5kW
	ES6230B-Z	VS510SZ	2 SPD	1 SPD	1 SPD (12A)	YES	5.5kW
	ES6330B-Z	VS520SZ	2 SPD	2 SPD	1 SPD (12A)	YES	5.5kW

SPASIDE OPTIONS EQUIPMENT SYSTEM COMPONENT OPTIONS CHART Voltage **Option Code* Pump** Voltage Blower 1 HP 1 HP 120 -A 120 -B 1 HP 120 N/A N/A -C 1.5 HP 120 1 HP 120 -C5 1.5 HP 1 HP 240 120 -D 1.5 HP 120 N/A N/A -D5 240 N/A 1.5 HP N/A **Auxiliary Spaside** -E 2 HP 1 HP 240 120 HQ PT#: 34-0228-U Wireless I/R Remote Kit -F 2 HP 240 N/A N/A 7.5"L x 2.3"H HQ PT#: 48-0197 -G 3 HP 240 1 HP 120 (parts available separately) 3 HP -H 240 N/A N/A 4 HP 240 1 HP 120 All Hydro-Quip control systems include a spaside as standard. If an optional spaside is desired, please contact your Hydro-Quip representative for more details.

Model	Circuit Board	Spaside	M7™ Sensors (12")	Heater Element (5.5kW)	Heater Assy (15")
ES6220B-Z	33-0033A	34-0227-U	34-0202 (x2)	12-0100-K	26-0071-M7
ES6230B-Z	33-0033	34-0227-U	34-0202 (x2)	12-0100-K	26-0071-M7
ES6330B-Z	33-0033B	34-0227-U	34-0202 (x2)	12-0100-K	26-0071-M7

SYSTEM SPECIFICATIONS

SYSTEM DIMENSIONS: 21.5"W x 12"H x 15"D **ELECTRICAL INPUT SPECIFICATION:** SINGLE PHASE, 120/240VAC, 60HZ

ELECTRICAL OUTPUT	SPECIFICATION:
015 0115 (0)	

23A

CIRCUIT(S)	MAXIMUM AMPS		
PUMP(S)	12A	PACKAGING / SHIPPING : INDIVIDUAL (HQ STO	OCK)
BLOWER	12A	FOB CORONA, CA 92	2880
OZONE	1A	WARRANTY:	
CIRCULATION PUMP	4A	2 YEAR LIMITED WARRANTY STANDARD - CONTACT YOU	R
12V LIGHT	1A	HYDRO-QUIP REPRESENTATIVE FOR MORE DETAILS	

SHIPPING WEIGHT:



Duplex CS4000B Solid State Series "SLIDE" Control Systems



STANDARD FEATURES

M7™ Technology Equipped
"SLIDE" 1.325/5.5KW, "L" Heater Assembly
Spaside Control
All Circuits Convertible to 120 or 240VAC
12V Light Assembly
Freeze Protection
Standard, Economy & Sleep Modes
Lighted Smart Cords
Easy To Install & Service
Installation Kit (see below)
Detailed Owners Manual & Wiring Diagram
US and Canada UL Recognized
2 Year Warranty

OPTIONS

Versi-Heat Remote Heater with 60" Cords Various Heater Wattages Wireless Remote Control Less Heater Unit

"SLIDE" HEATER FEATURE!

Balboa™Series

Spaside Control	SUPPORTE Model	D PERIPHERA Platform	LS AND C Pump 1	IRCUITS BY Pump 2	MODEL Blower	Circ Pump	Heater
ECO-200 Series 4.3"L x 1.6"H	CS4109B-US CS4209B-US CS4229B-US CS4239B-US*	VS500Z VS501Z VS511Z VS513Z/510Z	2 SPD 2 SPD 2 SPD 2 SPD	N/A 1 SPD** 0 2 SPD 1 SPD	N/A PR BLOWER** N/A 1 SPD (12A)	YES YES YES YES	5.5kW 5.5kW 5.5kW 5.5kW
ECO-401 Series 6.3"L x 2.2"H	CS4109B-US-F CS4209B-US-F CS4229B-US-F CS4239B-US-F* *Pump 2 & Blower button	VS500Z VS501Z VS511Z VS513Z/510Z work in sequence	2 SPD 2 SPD 2 SPD 2 SPD	N/A 1 SPD** 0 2 SPD 1 SPD	N/A PR BLOWER** N/A 1 SPD (12A)	YES YES YES YES	5.5kW 5.5kW 5.5kW 5.5kW ** Pump 2 OR Blower

WIRELESS I/R REMOTE KIT





Wireless I/R Remote Kit HQ PT#: 48-0197 (parts available separately)

All Hydro-Quip control systems include a spaside as standard. If an optional spaside is desired, please contact your Hydro-Quip representative for more details.

INSTALLATION KIT (Included)

Kit Includes:

Spaside Control (See Above)
Spaside Adapter Plate
Component Cords
2" Tailpieces w/Gaskets
12V Light Assembly



	REPLA	CEMENT PART	TS FOR CS4000B S	OLID STATE SERIES	
Model	Circuit Board	Spaside	M7™ Sensors (46")	Heater Element (5.5kW)	"L" Heater Assy
CS4109B-US	33-0032A	34-0225-U	34-0202B (x2)	12-0100-K	22-67M-S00-1F03
CS4209B-US	33-0032B	34-0225-U	34-0202B (x2)	12-0100-K	22-67M-S00-1F03
CS4229B-US	33-0032C	34-0225-U	34-0202B (x2)	12-0100-K	22-67M-S00-1F03
CS4239B-US	33-0032D	34-0225-U	34-0202B (x2)	12-0100-K	22-67M-S00-1F03
CS4109B-US-F	33-0032A	34-0226-U	34-0202B (x2)	12-0100-K	22-67M-S00-1F03
CS4209B-US-F	33-0032B	34-0226-U	34-0202B (x2)	12-0100-K	22-67M-S00-1F03
CS4229B-US-F	33-0032C	34-0226-U	34-0202B (x2)	12-0100-K	22-67M-S00-1F03
CS4239B-US-F	33-0032D	34-0226-U	34-0202B (x2)	12-0100-K	22-67M-S00-1F03
		For a complete I	ist of parts, refer to o	ur Parts Catalog	

SYSTEM SPECIFICATIONS

ELECTRICAL INPUT SPECIFICATION: SINGLE PHASE,120/240VAC, 60HZ FLOW RATE: 23 GPM Min.

ELECTRICAL OUTPUT SPECIFICATION: SYSTEM DIMENSIONS: 15"W x 11"H x 6"D CIRCUIT(S) MAXIMUM AMPS
PUMP(S) 12A SHIPPING WEIGHT: 18 LBS
BLOWER 12A

BLOWER 12A
OZONE 1A PACKAGING / SHIPPING: INDIVIDUAL (HQ STOCK)
CIRCULATION PUMP 4A FOB CORONA, CA 92880
12V LIGHT 1A WARRANTY:



Duplex ES4000B Standard Series Solid State Equipment Systems



STANDARD FEATURES

M7™ Technology Equipped 1.325/5.5KW, "L" Heater Assembly 2 SPD Pump (Various HP & Voltages)

1 HP Blower, 120V Spaside Control

All Circuits Convertible to 120 or 240VAC

12V Light Assembly Freeze Protection

Standard, Economy & Sleep Modes

Lighted Smart Cords
Easy To Install & Service

Installation Kit Included

Detailed Owners Manual & Wiring Diagram US and Canada UL Recognized

2 Year Warranty

OPTIONS

Versi-Heat Remote Heater with 60" Cords Various Heater Wattages Wireless Remote Control

ES4100B VS500Z 2 SPD N/A N/A SES4200B VS501Z 2 SPD 1 SPD** OR BLOWER** ECO-200 Series ES4220B VS511Z 2 SPD 2 SPD N/A SES4230B* VS513Z/510Z 2 SPD 1 SPD 1 SPD (12A) ES4100B-F VS500Z 2 SPD N/A N/A	rc Pump Heater		ALS ANI	ORTED PERIPHER	SUPP	
ES4200B VS501Z 2 SPD 1 SPD** OR BLOWER** ECO-200 Series 4.3"L x 1.6"H ES4230B* VS513Z/510Z 2 SPD 1 SPD 1 SPD (12A) ES4100B-F VS500Z 2 SPD N/A N/A	то гипр пеацег	Pump 2 Blower Circ P	Pump	Platform	Model	Spaside Control
	YES 5.5kW YES 5.5kW YES 5.5kW YES 5.5kW	1 SPD** OR BLOWER** YE 2 SPD N/A YE	2 SPD 2 SPD	VS501Z VS511Z	ES4200B ES4220B	
ES4220B-F VS511Z 2 SPD 2 SPD OR N/A	YES 5.5kW YES 5.5kW YES 5.5kW YES 5.5kW	1 SPD** BLOWER** YES 2 SPD OR N/A YES	2 SPD 2 SPD	VS501Z VS511Z * VS513Z/510	ES4200B-F ES4220B-F ES4230B-F	

WIRELESS I/R REMOTE KIT **EQUIPMENT SYSTEM COMPONENT OPTIONS CHART Option Code* Pump** Voltage **Blower** Voltage 1 HP 1 HP 120 120 -B 1 HP N/A N/A 120 -C 1.5 HP 120 1 HP 120 Kit Includes: -C5 1 HP 1.5 HP 240 120 Remote Control -D 120 1.5 HP N/A N/A I/R Receiver Sensor (7') -D5 1.5 HP 240 N/A N/A -E 2 HP 240 1 HP 120 Wireless I/R Remote Kit -F 2 HP 240 N/A N/A HQ PT#: 48-0197 3 HP -G 240 (parts available separately) 1 HP 120 -H 3 HP 240 N/A N/A 4 HP 240 1 HP 120 -.1 All Hydro-Quip control systems include a spaside as standard. If an optional 4 HP -K 240 N/A N/A

	REPLA	CEMENT PART	S FOR ES4000B SO	OLID STATE SERIES	
Model	Circuit Board	Spaside	M7™ Sensors (12")	Heater Element (5.5kW)	"L" Heater Assy
ES4100B	33-0032A	34-0225-U	34-0202 (x2)	12-0100-K	22-67M-S00-1F03
ES4200B	33-0032B	34-0225-U	34-0202 (x2)	12-0100-K	22-67M-S00-1F03
ES4220B	33-0032C	34-0225-U	34-0202 (x2)	12-0100-K	22-67M-S00-1F03
ES4230B	33-0032D	34-0225-U	34-0202 (x2)	12-0100-K	22-67M-S00-1F03
ES4100B-F	33-0032A	34-0226-U	34-0202 (x2)	12-0100-K	22-67M-S00-1F03
ES4200B-F	33-0032B	34-0226-U	34-0202 (x2)	12-0100-K	22-67M-S00-1F03
ES4220B-F	33-0032C	34-0226-U	34-0202 (x2)	12-0100-K	22-67M-S00-1F03
ES4230B-F	33-0032D	34-0226-U	34-0202 (x2)	12-0100-K	22-67M-S00-1F03
		For a complete li	st of parts, refer to oເ	ır Parts Catalog	

SYSTEM SPECIFICATIONS

ELECTRICAL INPUT SPECIFICATION: SINGLE PHASE,120/240VAC, 60HZ **SYSTEM DIMENSIONS:** 18"W x 15"H x 15"D

ELECTRICAL OUTPUT SPECIFICATION:

Some Assembly Required

 CIRCUIT(S)
 MAXIMUM AMPS

 PUMP(S)
 12A

 BLOWER
 12A

 OZONE
 1A

 CIRCULATION PUMP
 4A

 12V LIGHT
 1A

 HEATER
 23A

PACKAGING / SHIPPING : INDIVIDUAL (HQ STOCK) FOB CORONA, CA 92880

WARRANTY:

SHIPPING WEIGHT:

2 YEAR LIMITED WARRANTY STANDARD - CONTACT YOUR HYDRO-QUIP REPRESENTATIVE FOR MORE DETAILS

spaside is desired, please contact your Hydro-Quip representative for more details.

58.7 LBS

*Add Option Code to end of ES Model Number



Serial **CS4000B Solid State Series** "SLIDE" Control Systems



Balboa[™]Series

STANDARD FEATURES

M7™ Technology Equipped "SLIDE" 1.325/5.5KW, "L" Heater Assembly Spaside Control All Circuits Convertible to 120 or 240VAC 12V Light Assembly Freeze Protection Standard, Economy & Sleep Modes Lighted Smart Cords Easy To Install & Service Installation Kit (see below)

Detailed Owners Manual & Wiring Diagram US and Canada UL Recognized

2 Year Warranty

OPTIONS

Versi-Heat Remote Heater with 60" Cords Various Heater Wattages Wireless Remote Control Less Heater Unit

SUPPORTED PERIPHERALS AND CIRCUITS BY MODEL

Spaside Control	Model	Platform	Pump 1	Pump 2	Blower	Circ Pump	Heater
HT-701S Series 7.4"L x 3.2"H	CS4229B-USZ CS4239B-USZ CS4339B-USZ	VS511SZ VS510SZ VS520SZ	2 SPD 2 SPD 2 SPD	2 SPD 1 SPD 2 SPD	N/A 1 SPD (12A) 1 SPD (12A)	YES YES YES	5.5kW 5.5kW 5.5kW

SPASIDE OPTIONS



"SLIDE" HEATER FEATURE!



Auxiliary Spaside HQ PT#: 34-0228-U 7.5"L x 2.3"H

All Hydro-Quip control systems include a spaside as standard. If an optional spaside is desired, please contact your Hydro-Quip representative for more details.

INSTALLATION KIT (Included)



Spaside Adapter Plate Component Cords 2" Tailpieces w/Gaskets

12V Light Assembly



15"W x 11"H x 6"D

REPLACEMENT PARTS FOR CS4000B SOLID STATE SERIES Model Circuit Board **Spaside** M7™ Sensors (46") Heater Element (5.5kW) "L" Heater Assy 34-0202B (x2) CS4229B-USZ 33-0033A 34-0227-U 12-0100-K 22-67M-S00-1F03 CS4239B-USZ 33-0033 34-0227-U 34-0202B (x2) 12-0100-K 22-67M-S00-1F03 CS4339B-USZ 33-0033B 34-0227-U 34-0202B (x2) 12-0100-K 22-67M-S00-1F03 For a complete list of parts, refer to our Parts Catalog

SYSTEM SPECIFICATIONS

ELECTRICAL INPUT SPECIFICATION: SINGLE PHASE, 120/240VAC, 60HZ **FLOW RATE:** 23 GPM Min.

ELECTRICAL OUTPUT SPECIFICATION:

CIRCUIT(S) MAXIMUM AMPS PUMP(S) 12A **BLOWER** 12A **OZONE** 1A CIRCULATION PUMP 4A 12V LIGHT 1A **HEATER** 23A

SHIPPING WEIGHT: **18 LBS**

PACKAGING / SHIPPING: INDIVIDUAL (HQ STOCK) FOB CORONA, CA 92880

WARRANTY:

SYSTEM DIMENSIONS:



Some Assembly Required

Kit Includes:

Remote Control

I/R Receiver Sensor (10')

Serial **ES4000B Standard Series Solid State Equipment Systems**



Balboa" Series

SUPPORTED PERIPHERALS AND CIRCUITS BY MODEL

STANDARD FEATURES

M7™ Technology Equipped 1.325/5.5KW, "L" Heater Assembly 2 SPD Pump (Various HP & Voltages) 1 HP Blower, 120V

Spaside Control

All Circuits Convertible to 120 or 240VAC

12V Light Assembly Freeze Protection

Standard, Economy & Sleep Modes

Lighted Smart Cords Easy To Install & Service

Installation Kit Inlcuded

Detailed Owners Manual & Wiring Diagram US and Canada UL Recognized

2 Year Warranty

OPTIONS

Versi-Heat Remote Heater with 60" Cords Various Heater Wattages Wireless Remote Control

Spaside Control	Model	Platform	Pump 1	Pump 2	Blower	Circ Pump	Heater	
### 1 Jun 2 Light HT-701S Series 7.4"L x 3.2"H	ES4220B-Z ES4230B-Z ES4330B-Z	VS511SZ VS510SZ VS520SZ	2 SPD 2 SPD 2 SPD	2 SPD 1 SPD 2 SPD	N/A 1 SPD (12A) 1 SPD (12A)	YES YES YES	5.5kW 5.5kW 5.5kW	

SPASIDE OPTIONS EQUIPMENT SYSTEM COMPONENT OPTIONS CHART Option Code* Voltage Blower **Pump** Voltage 1 HP 1 HP 120 120 -B 1 HP 120 N/A N/A -C 1.5 HP 120 1 HP 120 -C5 1.5 HP 1 HP 240 120 -D 1.5 HP 120 N/A N/A -D5 240 N/A 1.5 HP N/A **Auxiliary Spaside** -E 240 1 HP 2 HP 120 HQ PT#: 34-0228-U Wireless I/R Remote Kit -F 2 HP 240 N/A N/A 7.5"L x 2.3"H HQ PT#: 48-0197 -G 3 HP 240 1 HP 120 (parts available separately) -H 3 HP 240 N/A N/A 4 HP 240 1 HP 120 All Hydro-Quip control systems include a spaside as standard. If an optional

-K

4 HP

240

N/A

N/A

*Add Option Code to end of ES Model Number

Model	Circuit Board	Spaside	M7™ Sensors (12")	Heater Element (5.5kW)	"L" Heater Assy
ES4220B-Z	33-0033A	34-0227-U	34-0202 (x2)	12-0100-K	22-67M-S00-1F03
ES4230B-Z	33-0033	34-0227-U	34-0202 (x2)	12-0100-K	22-67M-S00-1F03
ES4330B-Z	33-0033B	34-0227-U	34-0202 (x2)	12-0100-K	22-67M-S00-1F03

SYSTEM SPECIFICATIONS

ELECTRICAL INPUT SPECIFICATION: SINGLE PHASE, 120/240VAC, 60HZ **SYSTEM DIMENSIONS:** 18"W x 15"H x 15"D **SHIPPING WEIGHT: ELECTRICAL OUTPUT SPECIFICATION:** 58.7 LBS **MAXIMUM AMPS** CIRCUIT(S) **PACKAGING / SHIPPING:** INDIVIDUAL (HQ STOCK)

PUMP(S) 12A **BLOWER** 12A OZONE 1A **CIRCULATION PUMP** 4A 12V LIGHT 1A **HEATER** 23A

spaside is desired, please contact your Hydro-Quip representative for more details.

FOB CORONA, CA 92880 WARRANTY: 2 YEAR LIMITED WARRANTY STANDARD - CONTACT YOUR HYDRO-QUIP REPRESENTATIVE FOR MORE DETAILS



Lite Leader

CS7000B Economy Series Solid State "SLIDE" Control Systems



STANDARD

"SLIDE" 1.375/5.5KW, 15" Heater Assembly Spaside Control
All Circuits Convertible to 120 or 240VAC
12V Light Assembly
Freeze Protection
Lighted Smart Cords
Easy To Install & Service
Brushed Aluminum Enclosure
Heater "ON" Indicator Light
Installation Kit (see below)
Detailed Owners Manual & Wiring Diagram
US and Canada UL Recognized
2 Year Warranty

"SLIDE" HEATER FEATURE!

Balboa™Series

SUPPORTED PERIPHERALS AND CIRCUITS BY MODEL										
Spaside Control	Model	Platform	Pump 1	Pump 2	Blower	Circ Pump	Heater			
ECO-LL Series 4.5"L x 2.25"H	CS7109B-US CS7109B-US-4.0	LITE LEADER LITE LEADER	2 SPD 2 SPD	N/A N/A	N/A N/A	N/A N/A	5.5kW 4.0kW			

INSTALLATION KIT (Included)



ECO-LL Series 4.5"L x 2.25"H

Kit Includes:

Spaside Control

Spaside Adapter Plate

Component Cords

2" Tailpieces w/Gaskets

12V Light Assembly



REPLACEMENT PARTS FOR CS7000B SOLID STATE SERIES										
Model	Circuit Board	Spaside	Pressure Switch	Dual Temp/HL Sensors	Heater Element	Heater Assy (15")				
CS7100B-US CS7100B-US-4.0	33-0031 33-0031	34-0229 34-0229	34-0178A 34-0178A	34-0202B 34-0202B	12-0100-K 12-0102-K	22-87B-B00-1FP3 22-85B-B00-1FP3				
	F	or a comp	lete list of parts,	refer to our Parts Ca	talog					

SYSTEM SPECIFICATIONS

ELECTRICAL INPUT SPECIFICATION: SINGLE PHASE,120/240VAC, 60HZ SYSTEM DIMENSIONS: 15"W x 10"H x 5"D

ELECTRICAL OUTPUT SPECIFICATION:

 CIRCUIT(S)
 MAXIMUM AMPS

 PUMP(S)
 12A

 OZONE
 1A

 12V LIGHT
 1A

 HEATER
 23A

SHIPPING WEIGHT: 15 LBS

PACKAGING / SHIPPING : INDIVIDUAL (HQ STOCK) FOB CORONA, CA 92880

WARRANTY:



Lite Leader CS7000B "Value" Series Solid State Control Systems



STANDARD

1.375/5.5KW, 15" Heater Assembly
Spaside Control
All Circuits Convertible to 120 or 240VAC
12V Light Assembly
Freeze Protection
Amp Receptacles
Easy To Install & Service
Brushed Aluminum Enclosure
Heater "ON" Indicator Light
Installation Kit (see below)
Detailed Owners Manual & Wiring Diagram
US and Canada UL Recognized
2 Year Warranty

	SUPPORTED PERIPHERALS AND CIRCUITS BY MODEL									
Spaside Control	Model	Platform	Pump 1	Pump 2	Blower	Circ Pump	Heater			
ECO-LL Series 4.5"L x 2.25"H	CS7100B-U-WP CS7100B-U-4.0-WP	LITE LEADER LITE LEADER	2 SPD 2 SPD	N/A N/A	N/A N/A	N/A N/A	5.5kW 4.0kW			

INSTALLATION KIT (Included)



ECO-LL Series 4.5"L x 2.25"H

Kit Includes:

Spaside Control

Spaside Adapter Plate

Component Cords

2" Tailpieces w/Gaskets

12V Light Assembly



REPLACEMENT PARTS FOR CS7000B SOLID STATE SERIES									
Model	Circuit Board	Spaside	Pressure Switch	Dual Temp/HL Sensors	Heater Element	Heater Assy (15")			
CS7100B-U-WP CS7100B-U-4.0-WP	33-0031 33-0031	34-0229 34-0229	34-0178 34-0178	34-0202D 34-0202D	12-0100-K 12-0102-K	26-0071-KSS 26-0071-KSS			
	F	or a comp	lete list of parts,	refer to our Parts Cat	alog				

SYSTEM SPECIFICATIONS

ELECTRICAL INPUT SPECIFICATION: SINGLE PHASE,120/240VAC, 60HZ **SYSTEM DIMENSIONS:** 15"W x 10"H x 5"D

ELECTRICAL OUTPUT SPECIFICATION:

 CIRCUIT(S)
 MAXIMUM AMPS

 PUMP(S)
 12A

 OZONE
 1A

 12V LIGHT
 1A

 HEATER
 23A

SHIPPING WEIGHT: 15 LBS

PACKAGING / SHIPPING : INDIVIDUAL (HQ STOCK) FOB CORONA, CA 92880

WARRANTY:



CS6000B "Value" Series Solid State Control Systems





Classic AMP Plugs

STANDARD FEATURES

M7™ Technology Equipped
1.325/5.5KW, 15" Heater Assembly
Amp Receptacles
Spaside Control
All Circuits Convertible to 120 or 240VAC
12V Light Assembly
Freeze Protection
Standard, Economy & Sleep Modes
Easy To Install & Service
Installation Kit (see below)
Detailed Owners Manual & Wiring Diagram
US and Canada UL Recognized
2 Year Warranty

OPTIONS

Various Heater Wattages Wireless Remote Control

Balboa™Series

Spaside Control	Model	Platform	Pump 1	RCUITS BY Pump 2	Blower	Circ Pump	Heater
	CS6100B-U-WP	VS500Z	2 SPD	N/A	N/A	YES	5.5kW
SUS SOCIETY	CS6200B-U-WP	VS501Z	2 SPD	1 SPD** (OR BLOWER**	YES	5.5kW
500 000 0 visa	CS6220B-U-WP	VS511Z	2 SPD	2 SPD	N/A	YES	5.5kW
ECO-200 Series 4.3"L x 1.6"H	CS6230B-U-WP*	VS513Z/510Z	2 SPD	1 SPD	1 SPD (12A)	YES	5.5kW
	CS6100B-U-F-WP	VS500Z	2 SPD	N/A	N/A	YES	5.5kW
	CS6200B-U-F-WP	VS501Z	2 SPD	1 SPD** (OR BLOWER**	YES	5.5kW
Sieer Jos - Trop Ujts	CS6220B-U-F-WP	VS511Z	2 SPD	2 SPD	N/A	YES	5.5kW
ECO-401 Series	CS6230B-U-F-WP*	VS513Z/510Z	2 SPD	1 SPD	1 SPD (12A)	YES	5.5kW
6.3"L x 2.2"H	*Pump 2 & Blower Button v	vork in sequence				** P	ump 2 OR Blov

WIRELESS I/R REMOTE KIT



Wireless I/R Remote Kit HQ PT#: 48-0197 (parts available separately)

All Hydro-Quip control systems include a spaside as standard. If an optional spaside is desired, please contact your Hydro-Quip representative for more details.

INSTALLATION KIT (Included)

HYDRO-QUIP REPRESENTATIVE FOR MORE DETAILS

Kit Includes:

Spaside Control (See Above)
Spaside Adapter Plate
Component Cords
2" Tailpieces w/Gaskets
12V Light Assembly



	REPL	ACEMENT PART	S FOR CS6000B SC	OLID STATE SERIES	
Model	Circuit Board	Spaside	M7™ Sensors (12")	Heater Element (5.5kW)	Heater Assy (15")
CS6100B-U-WP	33-0032A	34-0225-U	34-0202 (x2)	12-0100-K	26-0071-M7
CS6200B-U-WP	33-0032B	34-0225-U	34-0202 (x2)	12-0100-K	26-0071-M7
CS6220B-U-WP	33-0032C	34-0225-U	34-0202 (x2)	12-0100-K	26-0071-M7
CS6230B-U-WP	33-0032D	34-0225-U	34-0202 (x2)	12-0100-K	26-0071-M7
CS6100B-U-F-WP	33-0032A	34-0225-U	34-0202 (x2)	12-0100-K	26-0071-M7
CS6200B-U-F-WP	33-0032B	34-0225-U	34-0202 (x2)	12-0100-K	26-0071-M7
CS6220B-U-F-WP	33-0032C	34-0225-U	34-0202 (x2)	12-0100-K	26-0071-M7
CS6230B-U-F-WP	33-0032D	34-0225-U	34-0202 (x2)	12-0100-K	26-0071-M7
	Fo	or a complete list o	of parts, refer to our P	arts Catalog	

SYSTEM SPECIFICATIONS

ELECTRICAL INPUT SPECIFICATION: SINGLE PHASE,120/240VAC, 60HZ FLOW RATE: 23 GPM Min. **ELECTRICAL OUTPUT SPECIFICATION: SYSTEM DIMENSIONS:** 15"W x 11"H x 6"D CIRCUIT(S) **MAXIMUM AMPS** PUMP(S) SHIPPING WEIGHT: 18 LBS 12A **BLOWER** 12A OZONE 1A **PACKAGING / SHIPPING:** INDIVIDUAL (HQ STOCK) CIRCULATION PUMP 4A FOB CORONA, CA 92880 12V LIGHT 1A **WARRANTY:** 2 YEAR LIMITED WARRANTY STANDARD - CONTACT YOUR **HEATER** 23A



Serial CS6000B "Value" Series Solid State Control Systems





Classic AMP Plugs

STANDARD FEATURES

M7™ Technology Equipped
1.325/5.5KW, 15" Heater Assembly
Amp Receptacles
Spaside Control
All Circuits Convertible to 120 or 240VAC
12V Light Assembly
Freeze Protection
Standard, Economy & Sleep Modes
Easy To Install & Service
Installation Kit (see below)
Detailed Owners Manual & Wiring Diagram
US and Canada UL Recognized
2 Year Warranty

OPTIONS

Various Heater Wattages Wireless Remote Control

Balboa"Series

Spaside Control	Model	Platform	Pump 1	Pump 2	Blower	Circ Pump	Heater
### #################################	CS6220B-UZ-WP	VS511SZ	2 SPD	2 SPD	N/A	YES	5.5kW
	CS6230B-UZ-WP	VS510SZ	2 SPD	1 SPD	1 SPD (12A)	YES	5.5kW
	CS6330B-UZ-WP	VS520SZ	2 SPD	2 SPD	1 SPD (12A)	YES	5.5kW

SPASIDE OPTIONS



Wireless I/R Remote Kit HQ PT#: 48-0197 (parts available separately)

Auxiliary Spaside HQ PT#: 34-0228-U 7.5"L x 2.3"H

All Hydro-Quip control systems include a spaside as standard. If an optional spaside is desired, please contact your Hydro-Quip representative for more details.

INSTALLATION KIT (Included)



Spaside Control (See Above)
Spaside Adapter Plate
Component Cords
2" Tailpieces w/Gaskets
12V Light Assembly



Model	Circuit Board	Spaside	M7™ Sensors (12")	Heater Element (5.5kW)	Heater Assy (15")
CS6220B-UZ-WP	33-0033A	34-0227-U	34-0202 (x2)	12-0100-K	26-0071-M7
CS6230B-UZ-WP	33-0033	34-0227-U	34-0202 (x2)	12-0100-K	26-0071-M7
CS6330B-UZ-WP	33-0033B	34-0227-U	34-0202 (x2)	12-0100-K	26-0071-M7

SYSTEM SPECIFICATIONS

ELECTRICAL INPUT SPECIFICATION: SINGLE PHASE,120/240VAC, 60HZ **FLOW RATE:** 23 GPM Min.

ELECTRICAL OUTPUT SPECIFICATION:

 CIRCUIT(S)
 MAXIMUM AMPS

 PUMP(S)
 12A

 BLOWER
 12A

 OZONE
 1A

 CIRCULATION PUMP
 4A

 12V LIGHT
 1A

 HEATER
 23A

CVCTEM DIMENCIONS:

SYSTEM DIMENSIONS: 15"W x 11"H x 6"D

SHIPPING WEIGHT: 18 LBS

PACKAGING / SHIPPING : INDIVIDUAL (HQ STOCK) FOB CORONA, CA 92880

WARRANTY:



THE **SMART** CHOICE Solid State "SLIDE" Control Systems



STANDARD FEATURES

"SLIDE" 1.325/5.5KW, 15" Heater Assembly All Circuits Convertible to 120 or 240VAC Installation Kit (see below) Smart-Freeze Protection "VDS" Visual Diagnostics Lighted Smart Cords Pressure Switch Protected Detailed Owners Manual & Wiring Diagram 2 Year Warranty

OPTIONS

Versi-Heat Remote Heater with 60" Cords Various Heater Wattages Less Heater Unit

Full Size Spaside Controls (standard on some models)

	SUPPORTED PERIPHERALS AND CIRCUITS BY MODEL											
Model	Pump 1	Pump 2		Blower	Ozone	Circ Pump	12V Light	H/C GFCI	Warranty			
CS6109-US	2 SPD	N/A		N/A	YES	N/A	INCLUDED	NO	2 YEARS			
CS6209-US	2 SPD	1 SPD**	OR	BLOWER**	YES	YES	INCLUDED	NO	2 YEARS			
CS6229-US	2 SPD	2 SPD		N/A	YES	N/A	INCLUDED	NO	2 YEARS			
CS6239-US	2 SPD	1 SPD		1 SPD (8A)	YES	YES	INCLUDED	NO	2 YEARS			
CS6339-US	2 SPD	2 SPD		1 SPD (8A)	YES	YES	INCLUDED	NO	2 YEARS			
CS6109-US-HC	2 SPD	N/A		N/A `	YES	N/A	INCLUDED	YES	2 YEARS			
CS6209-US-HC	2 SPD	1 SPD**	OR	BLOWER**	YES	YES	INCLUDED	YES	2 YEARS			
CS6229-US-HC	2 SPD	2 SPD		N/A	YES	N/A	INCLUDED	YES	2 YEARS			
CS6239-US-HC	2 SPD	1 SPD		1 SPD (8A)	YES	YES	INCLUDED	YES	2 YEARS			
CS6339-US-HC	2 SPD	2 SPD		1 SPD (8A)	YES	YES	INCLUDED	YES	2 YEARS			

-F = Full size spaside on CS6109, 6209 & 6229 models only. (Add to the end of "CS" model number)

** Pump 2 or Blower only

SPASIDE OPTIONS



ECO-5 Spaside (Standard for CS6109) HQ PT#: 34-0207

Optional Eco-7 Spaside

(CS6109)



ECO-3 Spaside (Standard for CS6239,CS6339) HQ PT#: 34-0197



(Standard for CS6209, CS6229) HQ PT#: 34-0208



Optional Eco-8 Spaside (CS6209, CS6229) HQ PT#: 34-0198A

INSTALLATION KIT (Included)

Kit Includes:

Spaside Control (Eco-6 shown)

Spaside Adapter Plate

Component Cords

2" Tailpieces w/Gaskets

12V Light Assembly



All Hydro-Quip control systems include a spaside as standard. If an optional spaside is desired, please contact your Hydro-Quip representative for more details.

REPLACEMENT PARTS FOR CS6000 SOLID STATE SERIES

Model	Circuit Board	Spaside	Temp Sensor	Hi-Limit Sensor	Heater Element (5.5kW)	PSI Switch	Heater Assy (15")
CS6109-US/HC	33-0014A-R8	34-0207	34-0203	34-0201B	12-0100-K	34-0178A	22-87B-S00-1FP3
CS6209-US/HC	33-0024-R6	34-0208	34-0203D-36	34-0201D-36	12-0100-K	34-0178A	22-87B-S00-1FP3
CS6229-US/HC	33-0024D-R3	34-0208	34-0203D-36	34-0201D-36	12-0100-K	34-0178A	22-87B-S00-1FP3
CS6239-US/HC	33-0024B-R4	34-0197	34-0203D-36	34-0201D-36	12-0100-K	34-0178A	22-87B-S00-1FP3
CS6339-US/HC	33-0024E	34-0197	34-0203D-36	34-0201D-36	12-0100-K	34-0178A	22-87B-S00-1FP3
	F	or a comp	lete list of part	ts, refer to our P	arts Catalog		

SYSTEM SPECIFICATIONS

ELECTRICAL INPUT SPECIFICATION: SINGLE PHASE,120/240VAC, 60HZ **SYSTEM DIMENSIONS:** 15"W x 11"H x 6"D

ELECTRICAL OUTPUT SPECIFICATION:

CIRCUIT(S) **MAXIMUM AMPS** PUMP(S) 13A **BLOWER** A8 **OZONE** 2A CIRCULATION PUMP 5A 12V LIGHT 1A **HEATER** 23A

SHIPPING WEIGHT:

PACKAGING / SHIPPING: INDIVIDUAL (HQ STOCK) FOB CORONA, CA 92880

18 LBS

WARRANTY:



ES6000 Standard Series Solid State Equipment Systems



STANDARD FEATURES

1.325/5.5KW, 15" Heater Assembly

2 SPD Pump (various hp & voltage)

1 HP Blower, 120V

All Circuits Convertible to 120 or 240VAC

Installation Kit Included

Smart-Freeze Protection

"VDS" Visual Diagnostics

Lighted Smart Cords

Pressure Switch Protected Detailed Owners Manual & Wiring Diagram

2 Year Warranty

OPTIONS

Versi-Heat Remote Heater with 60" Cords

Various Heater Wattages

Full Size Spaside Controls (standard on some models)

Some Assembly Required

Gecko™Series

	SUPPORTED PERIPHERALS AND CIRCUITS BY MODEL											
Model	Pump 1	Pump 2		Blower	Ozone	Circ Pump	12V Light	H/C GFCI	Warranty			
ES6100	2 SPD	N/A		N/A	YES	N/A	INCLUDED	NO	2 YEARS			
ES6200	2 SPD	1 SPD**	OR	BLOWER**	YES	YES	INCLUDED	NO	2 YEARS			
ES6220	2 SPD	2 SPD		N/A	YES	N/A	INCLUDED	NO	2 YEARS			
ES6230	2 SPD	1 SPD		1 SPD (8A)	YES	YES	INCLUDED	NO	2 YEARS			
ES6330	2 SPD	2 SPD		1 SPD (8A)	YES	YES	INCLUDED	NO	2 YEARS			
ES6100-HC	2 SPD	N/A		N/A	YES	N/A	INCLUDED	YES	2 YEARS			
ES6200-HC	2 SPD	1 SPD**	OR	BLOWER**	YES	YES	INCLUDED	YES	2 YEARS			
ES6220-HC	2 SPD	2 SPD		N/A	YES	N/A	INCLUDED	YES	2 YEARS			
ES6230-HC	2 SPD	1 SPD		1 SPD (8A)	YES	YES	INCLUDED	YES	2 YEARS			
ES6330-HC	2 SPD	2 SPD		1 SPD (8A)	YES	YES	INCLUDED	YES	2 YEARS			
	See system compone	ent ontions chart h	elow for	r numn and blower	ontions							

⁻F = Full size spaside on ES6100, 6200 & 6220 models only. (Add to the end of "ES" model number)

SPASIDE OPTIONS



ECO-5 Spaside (Standard for ES6100) HQ PT#: 34-0207



ECO-3 Spaside (Standard for ES6230,ES6330) HQ PT#: 34-0197



14 **±**∴ †

ECO-6 Spaside

(Standard for ES6200, ES6220)

Optional Eco-8 Spaside

Optional Eco-7 Spaside (ES6100) (ES6200, ES6220) HQ PT#: 34-0198 HQ PT#: 34-0198A

All Hydro-Quip control systems include a spaside as standard. If an optional spaside is desired, please contact your Hydro-Quip representative for more details.

EQUIPMENT SYSTEM COMPONENT OPTIONS CHART

Option Code*	Pump	Voltage	Blower	Voltage
-A	1 HP	120	1 HP	120
-B	1 HP	120	N/A	N/A
-C	1.5 HP	120	1 HP	120
-C5	1.5 HP	240	1 HP	120
-D	1.5 HP	120	N/A	N/A
-D5	1.5 HP	240	N/A	N/A
-E	2 HP	240	1 HP	120
-F	2 HP	240	N/A	N/A
-G	3 HP	240	1 HP	120
-H	3 HP	240	N/A	N/A
-J	4 HP	240	1 HP	120
-K	4 HP	240	N/A	N/A
S.	*Add	d Option Code	to end of ES I	Model Number

REPLACEMENT PARTS FOR ES6000 SOLID STATE SERIES

Model	Circuit Board	Spaside	Temp Sensor	Hi-Limit Sensor	Heater Element (5.5kW)	PSI Switch	Heater Assy (15")
ES6100/HC	33-0014A-R8	34-0207	34-0203	34-0201B	12-0100-K	34-0178	26-0071
ES6200/HC	33-0024-R6	34-0208	34-0203D	34-0201D	12-0100-K	34-0178	26-0071
ES6220/HC	33-0024D-R3	34-0208	34-0203D	34-0201D	12-0100-K	34-0178	26-0071
ES6230/HC	33-0024B-R4	34-0197	34-0203D	34-0201D	12-0100-K	34-0178	26-0071
ES6330/HC	33-0024E	34-0197	34-0203D	34-0201D	12-0100-K	34-0178	26-0071
l		For a con	nplete list of pa	rts, refer to our l	Parts Catalog		

SYSTEM SPECIFICATIONS

ELECTRICAL INPUT SPECIFICATION: SINGLE PHASE,120/240VAC, 60HZ **SYSTEM DIMENSIONS:** 21.5"W x 12"H x 15"D

ELECTRICAL OUTPUT SPECIFICATION:

MAXIMUM AMPS CIRCUIT(S) PUMP(S) 13A **BLOWER** 8A **OZONE** 2A CIRCULATION PUMP 5A 1A 12V LIGHT **HEATER** 23A

SHIPPING WEIGHT: 58.7 LBS **PACKAGING / SHIPPING:** INDIVIDUAL (HQ STOCK)

FOB CORONA, CA 92880 **WARRANTY:**

^{**} Pump 2 or Blower only



HYDROQUIP[™] CS4000 Pump Mount Series

THE SMART CHOICE™ Solid State "SLIDE" Control Systems



"SLIDE" HEATER FEATURE!

HEATER SLIDES

FROM BOTTOM TO TOP!

STANDARD FEATURES

"SLIDE" 1.325/5.5KW, "L" Heater Assembly All Circuits Convertible to 120 or 240VAC Installation Kit (see below) Smart-Freeze Protection

"VDS" Visual Diagnostics

Lighted Smart Cords Pressure Switch Protected

Detailed Owners Manual & Wiring Diagram

2 Year Warranty

OPTIONS

Versi-Heat Remote Heater with 60" Cords Various Heater Wattages

INSTALLATION KIT (Included)

Less Heater Unit

Full Size Spaside Controls (standard on some models)

Gecko™Series

	SUPPORTED PERIPHERALS AND CIRCUITS BY MODEL											
Model	Pump 1	Pump 2		Blower	Ozone	Circ Pump	12V Light	H/C GFCI	Warranty			
CS4109-US	2 SPD	N/A	0.0	N/A	YES	N/A	INCLUDED	NO	2 YEARS			
CS4209-US CS4229-US	2 SPD 2 SPD	1 SPD** 2 SPD	OR	BLOWER** N/A	YES YES	YES N/A	INCLUDED INCLUDED	NO NO	2 YEARS 2 YEARS			
CS4239-US CS4339-US	2 SPD 2 SPD	1 SPD 2 SPD		1 SPD (8A) 1 SPD (8A)	YES YES	YES YES	INCLUDED INCLUDED	NO NO	2 YEARS 2 YEARS			
CS4109-US-HC	2 SPD	N/A		N/A	YES	N/A	INCLUDED	YES	2 YEARS			
CS4209-US-HC CS4229-US-HC	2 SPD 2 SPD	1 SPD** 2 SPD	OR	BLOWER** N/A	YES YES	YES N/A	INCLUDED INCLUDED	YES YES	2 YEARS 2 YEARS			
CS4239-US-HC	2 SPD	1 SPD		1 SPD (8A)	YES	YES	INCLUDED	YES	2 YEARS			
CS4339-US-HC	2 SPD	2 SPD		1 SPD (8A)	YES	YES	INCLUDED	YES	2 YEARS			

⁻F = Full size spaside on CS4109, 4209 & 4229 models only. (Add to the end of "CS" model number)

SPASIDE OPTIONS



ECO-5 Spaside (Standard for CS4109) HQ PT#: 34-0207

HEATER

Optional Eco-7 Spaside

(CS4109) HQ PT#: 34-0198



ECO-3 Spaside (Standard for CS4239,CS4339) HQ PT#: 34-0197



104 8 0 0 0

ECO-6 Spaside

(Standard for CS4209, CS4229)

Optional Eco-8 Spaside (CS4209, CS4229) HQ PT#: 34-0198A

Kit Includes:

Spaside Adapter Plate

Component Cords

2" Tailpieces w/Gaskets

12V Light Assembly



All Hydro-Quip control systems include a spaside as standard. If an optional spaside is desired, please contact your Hydro-Quip representative for more details.

REPLACEMENT PARTS FOR CS4000 SOLID STATE SERIES

Model	Circuit Board	Spaside	Temp Sensor	Hi-Limit Sensor	Heater Element (5.5kW)	PSI Switch	"L" Heater Assy
CS4109-US/HC	33-0014A-R8	34-0207	34-0203	34-0201B	12-0100-K	34-0178A	22-67B-S00-1FP3
CS4209-US/HC	33-0024-R6	34-0208	34-0203D-36	34-0201D-36	12-0100-K	34-0178A	22-67B-S00-1FP3
CS4229-US/HC	33-0024D-R3	34-0208	34-0203D-36	34-0201D-36	12-0100-K	34-0178A	22-67B-S00-1FP3
CS4239-US/HC	33-0024B-R4	34-0197	34-0203D-36	34-0201D-36	12-0100-K	34-0178A	22-67B-S00-1FP3
CS4339-US/HC	33-0024E	34-0197	34-0203D-36	34-0201D-36	12-0100-K	34-0178A	22-67B-S00-1FP3
(For a co	omplete list of p	oarts, refer to ou	r Parts Catalog		

SYSTEM SPECIFICATIONS

ELECTRICAL INPUT SPECIFICATION: SINGLE PHASE, 120/240VAC, 60HZ **SYSTEM DIMENSIONS:** 17"W x 9.5"H x 7.5"D

ELECTRICAL OUTPUT SPECIFICATION: SHIPPING WEIGHT: 18 LBS **MAXIMUM AMPS**

23A

CIRCUIT(S) PUMP(S) 13A **PACKAGING / SHIPPING:** INDIVIDUAL (HQ STOCK) **BLOWER** 88 FOB CORONA, CA 92880

OZONE 2A WARRANTY: CIRCULATION PUMP 5A 2 YEAR LIMITED WARRANTY STANDARD - CONTACT YOUR 12V LIGHT 1A HYDRO-QUIP REPRESENTATIVE FOR MORE DETAILS

^{**} Pump 2 or Blower only



ES4000 Pump Mount Series Solid State Equipment Systems



STANDARD FEATURES

1.325/5.5KW, "L" Heater Assembly 2 SPD Pump (various hp & voltage)

1 HP Blower, 120V

All Circuits Convertible to 120 or 240VAC

Installation Kit Included

Smart-Freeze Protection

"VDS" Visual Diagnostics

Lighted Smart Cords

Pressure Switch Protected

Detailed Owners Manual & Wiring Diagram

2 Year Warranty

OPTIONS

Versi-Heat Remote Heater with 60" Cords

Various Heater Wattages

Full Size Spaside Controls (standard on some models)

Some Assembly Required

Gecko "Series

	SUPPORTED PERIPHERALS AND CIRCUITS BY MODEL											
Model	Pump 1	Pump 2		Blower	Ozone	Circ Pump	12V Light	H/C GFCI	Warranty			
ES4100	2 SPD	N/A		N/A	YES	N/A	INCLUDED	NO	2 YEARS			
ES4200	2 SPD	1 SPD**	OR	BLOWER**	YES	YES	INCLUDED	NO	2 YEARS			
ES4220	2 SPD	2 SPD		N/A	YES	N/A	INCLUDED	NO	2 YEARS			
ES4230	2 SPD	1 SPD		1 SPD (8A)	YES	YES	INCLUDED	NO	2 YEARS			
ES4330 ES4100-HC	2 SPD 2 SPD	2 SPD N/A		1 SPD (8A) N/A	YES YES	YES N/A	INCLUDED INCLUDED	NO YES	2 YEARS 2 YEARS			
ES4200-HC	2 SPD	1 SPD**	OR	BLOWER**	YES	YES	INCLUDED	YES	2 YEARS			
ES4220-HC	2 SPD	2 SPD		N/A	YES	N/A	INCLUDED	YES	2 YEARS			
ES4230-HC	2 SPD	1 SPD		1 SPD (8A)	YES	YES	INCLUDED	YES	2 YEARS			
ES4330-HC	2 SPD	2 SPD		1 SPD (8A)	YES	YES	INCLUDED	YES	2 YEARS			
	See system compon	ent options chart be	elow fo	r nump and blower	ontions							

⁻F = Full size spaside on ES4100, 4200 & 4220 models only. (Add to the end of "ES" model number)

SPASIDE OPTIONS



ECO-5 Spaside (Standard for ES4100) HQ PT#: 34-0207

Optional Eco-7 Spaside

(ES4100) HQ PT#: 34-0198



ECO-3 Spaside (Standard for ES4230,ES4330) HQ PT#: 34-0197



(Standard for ES4200, ES4220) HQ PT#: 34-0208



Optional Eco-8 Spaside (ES4200, ES4220) HQ PT#: 34-0198A

Option Code*	Pump	Voltage	Blower	Voltage
-A	1 HP	120	1 HP	120
-B	1 HP	120	N/A	N/A
-C	1.5 HP	120	1 HP	120
-C5	1.5 HP	240	1 HP	120
-D	1.5 HP	120	N/A	N/A
-D5	1.5 HP	240	N/A	N/A
-E	2 HP	240	1 HP	120
-F	2 HP	240	N/A	N/A
-G	3 HP	240	1 HP	120
-H	3 HP	240	N/A	N/A
-J	4 HP	240	1 HP	120
-K	4 HP	240	N/A	N/A
S.	*Ad	d Option Code	to end of ES	Model Numb

EQUIPMENT SYSTEM COMPONENT OPTIONS CHART

All Hydro-Quip control systems include a spaside as standard. If an optional spaside is desired, please contact your Hydro-Quip representative for more details.

REPLACEMENT PARTS FOR ES4000 SOLID STATE SERIES

Model	Circuit Board	Spaside	Temp Sensor	Hi-Limit Sensor	Heater Element (5.5kW)	PSI Switch	"L" Heater Assy				
ES4100/HC	33-0014A-R8	34-0207	34-0203	34-0201B	12-0100-K	34-0178A	22-67B-S00-1FP3				
ES4200/HC	33-0024-R6	34-0208	34-0203D	34-0201D	12-0100-K	34-0178A	22-67B-S00-1FP3				
ES4220/HC	33-0024D-R3	34-0208	34-0203D	34-0201D	12-0100-K	34-0178A	22-67B-S00-1FP3				
ES4230/HC	33-0024B-R4	34-0197	34-0203D	34-0201D	12-0100-K	34-0178A	22-67B-S00-1FP3				
ES4330/HC	33-0024E	34-0197	34-0203D	34-0201D	12-0100-K	34-0178A	22-67B-S00-1FP3				
	For a complete list of parts, refer to our Parts Catalog										

SYSTEM SPECIFICATIONS

ELECTRICAL INPUT SPECIFICATION: SINGLE PHASE,120/240VAC, 60HZ **SYSTEM DIMENSIONS:** 18"W x 15"H x 15"D

ELECTRICAL OUTPUT SPECIFICATION:

 CIRCUIT(S)
 MAXIMUM AMPS

 PUMP(S)
 13A

 BLOWER
 8A

 OZONE
 2A

 CIRCULATION PUMP
 5A

 12V LIGHT
 1A

 HEATER
 23A

PACKAGING / SHIPPING : INDIVIDUAL (HQ STOCK)

58.7 LBS

FOB CORONA, CA 92880 WARRANTY: 2 YEAR LIMITED WARRANTY STANDARD - CONTACT YOUR

HYDRO-QUIP REPRESENTATIVE FOR MORE DETAILS

HEATER 23A

SHIPPING WEIGHT:

^{**} Pump 2 or Blower only



CS9700 Deluxe Series Solid State "SLIDE" Control Systems



STANDARD FEATURES
"SLIDE" 1.375/5.5KW. 15" Heater Assembly

"SLIDE 1.375/5.5KW, 15 Heater Assembly
All Circuits Convertible to 120 or 240VAC
Installation Kit (see below)
SMART-ECON Economy Mode Settings
SMART-FREEZE Protection
"VDS" Visual Diagnostics
Lighted SMART Cords
"Paint-Lock" Rust Proof Enclosure
Heater "ON" Indicator Light
Detailed Owners Manual & Wiring Diagram
2 Year Warranty

OPTIONS

Versi-Heat Remote Heater with 60" Cord Less Heater Unit IR Remote Control Kit Auxiliary Spaside

"SLIDE" HEATER FEATURE!

Gecko™Series

SUPPORTED PERIPHERALS AND CIRCUITS BY MODEL										
Model	Pump 1	Pump 2	Pump 3	Blower	Aux Circuit	Ozone	Circ Pump	12V Light	H/C GFCI	Warranty
CS9709-US CS9709-US-HC	1 or 2 SPD 1 or 2 SPD	1 or 2 SPD 1 or 2 SPD	1 SPD 1 SPD	1-3 SPD 1-3 SPD	2 2	YES YES	YES YES	1-3 STEP 1-3 STEP	NO YES	2 YEARS 2 YEARS

SPASIDE OPTIONS



Auxiliary Spaside HQ PT#: 34-0210



HTII 10 Button Spaside (Included) HQ PT#: 34-0190A



IR Remote Kit HQ PT#: 48-0196A-6

INSTALLATION KIT (Included)

Kit Includes:

Spaside Control

Spaside Adapter Plate

Component Cords

2" Tailpieces w/Gaskets

12V Light Assembly



All Hydro-Quip control systems include a spaside as standard. If an optional spaside is desired, please contact your Hydro-Quip representative for more details.

	REPLACEMENT PARTS FOR CS9700 SOLID STATE SERIES										
Model	Circuit Board	Spaside	Temp Sensor	Hi-Limit Sensor	Heater Element (5.5kW)	PSI Switch	Heater Assy (15")				
CS9709-US/HC	33-0025-R8	34-0190A	34-0203D-36	34-0201D-36	12-0100-K	34-0178A	22-87B-S00-1FP3				
		For a com	plete list of par	ts, refer to our Pa	arts Catalog						

SYSTEM SPECIFICATIONS

ELECTRICAL INPUT SPECIFICATION: SINGLE PHASE,120/240VAC, 60HZ **SYSTEM DIMENSIONS:** 15"W x 14"H x 6"D

ELECTRICAL OUTPUT SPECIFICATION:

 CIRCUIT(S)
 MAXIMUM AMPS

 PUMP(S)
 13A

 BLOWER
 8A

 OZONE
 2A

 CIRCULATION PUMP
 5A

 12V LIGHT
 1A

 HEATER
 23A

SHIPPING WEIGHT: 23 LBS

PACKAGING / SHIPPING : INDIVIDUAL (HQ STOCK) FOB CORONA, CA 92880

WARRANTY:



ES9700 Deluxe Series Solid State Equipment Systems



STANDARD FEATURES

1.375/5.5KW, 15" Heater Assembly 2 Speed Pump (various hp & voltage) 1 HP Blower, 120V HT-II Spaside Control, 10' Cord All Circuits Convertible to 120 or 240VAC Installation Kit Included Smart-Freeze Protection "VDS" Visual Diagnostics **Lighted Smart Cords** "Paint-Lock" Rust Proof Enclosure Pressure Switch Protected

Detailed Owners Manual & Wiring Diagram

2 Year Warranty

OPTIONS

Various Heater Wattages IR Remote Control Kit Auxiliary Spaside

Some Assembly Required

Gecko™Series

SUPPORTED PERIPHERALS AND CIRCUITS BY MODEL										
Model	Pump 1	Pump 2	Pump 3	Blower	Aux Circuit	Ozone	Circ Pump	12V Light	H/C GFCI	Warranty
ES9700 ES9700-HC	1 or 2 SPD 1 or 2 SPD	1 or 2 SPD 1 or 2 SPD	1 SPD 1 SPD	1-3 SPD 1-3 SPD	2 2	YES YES	YES YES	1-3 STEP 1-3 STEP	NO YES	2 YEARS 2 YEARS

See system component options chart below for pump and blower options

SPASIDE OPTIONS







HTII 10 Button Spaside (Included) HQ PT#: 34-0190A



IR Remote Kit HQ PT#: 48-0196A-6

EQUIPMENT	SYSTEM	COMPONENT	OPTIONS	CHART
Option Code*	Pump	Voltage	Blower	Voltage

•	•	•		Ū
-A	1 HP	120	1 HP	120
-B	1 HP	120	N/A	N/A
-C	1.5 HP	120	1 HP	120
-C5	1.5 HP	240	1 HP	120
-D	1.5 HP	120	N/A	N/A
-D5	1.5 HP	240	N/A	N/A
-E	2 HP	240	1 HP	120
-F	2 HP	240	N/A	N/A
-G	3 HP	240	1 HP	120
-H	3 HP	240	N/A	N/A
-J	4 HP	240	1 HP	120
-K	4 HP	240	N/A	N/A

All Hydro-Quip control systems include a spaside as standard. If an optional spaside is desired, please contact your Hydro-Quip representative for more details.

*Add Option Code to end of ES Model Number

	REPLACEMENT PARTS FOR ES9700 SOLID STATE SERIES										
Model	Circuit Board	Spaside	Temp Sensor	Hi-Limit Sensor	Heater Element(5.5kW)	PSI Switch	Heater Assy (15")				
ES9700/HC	33-0025-R8	34-0190A	34-0203D	34-0201D	12-0100-K	34-0178	26-0071				
	F	or a complet	te list of parts, ı	efer to our Parts	s Catalog						

SYSTEM SPECIFICATIONS

ELECTRICAL INPUT SPECIFICATION: SINGLE PHASE.120/240VAC. 60HZ **SYSTEM DIMENSIONS:** 21.5"W x 15"H x 15"D

ELECTRICAL OUTPUT SPECIFICATION:

CIRCUIT(S) **MAXIMUM AMPS** PUMP(S) 13A BLOWER A8 2A OZONE **CIRCULATION PUMP** 5A 12V LIGHT 1A **HEATER** 23A

SHIPPING WEIGHT: 60.1 LBS

PACKAGING / SHIPPING: INDIVIDUAL (HQ STOCK) FOB CORONA, CA 92880

WARRANTY:



THE SMART CHOICE Solid State "SLIDE" Control Systems



STANDARD FEATURES

"SLIDE" 1.375/5.5KW, 15" Heater Assembly All Circuits Convertible to 120 or 240VAC Installation Kit (see below) Smart-Freeze Protection Brushed Aluminum Enclosure Heater "ON" Indicator Light Detailed Owners Manual & Wiring Diagram 2 Year Warranty

OPTIONS

Versi-Heat Remote Heater with 60"Cord Less Heater Unit

"SLIDE" HEATER FEATURE!

Gecko™Series

SUPPORTED PERIPHERALS AND CIRCUITS BY MODEL											
Model	Pump 1	Pump 2		Blower	Ozone	Circ Pump	12V Light	Warranty			
CS7109-US	2 SPD	N/A		N/A	YES	N/A	INCLUDED	2 YEARS			
CS7109-US-F	2 SPD	N/A		N/A	YES	N/A	INCLUDED	2 YEARS			
CS7509-US	1 or 2 SPD	1 SPD**	OR	BLOWER**	YES	YES	INCLUDED	2 YEARS			
CS7509-US-F	1 or 2 SPD	1 SPD**	OR	BLOWFR**	YES	YES	INCLUDED	2 YEARS			

-F = Full size spaside ** Pump 2 or Blower only

SPASIDE OPTIONS



ECO-5 Spaside (Standard for CS7109) HQ PT#: 34-0207



Optional Eco-7 Spaside (CS7109) HQ PT#: 34-0198



ECO-6 Spaside (Standard for CS7509) HQ PT#: 34-0208



Optional Eco-8 Spaside (CS7509) HQ PT#: 34-0198A

INSTALLATION KIT (Included)

Kit Includes:

Spaside Control (Eco-6 shown)

Spaside Adapter Plate

Component Cords

2" Tailpieces w/Gaskets

12V Light Assembly



All Hydro-Quip control systems include a spaside as standard. If an optional spaside is desired, please contact your Hydro-Quip representative for more details.

REPLACEMENT PARTS FOR CS7000 SOLID STATE SERIES

Model	Circuit Board	Spaside	Temp Sensor	Hi-Limit Sensor	Heater Element (5.5kW)	PSI Switch	Heater Assy (15")
CS7109-US CS7509-US	33-0014A-R8 33-0012-R2	34-0207 34-0208	34-0203 34-0203D-36	34-0201B 34-0201D-36	12-0100-K 12-0100-K	34-0178A 34-0178A	22-87B-S00-1FP3 22-87B-S00-1FP3
	Fo	r a comple	to list of narts	refer to our Parts	Catalog		J

For a complete list of parts, refer to our Parts Catalog

SYSTEM SPECIFICATIONS

ELECTRICAL INPUT SPECIFICATION: SINGLE PHASE, 120/240VAC, 60HZ **SYSTEM DIMENSIONS:** 15"W x 10"H x 5"D

ELECTRICAL OUTPUT SPECIFICATION:

CIRCUIT(S)	MAXIMUM AMPS
PUMP(S)	13A
BLOWER	8A
OZONE	2A
CIRCULATION PUMP	5A
12V LIGHT	1A
HEATER	23A

SHIPPING WEIGHT: 15 LBS

PACKAGING / SHIPPING: INDIVIDUAL (HQ STOCK) FOB CORONA, CA 92880

WARRANTY-



CS7000 "Value" Series **Solid State Control Systems**



STANDARD FEATURES

2 year warranty

120/240V Convertible Power 1.375/5.5KW, 15" Heater Assembly Amp Receptacles Brushed Aluminum Control Box Installation Kit (see below) **Smart-Freeze Protection** Heater "ON" Indicator Light

Detailed Owners Manual & Wiring Diagram

Gecko™Series

SUPPORTED PERIPHERALS AND CIRCUITS BY MODEL											
Model Pump 1 Pump 2 Blower Ozone Circ Pump 12V Light Warranty											
CS7100-U-WP	2 SPD	N/A	N/A	YES	N/A	YES	2 YEARS				
CS7100-U-F-WP	2 SPD	N/A	N/A	YES	N/A	YES	2 YEARS				
CS7500-U-WP	1 or 2 SPD	1 SPD** OR	BLOWER**	YES	YES	YES	2 YEARS				
CS7500-U-F-WP	1 or 2 SPD	1 SPD** OR	BLOWER**	YES	YES	YES	2 YEARS				

⁻F = Full size spaside

SPASIDE OPTIONS



ECO-5 Spaside HQ PT#: 34-0207



Optional Eco-7 Spaside (CS7100-U-F) HQ PT#: 34-0198



ECO-6 Spaside HQ PT#: 34-0208



Optional Eco-8 Spaside (CS7500-U-F) HQ PT#: 34-0198A

INSTALLATION KIT (Included)

Kit Includes:

Spaside Control (Eco-6 shown)

Spaside Adapter Plate

Component Cords

2" Tailpieces w/Gaskets

12V Light Assembly



All Hydro-Quip control systems include a spaside as standard. If an optional spaside is desired, please contact your Hydro-Quip representative for more details.

	REPLACE	MENT PAR	RTS FOR CS70	00 WATER PRO	SOLID STATE SERI	ES	
Model	Circuit Board	Spaside	Temp Sensor	Hi-Limit Sensor	Heater Element (5.5kW)	PSI Switch	Heater Assy (15")
CS7100-U-WP CS7500-U-WP	33-0014A-R8 33-0012-R2	34-0207 34-0208	34-0203 34-0203D-18	34-0201 34-0201D	12-0100-K 12-0100-K	34-0178 34-0178	26-0071-7KSS 26-0071-7KSS
		For a con	nplete list of par	ts, refer to our Pa	arts Catalog		

SYSTEM SPECIFICATIONS

ELECTRICAL INPUT SPECIFICATION: SINGLE PHASE, 120/240VAC, 60HZ **SYSTEM DIMENSIONS:** 15"W x 10"H x 5"D

ELECTRICAL OUTPUT SPECIFICATION:

CIRCUIT(S) **MAXIMUM AMPS** PUMP(S) 13A **BLOWER** 8A **OZONE** 2A CIRCULATION PUMP N/A 12V LIGHT 1A **HEATER** 23A

SHIPPING WEIGHT: 15 LBS


PACKAGING / SHIPPING: INDIVIDUAL (HQ STOCK)

FOB CORONA, CA 92880

WARRANTY:



CS6000 "Value" Series **Solid State Control Systems**



STANDARD FEATURES

120/240V Convertible Power 1.325/5.5KW, 15" Heater Assembly Amp Receptacles Brushed Aluminum Control Box Installation Kit (see below) Smart-Freeze Protection Heater "ON" Indicator Light Detailed Owners Manual & Wiring Diagram 2 Year Warranty

INSTALLATION KIT (Included)

Gecko™Series

Model	Pump 1	Pump 2		Blower	Ozone	Circ Pump	12V Light	H/C GFCI	Warranty
CS6100-U-WP	2 SPD	N/A		N/A	YES	N/A	INCLUDED	NO	2 YEARS
CS6200-U-WP	2 SPD	1 SPD**	OR	BLOWER**	YES	YES	INCLUDED	NO	2 YEARS
CS6220-U-WP	2 SPD	2 SPD		N/A	YES	N/A	INCLUDED	NO	2 YEARS
CS6230-U-WP	2 SPD	1 SPD		1 SPD (8A)	YES	YES	INCLUDED	NO	2 YEARS
CS6330-U-WP	2 SPD	2 SPD		1 SPD (8A)	YES	YES	INCLUDED	NO	2 YEARS
CS6100-U-HC-WP	2 SPD	N/A		N/A `	YES	N/A	INCLUDED	YES	2 YEARS
CS6200-U-HC-WP	2 SPD	1 SPD**	OR	BLOWER**	YES	YES	INCLUDED	YES	2 YEARS
CS6220-U-HC-WP	2 SPD	2 SPD		N/A	YES	N/A	INCLUDED	YES	2 YEARS
CS6230-U-HC-WP	2 SPD	1 SPD		1 SPD (8A)	YES	YES	INCLUDED	YES	2 YEARS
CS6330-U-HC-WP	2 SPD	2 SPD		1 SPD (8A)	YES	YES	INCLUDED	YES	2 YEARS

⁻F = Full size spaside on CS6100, 6200 & 6220 models only. (Add to the end of "CS" model number)

SPASIDE OPTIONS



ECO-5 Spaside (Standard for CS6100)





Optional Eco-7 Spaside (CS6100-U-F



ECO-3 Spaside (Standard for CS6230,CS6330) HQ PT#: 34-0197



ECO-6 Spaside

(Standard for CS6200, CS6220)

HQ PT#: 34-0208

Optional Eco-8 Spaside (CS6200-U-F, CS6220-U-F)

Kit Includes:

Spaside Control (Eco-3 shown)

Component Cords

2" Tailpieces w/Gaskets

Spaside Adapter Plate

12V Light Assembly



All Hydro-Quip control systems include a spaside as standard. If an optional spaside is desired, please contact your Hydro-Quip representative for more details.

REPLACEMENT PARTS FOR CS6000 WATER PRO SOLID STATE SERIES

Model	Circuit Board	Spaside	Temp Sensor	Hi-Limit Sensor	Heater Element (5.5kW)	PSI Switch	Heater Assy (15")
CS6100-U/HC-WP	33-0014A-R8	34-0207	34-0203	34-0201	12-0100-K	34-0178	26-0071
CS6200-U/HC-WP	33-0024-R6	34-0208	34-0203D-18	34-0201D	12-0100-K	34-0178	26-0071
CS6220-U/HC-WP	33-0024D-R3	34-0208	34-0203D-18	34-0201D	12-0100-K	34-0178	26-0071
CS6230-U/HC-WP	33-0024B-R4	34-0197	34-0203D-18	34-0201D	12-0100-K	34-0178	26-0071
CS6330-U/HC-WP	33-0024E	34-0197	34-0203D-18	34-0201D	12-0100-K	34-0178	26-0071
		For a co	mplete list of p	arts, refer to our	Parts Catalog		

SYSTEM SPECIFICATIONS

ELECTRICAL INPUT SPECIFICATION: SINGLE PHASE, 120/240VAC, 60HZ **SYSTEM DIMENSIONS:** 15"W x 11"H x 4"D

ELECTRICAL OUTPUT SPECIFICATION: SHIPPING WEIGHT: 14 LBS CIRCUIT(S) **MAXIMUM AMPS**

PUMP(S) 13A **PACKAGING / SHIPPING:** INDIVIDUAL (HQ STOCK) BLOWER A8 FOB CORONA, CA 92880 2Δ **OZONE**

CIRCULATION PUMP N/A **WARRANTY:** 12V LIGHT 1A 2 YEAR LIMITED WARRANTY STANDARD - CONTACT YOUR **HEATER** 23A HYDRO-QUIP REPRESENTATIVE FOR MORE DETAILS

^{**} Pump 2 or Blower only



Lo-Flo Circulation Series Solid State Control Systems



STANDARD FEATURES

Titanium Low Watt Density Heater Element 1.0/4.0kW Lo-Flo Heater Assy Flow Switch Control 3/4" x 1" Barb Adapter Installation Kit Included (see below) SMART-ECON Economy Mode Settings* SMART-FREEZE Protection "VDS" Visual Diagnostics (not on CS7506) Lighted SMART Cords "Paint-Lock" Rust Proof Enclosure Heater "ON" Indicator Light

OPTIONS

2 Year Warranty

Full Size Spaside Controls (standard on some models)

*CS9706 model only

2 YEARS

SUPPORTED PERIPHERALS AND CIRCUITS BY MODEL										
Model	Pump 1	Pump 2	Pump 3	Blower	Ozone	Circ Pump	12V Light	H/C GFCI	Warranty	
CS6206-U-LFC	2 SPD	1 SPD**	N/A	1 SPD**	YES	YES	YES	NO	2 YEARS	
CS6236-U-LFC	2 SPD	1 SPD	N/A	1 SPD	YES	YES	YES	NO	2 YEARS	
CS6336-U-LFC	2 SPD	2 SPD	N/A	1 SPD	YES	YES	YES	NO	2 YEARS	
CS7506-U-LFC	1 or 2 SPD	1 SPD**	N/A	1 SPD**	YES	YES	YES	NO	2 YEARS	

YES

1-3 SPD

Gecko™Series

SPASIDE OPTIONS

1 or 2 SPD

1 or 2 SPD



ECO-6 Spaside (Standard for CS6206, CS7506) HQ PT#: 34-0208



Optional Eco-8 Spaside (CS6206, CS7506) HQ PT#: 34-0198A



1 SPD

ECO-3 Spaside (Standard for CS6236,CS6336) HQ PT#: 34-0197



HTII 10 Button Spaside (CS9706) HQ PT#: 34-0190A

All Hydro-Quip control systems include a spaside as standard. If an optional spaside is desired, please contact your Hydro-Quip representative for more details.

INSTALLATION KIT (Included)

1-3 STEP

Kit Includes:

YES

Spaside Control (HTII shown)

Spaside Adapter Plate

Component Cords

Flow Switch Tee Assy

3/4" Clear Tubing

SS Clamps

12V Light Assembly



NO

REPLACEMENT PARTS FOR LO-FLO SERIES

Model	Circuit Board	Spaside	Temp Sensor	Hi-Limit Sensor	Flow Switch Assy	Heater Assy (Lo-Flo)
CS6206-U-LFC/HC CS6236-U-LFC/HC CS6336-U-LFC/HC CS7506-U-LFC/HC CS9706-U-LFC/HC	33-0024B-R4 33-0024E 33-0012-R2	34-0208 34-0197 34-0197 34-0208 34-0190A	34-0203D-72 34-0203D-72 34-0203D-72 34-0203D-72 34-0203D-72	34-0201D-72 34-0201D-72 34-0201D-72 34-0201D-72 34-0201D-72	48-0223C 48-0223C 48-0223C 48-0223C 48-0223C	22-7P8-000-0PP6 22-7P8-000-0PP6 22-7P8-000-0PP6 22-7P8-000-0PP6 22-7P8-000-0PP6
		For a com	plete list of part	s, refer to our Parts	Catalog	

SYSTEM SPECIFICATIONS

ELECTRICAL INPUT SPECIFICATION: SINGLE PHASE, 120/240VAC, 60HZ

ELECTRICAL OUTPUT SPECIFICATION:

CAL OUTFUT SPECIFICATION.	
CIRCUIT(S)	MAXIMUM AMPS
PUMP(S)	13A
BLOWER	8A
OZONE	2A
CIRCULATION PUMP	5A
12V LIGHT	1A
HEATER	23A

SYSTEM DIMENSIONS:

EO A OLUBBINO MEIOLIT

13"W x 9.25"H x 4.5"D

DIMENSIONS OF CONTROL BOXES & SHIPPING WEIGHT: CS7506: 8.5"W x 10"H x 4.25"D 15.2 LBS

 CS7506:
 8.5"W x 10"H x 4.25"D
 15.2 LBS

 CS6206, 6236, 6336:
 12.5"W x 11"H x 4.25"D
 21.8 LBS

 CS9706:
 13"W x 14"H x 4"D
 25.8 LBS

PACKAGING / SHIPPING: INDIVIDUAL (HQ STOCK) FOB CORONA, CA 92880

WARRANTY:

CS9706-U-LFC

** Pump 2 or Blower only



CS6000 Standard Series Air "SLIDE" Control Systems



STANDARD FEATURES

"SLIDE"1.375/5.5KW, 15" Heater Assembly 24hr Timer With Mode Switch Full Range Thermostat Spaside Receptacle Installation Kit (see below) "VDS" Visual Diagnostics Lighted Smart Cords "Paint-Lock" Rust Proof Enclosure Heater "ON" Indicator Light Detailed Owners Manual & Wiring Diagram 1 Year Warranty

OPTIONS

Versi-Heat Remote Heater with 60" Cord Spaside Control

SUPPORTED PERIPHERALS AND CIRCUITS BY MODEL										
Model	Pump 1	Pump 2	Blower	Ozone	12V Light	H/C GFCI	Warranty			
CS6009-US1	2 SPD	N/A	YES	YES	YES	N/A	1 YEAR			
CS6009-US2	2 SPD	1 SPD	YES	YES	YES	N/A	1 YEAR			
CS6009-US1-HC	2 SPD	N/A	YES	YES	YES	YES	1 YEAR			
CS6009-US2-HC	2 SPD	1 SPD	YES	YES	YES	YES	1 YEAR			

SPASIDE CONTROL OPTIONS



3 Button Analog Spaside Control HQ PT# 34-0039A-S



4 Button Analog Spaside Control HQ PT# 34-0037A-S

Model

CS6009-US1/HC CS6009-US2/HC



3 Button Digital Spaside Control HQ PT# 34-0039D-S



4 Button Digital Spaside Control HQ PT# 34-0037D-S

All Hydro-Quip Air Control systems are spaside control ready.

INSTALLATION KIT (Included)

Kit Includes:

Component Cords

Air Transmitters

Air Tubing

2" Tailpieces w/Gaskets

12V Light Assembly



	REPLACEMENT PARTS FOR CS6000 AIR SERIES									
Thermostat	Timer	Heater Element(5.5kW)	PSI Switch	Heater Assy (15")						
34-0081	34-0033	12-0100-K	34-0178A	22-87B-S80-1FM3						
34-0081	34-0033	12-0100-K	34-0178A	22-87B-S80-1FM3						
	For a comple	ete list of parts, refer to ou	r Parts Catalog							

SYSTEM SPECIFICATIONS

ELECTRICAL INPUT SPECIFICATION: SINGLE PHASE,120/240VAC, 60HZ SYSTEM DIMENSIONS: 15"W x 11"H x 5"D

ELECTRICAL OUTPUT SPECIFICATION:

 CIRCUIT(S)
 MAXIMUM AMPS

 PUMP(S)
 13A

 BLOWER
 8A

 OZONE
 2A

 12V LIGHT
 1A

 HEATER
 23A

PACKAGING / SHIPPING: INDIVIDUAL (HQ STOCK) FOB CORONA, CA 92880

18 LBS

WARRANTY:

SHIPPING WEIGHT:



ES6000 Standard Series Air Equipment Systems



STANDARD FEATURES

1.375/5.5KW, 15" Heater Assembly
2 Speed Pump (various HP & voltages)
Blower, 1 HP, 120V
24hr Timer With Mode Switch
Full Range Thermostat
Spaside Receptacle
Installation Kit Included
"VDS" Visual Diagnostics
Lighted Smart Cords
"Paint-Lock" Rust Proof Enclosure
Heater "ON" Indicator Light
Detailed Owners Manual & Wiring Diagram
1 Year Warranty

OPTIONS

Spaside Control

Some Assembly Required

SUPPORTED PERIPHERALS AND CIRCUITS BY MODEL										
Model	Pump 1	Pump 2	Blower	Ozone	12V Light	H/C GFCI	Warranty			
ES6000-U	2 SPD	N/A	YES	YES	YES	N/A	1 YEAR			
ES6000-U2	2 SPD	1 SPD	YES	YES	YES	N/A	1 YEAR			
ES6000-U-HC	2 SPD	N/A	YES	YES	YES	YES	1 YEAR			
ES6000-U2-HC	2 SPD	1 SPD	YES	YES	YES	YES	1 YEAR			

See system component options chart below for pump and blower options

SPASIDE CONTROL OPTIONS EQUIPMENT SYSTEM COMPONENT OPTIONS CHART Option Code* Pump Voltage Blower Voltage 1 HP -A 1 HP 120 120 -B 1 HP 120 N/A N/A 3 Button Digital 3 Button Analog -C 1.5 HP 120 1 HP 120 **Spaside Control Spaside Control** -C5 1.5 HP 240 1 HP 120 HQ PT# 34-0039A-S HQ PT# 34-0039D-S -D 1.5 HP 120 N/A N/A -D5 1.5 HP 240 N/A N/A -E 2 HP 240 1 HP 120 -F 2 HP 240 N/A N/A -G 3 HP 240 1 HP 120 4 Button Analog 4 Button Digital 3 HP Spaside Control -H 240 N/A N/A **Spaside Control** 120 HQ PT# 34-0037A-S HQ PT# 34-0037D-S 4 HP 240 1 HP -K 4 HP 240 N/A N/A All Hydro-Quip Air Control systems are spaside control ready. *Add Option Code to end of ES Model Number

	REPLACEMENT PARTS FOR ES6000 AIR SERIES									
Model	Thermostat	Timer	Hi Limit	Heater Element (5.5kW)	PSI Switch	Heater Assy (15")				
ES6000-U/HC	34-0081	34-0033	34-0012	12-0100-K	34-0178	26-0071				
ES6000-U2/HC	34-0081	34-0033	34-0012	12-0100-K	34-0178	26-0071				
	1	For a comple	ete list of par	ts, refer to our Parts Catal	og					

SYSTEM SPECIFICATIONS

SHIPPING WEIGHT:

ELECTRICAL INPUT SPECIFICATION: SINGLE PHASE,120/240VAC, 60HZ **SYSTEM DIMENSIONS:** 21.5"W x 12"H x 15"D

ELECTRICAL OUTPUT SPECIFICATION:

 CIRCUIT(S)
 MAXIMUM AMPS

 PUMP(S)
 13A

 BLOWER
 8A

 OZONE
 2A

 12V LIGHT
 1A

 HEATER
 23A


PACKAGING / SHIPPING: INDIVIDUAL (HQ STOCK)
FOB CORONA, CA 92880
WARRANTY:

58.7 LBS

12V LIGHT 1A 1 YEAR LIMITED WARRANTY STANDARD - CONTACT YOUR HEATER 23A HYDRO-QUIP REPRESENTATIVE FOR MORE DETAILS



CS4000 Pump Mount Series Air "SLIDE" Control Systems



STANDARD FEATURES

"SLIDE" 1.375/5.5KW "L" Heater Assembly 24hr Timer With Mode Switch Full Range Thermostat Spaside Receptacle Installation Kit (see below) "VDS" Visual Diagnostics Lighted Smart Cords "Paint-Lock" Rust Proof Enclosure Heater "ON" Indicator Light Detailed Owners Manual & Wiring Diagram 1 Year Warranty

OPTIONS

Versi-Heat Remote Heater with 60" Cord Spaside Control

SUPPORTED PERIPHERALS AND CIRCUITS BY MODEL										
Model	Pump 1	Pump 2	Blower	Ozone	12V Light	H/C GFCI	Warranty			
CS4009-US1	2 SPD	N/A	YES	YES	YES	N/A	1 YEAR			
CS4009-US2	2 SPD	1 SPD	YES	YES	YES	N/A	1 YEAR			
CS4009-US1-HC	2 SPD	N/A	YES	YES	YES	YES	1 YEAR			
CS4009-US2-HC	2 SPD	1 SPD	YES	YES	YES	YES	1 YEAR			

SPASIDE CONTROL OPTIONS



"SLIDE" HEATER FEATURE!

3 Button Analog Spaside Control HQ PT# 34-0039A-S



4 Button Analog Spaside Control HQ PT# 34-0037A-S



3 Button Digital Spaside Control HQ PT# 34-0039D-S



4 Button Digital Spaside Control HQ PT# 34-0037D-S

All Hydro-Quip Air Control systems are spaside control ready.

INSTALLATION KIT (Included)

Kit Includes:

Component Cords

Air Transmitters

Air Tubing

2" Tailpieces w/Gaskets

12V Light Assembly



REPLACEMENT PARTS FOR CS4000 AIR SERIES Model Thermostat Timer Heater Element (5.5kW) **PSI Switch** "L" Heater Assy CS4009-US1/HC 34-0081 34-0033 12-0100-K 34-0178A 22-67B-S80-1FM3 CS4009-US2/HC 34-0081 34-0033 12-0100-K 34-0178A 22-67B-S80-1FM3 For a complete list of parts, refer to our Parts Catalog

SYSTEM SPECIFICATIONS

ELECTRICAL INPUT SPECIFICATION: SINGLE PHASE,120/240VAC, 60HZ SYSTEM DIMENSIONS: 17"W x 9.5"H x 7.5"D

ELECTRICAL OUTPUT SPECIFICATION:

 CIRCUIT(S)
 MAXIMUM AMPS

 PUMP(S)
 13A

 BLOWER
 8A

 OZONE
 2A

 12V LIGHT
 1A

 HEATER
 23A

SHIPPING WEIGHT: 18 LBS

PACKAGING / SHIPPING: INDIVIDUAL (HQ STOCK) FOB CORONA, CA 92880

WARRANTY:



ES4000 Pump Mount Series Air Equipment Systems





STANDARD FEATURES

1.375/5.5KW, "L" Heater Assembly 2 Speed Pump (various HP & voltages) Blower, 1 HP, 120V 24hr Timer With Mode Switch Full Range Thermostat

Spaside Receptacle Installation Kit Included "VDS" Visual Diagnostics Lighted Smart Cords

"Paint-Lock" Rust Proof Enclosure Heater "ON" Indicator Light

Detailed Owners Manual & Wiring Diagram

1 Year Warranty

OPTIONS

Spaside Control

SUPPORTED PERIPHERALS AND CIRCUITS BY MODEL										
Model	Pump 1	Pump 2	Blower	Ozone	12V Light	H/C GFCI	Warranty			
ES4000-U	2 SPD	N/A	YES	YES	YES	N/A	1 YEAR			
ES4000-U2	2 SPD	1 SPD	YES	YES	YES	N/A	1 YEAR			
ES4000-U-HC	2 SPD	N/A	YES	YES	YES	YES	1 YEAR			
ES4000-U2-HC	2 SPD	1 SPD	YES	YES	YES	YES	1 YEAR			

See system component options chart below for pump and blower options

SPASIDE CONTROL OPTIONS



Some Assembly Required

3 Button Analog Spaside Control HQ PT# 34-0039A-S



4 Button Analog Spaside Control HQ PT# 34-0037A-S

3 Button Digital Spaside Control HO PT# 34-0039D-S



4 Button Digital Spaside Control HQ PT# 34-0037D-S

All Hydro-Quip Air Control systems are spaside control ready.

EQUIPMENT SYSTEM COMPONENT OPTIONS CHART

Option Code*	Pump	Voltage	Blower	Voltage
-A	1 HP	120	1 HP	120
-B	1 HP	120	N/A	N/A
-C	1.5 HP	120	1 HP	120
-C5	1.5 HP	240	1 HP	120
-D	1.5 HP	120	N/A	N/A
-D5	1.5 HP	240	N/A	N/A
-E	2 HP	240	1 HP	120
-F	2 HP	240	N/A	N/A
-G	3 HP	240	1 HP	120
-H	3 HP	240	N/A	N/A
-J	4 HP	240	1 HP	120
-K	4 HP	240	N/A	N/A
	*4	Add Option Co	de to end of E	S Model Number

REPLACEMENT PARTS FOR ES4000 AIR SERIES

Model	Thermostat	Timer	Heater Element (5.5kW)	PSI Switch	"L" Heater Assy				
ES4000-U/HC ES4000-U2/HC	34-0081 34-0081	34-0033 34-0033	12-0100-K 12-0100-K	34-0178A 34-0178A	22-67B-S80-1FM3 22-67B-S80-1FM3				
	For a complete list of parts, refer to our Parts Catalog								

SYSTEM SPECIFICATIONS

ELECTRICAL INPUT SPECIFICATION: SINGLE PHASE,120/240VAC, 60HZ SYSTEM DIMENSIONS: 18"W x 15"H x 15"D

ELECTRICAL OUTPUT SPECIFICATION:

 CIRCUIT(S)
 MAXIMUM AMPS

 PUMP(S)
 13A

 BLOWER
 8A

 OZONE
 2A

 12V LIGHT
 1A

 HEATER
 23A

SHIPPING WEIGHT: 58.7 LBS

PACKAGING / SHIPPING: INDIVIDUAL (HQ STOCK) FOB CORONA, CA 92880

WARRANTY:



CS7000 Economy Series Air Control Systems



STANDARD FEATURES

120/240V Universal Models
1.0/4.0kW 13" Heater Assembly
24hr Timer with Mode Switch ("T" units)
Full Range Thermostat
Lightweight Aluminum Box
Spaside Receptacle
Installation Kit Included
Standard Smart Cords
Heater "ON" Indicator Light
Detailed Owners Manual & Wiring Diagram
1 Year Warranty

OPTIONS

120V/12V Light Kit w/Air Switch & Wall Fitting Option (see below)
Spaside Control

SUPPORTED PERIPHERALS AND CIRCUITS BY MODEL							
Model	Pump 1	Heater	Blower	Ozone	Voltage	15A GFCI	Warranty
CS7000-A-15A	2 SPD	1.0kW	YES	YES	120	YES	1 YEAR
CS7000T-A-15A	2 SPD	1.0kW	YES	YES	120	YES	1 YEAR
CS7000-A	2 SPD	1.0kW	YES	YES	120	NO	1 YEAR
CS7000T-A	2 SPD	1.0kW	YES	YES	120	NO	1 YEAR
CS7000-U	2 SPD	1.0/4.0kW	YES	YES	120/240	NO	1 YEAR
CS7000T-U	2 SPD	1.0/4.0kW	YES	YES	120/240	NO	1 YEAR

A = 120V only T = with Timer U = Universal

SPASIDE CONTROL OPTIONS



3 Button Analog Spaside Control HQ PT# 34-0039A-S



3 Button Digital Spaside Control HQ PT# 34-0039D-S

LIGHT KIT OPTIONS





Light Kit Assembly Options

PT# 37-0029-SM PT# 37-0031-SM
With Wall Fitting Kit Less Wall Fitting Kit

INSTALLATION KIT (Included)

Kit Includes:

Component Cords

Air Transmitters

Air Tubing

2" Tailpieces w/Gaskets



	REPLACEMENT PARTS FOR CS7000 AIR SERIES								
Model	Thermostat	Timer	Hi-Limt	Heater Element (4.0kW)	PSI Switch	Heater Assy (13")			
CS7000-A-15A	34-0030	N/A	34-0012	12-0102-K	34-0019-C	26-0070B-2			
CS7000T-A-15A	34-0030	34-0033	34-0012	12-0102-K	34-0019-C	26-0070B-2			
CS7000-A	34-0030	N/A	34-0012	12-0102-K	34-0019-C	26-0070B-2			
CS7000T-A	34-0030	34-0033	34-0012	12-0102-K	34-0019-C	26-0070B-2			
CS7000-U	34-0030	N/A	34-0012	12-0102-K	34-0019-C	26-0070B-2			
CS7000T-U	34-0030	34-0033	34-0012	12-0102-K	34-0019-C	26-0070B-2			
		For a com	plete list of	parts, refer to our Parts	Catalog				

SYSTEM SPECIFICATIONS

ELECTRICAL INPUT SPECIFICATION: SINGLE PHASE, 120/240VAC, 60HZ SYSTEM DIMENSIONS: 13"W x 9.25"H x 4.5"D

ELECTRICAL OUTPUT SPECIFICATION:

 CIRCUIT(S)
 MAXIMUM AMPS

 PUMP(S)
 13A

 BLOWER
 8A

 OZONE
 2A

 12V LIGHT
 1A

 HEATER
 23A

51012M BIMENOIONO: 10 W X 0.20 11 X 4.0 E

SHIPPING WEIGHT: 13 LBS

PACKAGING / SHIPPING OPTIONS: INDIVIDUAL (HQ STOCK) FOB CORONA, CA 92880

WARRANTY:



CS500 Series Air Control Systems





STANDARD FEATURES

1.125/4.5KW Heater in ABS Housing 24hr Timer with Mode Switch ("T" Models) Full Range Thermostat Installation Kit Included Lighted Smart Cords Heater "ON" Indicator Light Detailed Owners Manual & Wiring Diagram 1 Year Warranty

OPTIONS

120V/12V Light Kit w/Air Switch & Wall Fitting Option (see below)

SUPPORTED PERIPHERALS AND CIRCUITS BY MODEL								
Model	Pump 1(2SPD)	Voltage	15A GFCI	Blower	Ozone	Timer	Warranty	
CS500-A CS500T-A	120V 120V	120V 120V	YES N/A	YES YES	YES YES	NO YES	1 YEAR 1 YEAR	
CS500-C CS500T-C	240V 240V	120V 240V	YES N/A	YES YES	YES YES	NO YES	1 YEAR 1 YEAR	
CS500T-C9	240V	240V	N/A	YES	YES	YES	1 YEAR	

A = 120V only T = with Timer

LIGHT KIT OPTIONS





Light Kit Assembly Options

PT# 37-0029-SM PT# 37-0031-SM With Wall Fitting Kit Less Wall Fitting Kit

INSTALLATION KIT (Included)

Kit Includes:

Component Cords

Air Transmitters

Air Tubing

11/2" Tailpieces w/Gaskets



Model	Thermostat	Timer	Hi Limit	Heater Element (4.5kW)	PSI Switch	Heater Housing Assy
CS500-A	34-0030	N/A	34-0058	12-0010	34-0178	48-0014
CS500T-A	34-0030	34-0033	34-0058	12-0010	34-0178	48-0014
CS500-C	34-0030	N/A	34-0058	12-0010	34-0178	48-0014
CS500T-C	34-0030	34-0033	34-0058	12-0010	34-0178	48-0014
CS500T-C9	34-0030	34-0033	34-0058	12-0010	34-0178	48-0014

SYSTEM SPECIFICATIONS

ELECTRICAL INPUT SPECIFICATION: SINGLE PHASE, 120/240VAC, 60HZ SYSTEM DIMENSIONS: 14"W x 6"H x 6"D

ELECTRICAL OUTPUT SPECIFICATION:

 CIRCUIT(S)
 MAXIMUM AMPS

 PUMP(S)
 13A

 BLOWER
 8A

 OZONE
 2A

 12V LIGHT
 1A

 HEATER
 23A

SHIPPING WEIGHT: 16 LBS

PACKAGING / SHIPPING: INDIVIDUAL (HQ STOCK) FOB CORONA, CA 92880

WARRANTY:



ES8750 Outdoor Series Solid-State Equipment Systems



Some Assembly Required

Self Priming System

STANDARD FEATURES

M7™ Technology Equipped
5.5/11KW, 19.25" Heater Assembly
2 Speed Pump (various HP & Voltage)
60" P2 Cord Terminated 14/3
Outdoor Weather-tight Construction
Spaside With 50' Extension
Installation Kit
Smart-Freeze Protection
"Paint-Lock" Rust Proof Enclosure
Detailed Owners Manual & Wiring Diagram

OPTIONS

2 Year Warranty

In-House Control Panel RF Remote Control Auxiliary Spaside (HQ PT#34-0224)

	SUPPORTED PERIPHERALS AND CIRCUITS BY MODEL									
Model	Pump1 2SPD Included	Pump2	Pump3	Blower Included	Ozone	Heater	Light	Warranty		
ES8750-A	1.5 HP	1 or 2 SPD	1 SPD	1.5 HP	YES	11kW	12/120V	2 YEARS		
ES8750-B	2 HP	1 or 2 SPD	1 SPD	1.5 HP	YES	11kW	12/120V	2 YEARS		
ES8750-C	2.5 HP	1 or 2 SPD	1 SPD	1.5 HP	YES	11kW	12/120V	2 YEARS		
ES8750-D	1.5 HP	1 or 2 SPD	1 SPD	1.5 HP	YES	5.5kW	12/120V	2 YEARS		
ES8750-E	2 HP	1 or 2 SPD	1 SPD	1.5 HP	YES	5.5kW	12/120V	2 YEARS		
ES8750-F	2.5 HP	1 or 2 SPD	1 SPD	1.5 HP	YES	5.5kW	12/120V	2 YEARS		
ES8750-G	1.5 HP	1 or 2 SPD	1 SPD	1.5 HP	YES	N/A	12/120V	2 YEARS		
ES8750-H	2 HP	1 or 2 SPD	1 SPD	1.5 HP	YES	N/A	12/120V	2 YEARS		
ES8750-J	2.5 HP	1 or 2 SPD	1 SPD	1.5 HP	YES	N/A	12/120V	2 YEARS		

SPASIDE OPTIONS



In House Control Panel HQ PT#: 48-0197D Includes Receiver



Auxiliary Spaside HQ PT#: 34-0214-U



Spaside Control (Included) HQ PT#: 34-0213



Extension Cords
HQ PT# (50" Cord): 30-1014-50
HQ PT# (100" Cord): 30-1014-100



Single Button Auxiliary HQ PT#: 34-0224 (for Pump 3 Option)



Wireless RF Remote Kit HQ PT#: 48-0197A Includes Receiver

INSTALLATION KIT (Included)



Spaside Control w/ 7' Cord & 50' extension 60" Pump 2, cords Fittings w/Gaskets

REPLACE	MENT PARTS FOI	R ES8750 SOLID STA	ATE SERIES
Board	Spaside	Heater Element	Heater Ass

Model	Circuit Board	Spaside	Heater Element	Heater Assy (19.25")					
ES8750-A	33-0029A	34-0213	12-0100D-K (x2)	26-0054A-M7					
ES8750-C	33-0029A	34-0213	12-0100D-K (x2)	26-0054A-M7					
ES8750-D	33-0029A	34-0213	12-0100-K	26-0053-M7					
ES8750-F	33-0029A	34-0213	12-0100-K	26-0053-M7					
ES8750-G	33-0029A	34-0213	N/A	N/A					
ES8750-J	33-0029A	34-0213	N/A	N/A					
	For a complete list of parts, refer to our Parts Catalog								

SYSTEM SPECIFICATIONS

ELECTRICAL INPUT SPECIFICATION: SINGLE PHASE,240VAC, 60HZ **SYSTEM DIMENSIONS:** 36"W x 26"H x 18"D

ELECTRICAL OUTPUT SPECIFICATION:

 CIRCUIT(S)
 MAXIMUM AMPS

 PUMP(S)
 13A

 BLOWER
 8A

 OZONE
 2A

 CIRCULATION PUMP
 5A

 12V LIGHT
 1A

 HEATER
 23A/46A

SHIPPING WEIGHT: 101 LBS (2 Boxes)

PACKAGING / SHIPPING: INDIVIDUAL (HQ STOCK) FOB CORONA, CA 92880

WARRANTY:



ES8748 Outdoor Series Solid-State Equipment Systems



Some Assembly Required

Not A Self Priming System

STANDARD FEATURES

M7™ Technology Equipped
5.5/11KW, 19.25" Heater Assembly
2 Speed Pump (various HP & Voltage)
60" P2 Cord Terminated 14/3
Outdoor Weather-tight Construction
Spaside With 50' Extension
Installation Kit
Smart-Freeze Protection
"Paint-Lock" Rust Proof Enclosure
Detailed Owners Manual & Wiring Diagram
2 Year Warranty

OPTIONS

In-House Control Panel RF Remote Control Auxiliary Spaside (HQ PT#34-0224)

/lodel	Pump 1 2SPD Included	Pump 2	Pump 3	Blower Included	Ozone	Heater	Light	Warranty
S8748-A	1.5 HP	1 or 2 SPD	1 SPD	1.5 HP	YES	11kW	12/120V	2 YEARS
ES8748-B	2 HP	1 or 2 SPD	1 SPD	1.5 HP	YES	11kW	12/120V	2 YEARS
ES8748-C	3 HP	1 or 2 SPD	1 SPD	1.5 HP	YES	11kW	12/120V	2 YEARS
ES8748-D	1.5 HP	1 or 2 SPD	1 SPD	1.5 HP	YES	5.5kW	12/120V	2 YEARS
ES8748-E	2 HP	1 or 2 SPD	1 SPD	1.5 HP	YES	5.5kW	12/120V	2 YEARS
ES8748-G	1.5 HP	1 or 2 SPD	1 SPD	1.5 HP	YES	N/A	12/120V	2 YEARS
ES8748-H	2 HP	1 or 2 SPD	1 SPD	1.5 HP	YES	N/A	12/120V	2 YEARS
ES8748-J	3 HP	1 or 2 SPD	1 SPD	1.5 HP	YES	N/A	12/120V	2 YEARS

SPASIDE OPTIONS



In House Control Panel HQ PT#: 48-0197D Includes Receiver



Auxiliary Spaside HQ PT#: 34-0214-U



Spaside Control (Included) HQ PT#: 34-0213



Extension Cords HQ PT# (50" Cord): 30-1014-50 HQ PT# (100" Cord): 30-1014-100



Single Button Auxiliary HQ PT#: 34-0224 (for Pump 3 Option)



Wireless RF Remote Kit HQ PT#: 48-0197A Includes Receiver

INSTALLATION KIT (Included)



Spaside Control w/ 7' Cord & 50' extension 60" Pump 2, cords
Fittings w/Gaskets

REPLACEMENT PARTS FOR ES8748 SOLID STATE SERIES

Model	Circuit Board	Spaside	Heater Element	Heater Assy (19.25")				
ES8748-A	33-0029A	34-0213	12-0100D-K (x2)	26-0054A-M7				
ES8748-C	33-0029A	34-0213	12-0100D-K (x2)	26-0054A-M7				
ES8748-D	33-0029A	34-0213	12-0100-K `´	26-0053-M7				
ES8748-F	33-0029A	34-0213	12-0100-K	26-0053-M7				
ES8748-G	33-0029A	34-0213	N/A	N/A				
ES8748-J	33-0029A	34-0213	N/A	N/A				
	For a complete list of parts, refer to our Parts Catalog							

SYSTEM SPECIFICATIONS

ELECTRICAL INPUT SPECIFICATION: SINGLE PHASE, 240VAC, 60HZ SYSTEM DIMENSIONS: 36"W x 26"H x 18"D

ELECTRICAL OUTPUT SPECIFICATION:

 CIRCUIT(S)
 MAXIMUM AMPS

 PUMP(S)
 13A

 BLOWER
 8A

 OZONE
 2A

 CIRCULATION PUMP
 5A

 12V LIGHT
 1A

 HEATER
 23A/46A

SHIPPING WEIGHT: 80 LBS (2 Boxes)

PACKAGING / SHIPPING: INDIVIDUAL (HQ STOCK) FOB CORONA, CA 92880

WARRANTY:



CS8700 Outdoor Series Solid State Control Systems





STANDARD FEATURES

M7™ Technology Equipped 5.5/11KW, 19.25" Heater Assembly Outdoor Weather-Tight Construction Wall Mount Brackets Spaside With 50' Extension Installation Kit Included Smart-Freeze Protection "Paint-Lock" Rust Proof Enclosure Detailed Owners Manual & Wiring Diagram 2 Year Warranty

OPTIONS

In-House Control Panel RF Remote Control Kit Auxiliary Spaside (HQ PT#34-0224)

SUPPORTED PERIPHERALS AND CIRCUITS BY MODEL Model Pump1 Pump2 Pump3 **Blower** Ozone Heater Liaht Warranty 1 or 2 SPD 1 SPD 12/120V CS8700-A 1 or 2 SPD YES YES 11kW 2 YEARS CS8700-B 1 or 2 SPD 1 or 2 SPD 1 SPD YES YES 5.5kW 12/120V 2 YEARS 1 or 2 SPD CS8700-C 1 or 2 SPD 1 SPD YES YES N/A 12/120V 2 YEARS



In House Control Panel Includes Receiver



Auxiliary Spaside HQ PT#: 34-0214-U

Model CS8700-A

CS8700-B CS8700-C

SPASIDE OPTIONS



Spaside Control (Included) HQ PT#: 34-0213



Extension Cords HQ PT# (50" Cord): 30-1014-50 HQ PT# (100" Cord): 30-1014-100



Single Button Auxiliary HQ PT#: 34-0224 (for Pump 3 Option)



Wireless RF Remote Kit HQ PT#: 48-0197A Includes Receiver

INSTALLATION KIT (Included)



Kit Includes: Spaside Control w/ 7' Cord & 50' extension Fittings w/Gaskets

REPLACI	REPLACEMENT PARTS FOR CS8/00 SOLID STATE SERIES							
Circuit Board	Spaside	Heater Element	Heater Assy (19.25")					
33-0029A	34-0213	12-0100D-K (x2)	26-0054A-M7					
33-0029A	34-0213	12-0100-K	26-0053-M7					
33-0029A	34-0213	N/A	N/A					

SYSTEM SPECIFICATIONS

For a complete list of parts, refer to our Parts Catalog

DEDLA CEMENT DADTO FOR COURSE OF STATE CERIES

ELECTRICAL INPUT SPECIFICATION: SINGLE PHASE, 240VAC, 60HZ **SYSTEM DIMENSIONS:** 12"W x 19.5"H x 12"D

ELECTRICAL OUTPUT SPECIFICATION:

CIRCUIT(S) **MAXIMUM AMPS** PUMP(S) 13A **BLOWER** 8A **OZONE** 2A CIRCULATION PUMP 5A 12V LIGHT 1A **HEATER** 23A/46A


SHIPPING WEIGHT: 32.5 LBS

PACKAGING / SHIPPING: INDIVIDUAL (HQ STOCK) FOB CORONA, CA 92880

WARRANTY:



HEATMAX Series Remote Heater System



The Hydro-Quip HEATMAX series heater is our basic "heater in a box" unit. When all you need is heat, this is the most practical and user friendly unit in the industry. 5.5kW OR 11kW for new and existing applications where a full 2" high flow free standing heater is needed.

STANDARD FEATURES

5.5 or 11KW, "U" Heater Assembly
2.25" High Flow U-Shaped Heater Design
Stainless Steel Heater Housing
Full Range Thermostat
High Limit and Pressure Switch Protected
2" or 1½" Plumbing Connections
Weather-Tight Construction
Heater "ON" Indicator Light
"Paint-Lock" rust proof enclosure
Detailed Owners Manual & Wiring Diagram
2 Year Warranty

OPTIONS

Various Heater Wattages

AVAILABLE MODELS

Model	Voltage	Wattage	Warranty
HEATMAX RHS 5.5 HEATMAX RHS 11	240 240	5.5kW 11kW	2 YEARS 2 YEARS

REPLACEMENT PARTS FOR HEATMAX SERIES

Model	Thermostat	Hi-Limit	Heater Element	PSI Switch	"U" Heater Assy
HEATMAX 5.5	34-0030	34-0012	12-0100-K	34-0178	26-0082
HEATMAX 11	34-0030	34-0012	12-0100-K (X2)	34-0178	26-0082A
TIEATMAX TI	04-0000	34-0012	12-0100-1(1/2)	04-0170	20-0002A

SYSTEM SPECIFICATIONS

ELECTRICAL INPUT SPECIFICATION: SINGLE PHASE, 240VAC, 50/60HZ **PACKAGING / SHIPPING:** INDIVIDUAL (HQ STOCK) FOB CORONA, CA 92880

SYSTEM DIMENSIONS: 15"W x 12"H x 4"D WARRANTY:

2 YEARS LIMITED WARRANTY STANDARD - CONTACT YOUR
SHIPPING WEIGHT: 19 LBS HYDRO-QUIP REPRESENTATIVE FOR MORE DETAILS



Universal SILENT AIRE Blower Series



Hydro-Quip introduces our *SILENT AIRE* blower series. This innovative, compact and sleek design make this the most practical blower on the market today. With its quiet operation and universal cord configurations*, the *SILENT AIRE* blower was engineered to perform above all the rest!

STANDARD FEATURES

New Innovative Design Quiet Operation Compact and Lightweight Thermally Protected Motor Available In Various Voltages and HP's 42" Amp Adapter Cord 6" Universal Cord/Plug 1 Year Warranty

OPTIONS

Various Cord Configurations Built in Air Switch Built in Heater Export models

AVAILABLE MODELS

Model	Volts	НР	Speed	Amps	Warranty
AS-610U	120	1.0	1	4.4	1 YEAR
AS-620U	240	1.0	1	2.4	1 YEAR
AS-810U	120	1.5	1	5.8	1 YEAR
AS-820U	240	1.5	1	3.1	1 YEAR

CORD OPTIONS



SYSTEM SPECIFICATIONS

ELECTRICAL INPUT SPECIFICATION: SINGLE PHASE,120/240VAC, 60HZ

SYSTEM DIMENSIONS: 8"W x 5"H x 9.25"L

SHIPPING WEIGHT: 4 LBS

PACKAGING / SHIPPING OPTIONS:

INDIVIDUAL (HQ STOCK)

BULK PACK 12 INDIVIDUALLY BOXED OR LOOSE IN MASTER CARTON

FOB CORONA, CA 92880

WARRANTY:



Universal *RITE-FIT* Heater Assembly




Hydro-Quip introduces our new universal *RITE FIT* heater assembly. This innovative design allows you to use the *RITE FIT* heater to replace many on the market today. Save on inventory and save space, no need to carry so many different models when you only need one, the *RITE FIT* universal heater!

STANDARD FEATURES

Universal 15" Length (others available) 4.0, 4.5, & 5.5kW Elements Available Adjustable Mounting and Grounding Studs Adjustable Sensor Cover Plate Multiple Pressure Switch Ports Flush Mount Pressure Switch Port Plugs 2" Tailpieces and Gaskets 12" Ground Wire Individually Boxed

AVAILABLE MODELS

Model	kW	Size	Length	Warranty
48-1540-RP	4.0	2"	15"	1 YEAR
48-1545-RP	4.5	2"	15"	1 YEAR
48-1555-RP	5.5	2"	15"	1 YEAR



SYSTEM SPECIFICATIONS

ELECTRICAL INPUT SPECIFICATION: SINGLE PHASE,120/240VAC, 60HZ

4 LBS

PACKAGING / SHIPPING:

INDIVIDUAL (HQ STOCK) FOB CORONA, CA 92880

SYSTEM DIMENSIONS: 15"W x 2.25"H

SHIPPING WEIGHT:

WARRANTY:

1 YEAR LIMITED WARRANTY STANDARD - CONTACT YOUR HYDRO-QUIP REPRESENTATIVE FOR MORE DETAILS

Call (951) 273-7575 Visit us at hydroquip.com



Pure Heat Series 7" Tee Style Bath Heater



STANDARD FEATURES

Low Profile Design Versatile Compact Size Automatic Smart Thermostat Intelligent High-Limit Pressure Switch Activated Heater "On" Indicator Light Stainless Steel Heater Housing Detailed Owners Manual & Installation Guide Installation Kit Included (see below) 2 Year Warranty

OPTIONS

240 Volt, Export & Domestic

SUPPORTED PERIPHERALS AND CIRCUITS BY MODEL									
MODEL	PSI**	Volts	Wattage	Size	Fittings (Included)	Warranty			
PH100-10UP PH100-15UP PH202-20UP	YES YES YES	120 120 240	1000 1500 2000	1.5" 1.5" 1.5"	1.5" & 1"SOC, 1"SPIG 1.5" & 1"SOC, 1"SPIG 1.5" & 1"SOC, 1"SPIG	2 YEARS 2 YEARS 2 YEARS			

^{**}PSI = Pressure Switched





1.5" x 1.5" SOC PT# 42-0015 (X2)



1.5" x 1" SOC PT# 42-0031 (X2)



1.5" x 1" SPIG PT# 42-0031-A (X2)




1.5" Ridged Gasket PT# 60-0017 (X2)



3' Copper Wire PT# 32-0019-S



1.5" Flat Gasket PT# 61-0011 (1)



SYSTEM SPECIFICATIONS

ELECTRICAL INPUT SPECIFICATION: SINGLE PHASE, 120VAC, 50/60HZ

ELECTRICAL OUTPUT SPECIFICATION:

VOLTS WATTAGE MAXIMUM AMPS 120 1000 8.3A 120 1500 12.5A 240 2000 8.3A **HEATER DIMENSIONS:** 7"W x 5"H x 4"D

SHIPPING WEIGHT: 1.75 LBS

PACKAGING / SHIPPING: INDIVIDUAL (HQ STOCK) FOB CORONA, CA 92880

WARRANTY:



Pure Heat Series 7" Inline Style Bath Heater



STANDARD FEATURES


Versatile Compact Size
Automatic Smart Thermostat
Intelligent High-Limit
Pressure & Vacuum Switch Activated
Heater "On" Indicator Light
Stainless Steel Heater Housing
Detailed Owners Manual & Installation Guide
Installation Kit Included (see below)
2 Year Warranty

OPTIONS

240 Volt, Export & Domestic

SUPPORTED PERIPHERALS AND CIRCUITS BY MODEL									
MODEL	PSI/VAC**	Volts	Wattage	Size	Fittings (Included)	Warranty			
PH101-65UP	PSI	120	650	1.5"	1.5" & 1"SOC, 1" SPIG	2 YEARS			
PH101-10UP	PSI	120	1000	1.5"	1.5" & 1"SOC, 1" SPIG	2 YEARS			
PH101-15UP	PSI	120	1500	1.5"	1.5" & 1"SOC, 1" SPIG	2 YEARS			
PH203-20UP	PSI	240	2000	1.5"	1.5" & 1"SOC, 1" SPIG	2 YEARS			
PH301-15UP	PSI	120	1500	2"	2" SOC & 2"SPIG	2 YEARS			
PH101-10UV	VAC	120	1000	1.5"	1.5" & 1"SOC	2 YEARS			
PH101-15UV	VAC	120	1500	1.5"	1.5" & 1"SOC	2 YEARS			
PH301-15UV	VAC	120	1500	2"	2" SOC & 2" SPIG	2 YEARS			

^{**}PSI = Pressure Switched VAC = Vacuum Switched



SYSTEM SPECIFICATIONS

ELECTRICAL INPUT SPECIFICATION: SINGLE PHASE,120VAC, 50/60HZ

ELECTRICAL OUTPUT SPECIFICATION:

VOLTS	WATTAGE	MAXIMUM AMPS
120	650	5.3A
120	1000	8.3A
120	1500	12.5A
240	2000	8.3A

PH301 7"W x 4.75"H x 3.5"D

PACKAGING / SHIPPING: INDIVIDUAL (HQ STOCK)

FOB CORONA, CA 92880

PH101

7"W x 4"H x 3"D

1.5 LBS

WARRANTY:

HEATER DIMENSIONS:

SHIPPING WEIGHT:



Amperage & Ohms Measurements Kilowatts **Watts** Voltage **Amps Ohms** 11(dual) 11000 240 45.8 5.24 11000 11 (single) 240 43.6 5.5 8000 240 33.3 7.21 5.5 5500 240 22.9 10.4 4500 12.8 4.5 240 18.75 4 4000 240 16.7 14.4 3 3000 240 12.5 19.2 2.5 2500 240 10.4 23.04 2 2000 240 8.3 28.8 1.5 1500 120 12.5 9.6 1000 120 14.4 1 8.3 0.65 650 120 22.15 5.4

Unit Weights and Unit Conversions

1 cubic foot of water weighs 62.4 pounds 1 cubic foot of water equals 7.5 gallons 1 gallon of water weighs 8.35 pounds

Multiply By To Get Gallons of Water 8.35 Pounds of Water Pounds of Water 27.65 Cubic Inches Gallons 231 Cubic Inches 0.001341 Watts Horse Power Volte Watte Amps

Fahrenheit and Celsius Conversions

To convert Fahrenheit temperature into Celsius:

- Begin by subtracting 32 from the Fahrenheit number
- Divide the answer by 9
- Then multiply that answer by 5

To convert Celsius temperatures into Fahrenheit:

- Begin by multiplying the Celsius temperature by 9
- · Divide the answer by 5
- Now add 32

PSI Conversions

MultiplyByTo getInches of Water0.03612625PSIPSI27.6807Inches of Water

PSI settings for control systems below water level



Current Capacity (Amps) of Wire

\A/: O:	Amperes					
Wire Size	Copper	Aluminum				
14	20	-				
12	25	20				
10	30	25				
8	40	30				
6	55	40				
4	70	55				

TECHNICAL FACTS SHEET

Ohm's Law

Ohm's Law is made from 3 mathematical equations that shows the relationship between electric voltage, current and resistance.

V = I x R (Voltage = Current multiplied by Resistance) R = V / I (Resistance = Voltage divided by Current) I = V / R (Current = Voltage divided by Resistance)

Knowing any two of the values of a circuit, one can determine (calculate) the third, using Ohm's Law.



The Wheel:

Volts V (on top of the divided line)
Amps I (lower left below the divided line)
Resistance R (lower right below the divided line)
X represents the (multiply by sign)

To use, just cover the known quantity you need with your minds eye and what is left is the formula to find the unknown.

Temperature Rise

Based on Gallons and Heater Wattage TEMPERATURE RISE METHOD

V = Volume of water

kW = Kilowatt rating of heater

DT = Temperature rise in °F Per Hour

 $DT = kW \times 411$ This formula is used to determine the temperature rise

V a kilowatt rating will achieve.

 $kW = V \times 8.3 \times DT$ This formula is used to determine the kilowatt required to achieve a desired temperature rise.

1.5kW	Gallons of Water	102	123	155	205	250	305
	Water Temperature Rise in °F Per Hour*	6.0	5.0	4.0	3.0	2.5	2.0
5.5kW	Gallons of Water	113	126	151	205	281	375
5.5KVV	Water Temperature Rise in °F Per Hour*	20.0	18.0	15.0	11.0	8.0	6.0
11kW	Gallons of Water	181	226	302	450	900	1120
	Water Temperature Rise in °F Per Hour*	25.0	20.0	15.0	10.0	5.0	4.0

^{*}Temperature rise as listed above does not account for heat loss - actual heat up times may vary

Spa Blower Information

<u>HORSEPOWER</u>					
To Get This	Divide This	By This			
Horsepower	Kilowatts	0.75			
Horsepower	Watts	746			
Horsepower	Torque (ft.lbs.) x RPM	33000			
Horsepower	Torque (ft.lbs.) x RPS	550			
Horsepower required to pump water at a given rate to given height,	GPM x TDH (ft.)	3960			
assuming 100% eff. AKA Water Horsepower	GPM x TDH (psi)	103000			
Brake hp	Water hp	Pump eff.			

SIZING CHART

Blower Motor Size	Volts	Amps	Maximum In. of Water Depth
1 HP	120	4.4	35"
1 ½ HP	120	5.8	45"
1 HP	240	2.4	30"
1 ½ HP	240	3.1	40"

SIZING FORMULA

Measure total depth of water in spa (not total spa depth)

Add 1" water for each 10ft. of air pipe Add ½" water for each 90 deg. elbow

Compare your total with maximum inches of water column and select that size or the next size higher blower than your total, in your selected voltage.




PRODUCT INFORMATION

GFCI Breaker Connection / Electrical Wiring Information


The number one cause for repeated tripping of a GFCI breaker on a new install is that the breaker has been incorrectly wired. The Illustration above shows a typical installation. Note that the Neutral "pigtail" is connected at the neutral bus bar and the Neutral wire coming from the spa control system is connected directly to the breaker. Connecting the Neutral wire from the spa control system to the Neutral bus bar will cause the repeat tripping.

Warning - The illustration is meant to be used as a guide ONLY. This does not in any way supercede any manufacturers installation instructions.




Circuit & Breaker Rating	15A	20A	30A	40A	50A	60A	70A	80A
Maximum Amps	12A	16A	24A	32A	40A	48A	56A	64A
Minimum Wire Size	14	12	10	8	6	4	4	4

Universal Control System Wiring Instructions




Molded Receptacle Color Chart RED YELLOW Pump 1 Ozone (2 Speed) **BROWN VIOLET** Pump 2 Blower (2 Speed) **PINK** BLUE Pump 2 Circ Pump (1 Speed) **ORANGE** WHITE **Heater Control** Firemans Switch LT VIOLET **GREEN Heater Control** Auxiliary (Solid State)



Line 2 to Neutral

Line 1 to Neutral



Line 1 to Line 2



HYDROQUIP*
THE SMART CHOICE*

510A N. Sheridan Street, Corona CA. 92880

Telephone: (951) 273-7575 Fax: (800) 332-7190

www.hydroquip.com

85-0310 REV.30 8/16/12 JL/EP