

## BEFORE YOU PAINT...

### WHAT PAINT TO USE

#### Ramuc Pool Paint COMPATIBILITY CHART

PAINT TYPE	EPOXY		RUBBER				ACRYLIC
Product Name	EP Hi Build	EP	Type A	Pro 2000	Ultra Pro 2000	Type A2	DS
<b>BARE SURFACES</b>							
Concrete	★★★	★★	★★★	★★	★★	★★	★
Plaster	★★★	★★	★★★	★★	★★	★★	★
Fiberglass	★★★	★★	☒	☒	☒	☒	☒
Gunite	★★★	★	☒	☒	☒	☒	☒
Marcite	★★★	★★	★★★	★★	★★	★★	★
<b>SURFACE WITH EXISTING COATING</b>							
Chlorinated Rubber	☒	☒	★★★	★★	★★	★★★	★★
Synthetic Rubber	☒	☒	☒	☒	☒	★★★	★★
Epoxy	★★★	★★	☒	☒	☒	☒	★
Acrylic	☒	☒	☒	☒	☒	☒	★★★
<b>DURABILITY</b>							
Chemical Resistance	★★★	★★★	★★	★	★	★★	★
Stain Resistance	★★★	★★★	★★★	★	★	★★★	★
Life Expectancy							
*Residential	up to 8 years	up to 4 years	up to 4 years	up to 2 years	up to 2 years	up to 4 years	up to 2 years
*Commercial	up to 5 years	up to 3 years	up to 3 years	1 Season	1 Season	up to 3 years	1 Season

\*Water chemistry, surface prep and use, etc. will effect the life of all paints.






RATING: GOOD ★ BETTER ★★ BEST ★★★ Do Not Use ☒

To Determine the existing coating on your pool, send a sample chip for analysis to RAMUC Pool Paint

### HOW MUCH PAINT TO USE

#### Estimating the Quantity of Paint Required:

Below are the standard pool configurations together with corresponding simple formulas to calculate the square footage of your pool. Keep in mind that the amount of paint you will need depends on whether your pool surface is rough or smooth. The square foot coverage of each type of paint will determine how much product you will need.

				
<b>RECTANGLE</b>	<b>ROMAN</b>	<b>LAZY "L"</b>	<b>KIDNEY</b>	<b>OVAL</b>
Length x Width x 1.65 =Total Square Feet	Length x Width x 1.5 =Total Square Feet	Length x Width x 1.6 =Total Square Feet	Length x Width x 1.65 =Total Square Feet	Length x Width x 1.55 =Total Square Feet

### SURFACE PREPARATION

#### Clean & Prep Solution™

Used to clean and degrease while simultaneously dissolving mineral deposits, increasing porosity for good adhesion on surfaces prior to painting.



- **Mix** Clean and Prep with water according to package directions. Ratio is contingent upon type of surface to be cleaned.
- **Dampen** surface with water
- **Apply** mixed solution with garden sprayer
- **Scrub** thoroughly until foaming stops
- **Flush** with clear water and hose. Continue until foam is completely gone and water runs clear. (Sprayer is not recommended)

NOTE: do not apply to concrete that has already been sealed or stained.

[www.ramucpoolpaint.com](http://www.ramucpoolpaint.com)